



Installation Methods: Ashlar, 1/3 Drop, Herringbone

### Product Specifications

|                     |                                               |
|---------------------|-----------------------------------------------|
| Wear Layer          | 20 mil                                        |
| Thickness           | 2.5mm                                         |
| Finish / Coating    | Enhanced UV Urethane w/ Ceramic Micro Bead    |
| Pattern Repeat      | Random Wood                                   |
| Edge Treatment      | None                                          |
| Dimensions:         | 6" x 48"                                      |
| Standard Adhesive   | Commercialon Premium Modular and LVT Adhesive |
| Backing Class       | Commercial Grade                              |
| Commercial Traffic  | Heavy Commercial                              |
| Standard Warranties | 15 Year LVT                                   |

### Packaging

|                           |                          |
|---------------------------|--------------------------|
| Sq.ft. per piece / carton | 2 / 36                   |
| Weight per piece / carton | 2.05 (lbs) / 36.97 (lbs) |
| Pieces per box            | 18                       |
| Boxes per pallet          | 60                       |

### Special Technologies


|                     |     |
|---------------------|-----|
| Added Antimicrobial | Yes |
|---------------------|-----|

### Environmental Specifications & Tests


|                    |                                            |
|--------------------|--------------------------------------------|
| Indoor Air Quality | FloorScore® Certified                      |
| LEED v4            | Contributes to IAQ: Low Emitting Materials |
| End of Life        | 100% Recyclable                            |
| Radiant Panel      | Class 1                                    |
| ADA Compliance     | Compliant For Accessible Routes            |

|                                    |        |
|------------------------------------|--------|
| ASTM F2055 (Size and Tolerance)    | Passes |
| ASTM F386 (Thickness)              | Passes |
| ASTM F1914 (Residual Indentation)  | Passes |
| ASTM F137 (Flexibility)            | Passes |
| ASTM F2199 (Dimensional Stability) | Passes |
| ASTM F925 (Chemical Resistance)    | Passes |
| ASTM F1514 (Resistance to Heat)    | Passes |
| ASTM F1515 (Resistance to Light)   | Passes |
| ASTM E648 (Critical Radiant Flux)  | Passes |
| ASTM E662 (Optical Smoke Density)  | Passes |
| ASTM C1028 (Slip Resistance)       | Passes |
| ASTM F970 (Static Load)            | Passes |

### Colorways




001 Manzanita




002 Chamis



003 Scrub Oak



004 Sumac



005 Sage Brush