KOHLER, Faucets

Single-function handshower, 1.75 gpm **K-27052-G**

Features

- Single-function handshower delivers a full, consistent spray, regardless of water pressure
- Full Coverage with Katalyst™ air-induction technology delivers a drenching spray experience, ideal for rinsing shampoo from hair
- MasterClean™ sprayface features an easy-to-clean surface that withstands mineral buildup and maximizes spray performance
- Optimized sprayface for maximum performance
- 1.75 gpm (6.6 lpm) maximum flow rate at 80 psi (5.5 bar)
- Part of the Occasion bathroom faucet and accessory collection
- Requires shower hose (sold separately)
- This product can help a building earn Water Efficiency points in LEED® Green Building Rating System

Material

- Premium material construction for durability and reliability
- KOHLER finishes resist corrosion and tarnishing

Technology

 Katalyst® air-induction technology infuses water with air, creating bigger drops for a more powerful spray

Installation

- G 1/2 inlet and outlet
- Bracket or slidebar required for wall-mount installation
- Deck-mount holder required for deck-mount installation

Recommended Products/Accessories

K-9514 60" Shower Hose

K-8593 72" Shower Hose

K-26309 Wall-mount handshower holder

K-26310 Wall-mount handshower holder with supply elbow and check valve

K-26312 32-1/8" slidebar

K-26313 40" slidebar

K-26314 32" deluxe slidebar with integrated water supply

K-23723 Faucet cleaner





Codes/Standards

ASME A112.18.1/CSA B125.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC)

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color Code Description

Color tiles intended for reference only.


	•
CP	Polished Chrome
SN	Vibrant® Polished Nickel
AF	Vibrant® French Gold
BN	Vibrant® Brushed Nickel
BV	Vibrant® Brushed Bronze
BL	Matte Black
2MB	Vibrant® Brushed Moderne
TT	Brass Vibrant Titanium






Occasion®

Single-function handshower, 1.75 gpm **K-27052-G**





Technical Information

All product dimensions are nominal.

Spout:

Handshower rated max flow: 1.75 gal/min (6.6 l/min)

Notes

For use with automatic compensating valves rated at 1.75 gal/min (6.6 l/min) or less.

