

Ensemble™ Acoustical Drywall Ceiling & Ensemble™ RAP Acoustical Drywall Ceiling United States Gypsum Company

Final Assembly: Walworth, Wisconsin, USA

Life Expectancy: 30+ Year(s)

End of Life Options: Salvageable/Reusable in its Entirety,

Landfill (100%)

Ingredients:

Calcium sulfate dihydrate; Mineral wool fiber; Cellulose; Water; Calcium Carbonate; Starch; Mineral wool; Styrene-based polymer; Adhesive; Titanium dioxide; Polyvinyl acetate; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Glass, oxide, chemicals; Steel; Stucco; Calcined kaolin; Polyethylene Terephthalate; Propanoic acid, 2-methyl-, monoester with 2,2,4-trimethyl-1,3-pentanediol; Aluminum hydroxide; Dextrose; Attapulgite; 1,3,5-Triazine-1,3,5(2H,4H,6H)-triethanol; Metaphosphoric acid (H3P3O9), trisodium salt

Living Building Challenge Criteria:

I-13 Red List:

■ LBC Red List Free % Disclosed: 100% at 100ppm

☐ LBC Red List Approved VOC Content: 12.8 g/L

□ Declared

I-10 Interior Performance: Not Compliant
I-14 Responsible Sourcing: Not Applicable

USG-0048 EXP. 01 NOV 2025

Original Issue Date: 2018