USG PROSTONE™ SM

SOUTHARD, OK

DESCRIPTION

TYPICAL PHYSICAL PROPERTIES

STORAGE AND USAGE

PRODUCT INFORMATION

See usg.com for the most up-to-date product information.

CAUTION

When mixed with water, this material hardens and becomes very hot sometimes quickly. DO NOT attempt to make acast enclosing any part of the body using this material. Dust from mixing may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Use only in a well-ventilated area, wear a NIOSH/MSHA-approved respirator. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If on skin: Wash with plenty of water. If swallowed and/or irritation persists, call physician. For more information call Product Safety: 800-507-8899 or see the SDS at usa, com

KEEP OUT OF REACH OF CHILDREN.

TRADEMARKS

The trademarks USG, PROSTONE, IT'S YOUR WORLD. BUILD IT., the USG logo, the design elements and colors and related marks are trademarks of USG Corporation or its affiliates.

NOTE

The information in this document is subject to change without notice. USG Corp. assumes no responsibility for any errors that may inadvertently appear in this document. Consult your USG Company sales office or representative for information.

NOTICE

We shall not be liable for incidental or consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instruction or for other than the intended use. Our liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing to us within thirty (30) days from date it was or reasonably should have been discovered.

SAFETY FIRST!

Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read SDS and literature before specification

USG Prostone™ SM is a smooth, white dental mortar that offers good workability and great reproduction detail for a variety of dental stone applications. Easy to use, USG Prostone SM's set time can be altered by the use of accelerators or retarders. It is water soluble – there is no need for organic solvents for cleanup. If information for a specific use is needed, please contact your local USG Sales Representative for further assistance.

Test Consistency	30 lbs. water/100 lbs. product (13.6 kg water/45 kg product)
Hand Mix Vicat Set, at 30 cc	18 - 24 minutes
Color	White
% Passing — 100 mesh	99.00% - 100%
Compressive Strength, One Hour After Set (minimum) at 20 cc	7000 psi (48.3 MPa)
Compressive Strength, Dry (minimum) at 20 cc	15,000 psi (103.4 MPa)
% Expansion (maximum)	0.25%

NOTE The *Typical Physical Properties* in the above table were achieved under controlled laboratory conditions with freshly produced material, results may vary.

When properly used, USG Prostone SM is easy to work with. Keep indoors at temperatures between 65 °F – 75 °F (18 °C – 24 °C) and 45% – 55% RH. Do not stack more than two pallets high. Keep from drafts. Rotate stock. USG Prostone SM should be used within six months of the manufacturing date located on the package. Always follow handling and use directions and safety warnings on the package.

800 USG.4YOU 800 (874.4968) usg.com

Manufactured by United States Gypsum Company 550 West Adams Street Chicago, IL 60661 IG5211-USA-ENG/7-18 © 2018 USG Corporation and/or its affiliates. All rights reserved. Printed in U.S.A.

