




Installation Method



Ashlar

Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Textured Woodgrains 4.5 mm **Color** Antique Oak **Collection** Level Set Collection

| Product Specifications                |                                                                                    |
|---------------------------------------|------------------------------------------------------------------------------------|
| Product Number                        | A004                                                                               |
| Product Construction                  | High Performance Luxury Vinyl Tile                                                 |
| Class / ASTM F1700                    | Class III Printed Vinyl Plank                                                      |
| Wear Layer Thickness                  | 22 mil                                                                             |
| Total Thickness                       | 4.5 mm                                                                             |
| Backing Class                         | Commercial Grade                                                                   |
| Finish                                | Ceramor™                                                                           |
| Nominal Dimensions                    | 25 cm x 1 m (9.845 in x 39.38 in)                                                  |
| Performance Specifications            |                                                                                    |
| IIC Sound Rating                      | (ASTM E492-09) 64 IIC                                                              |
| Slip Resistance                       | (ASTM D2047) >0.55 wet/dry, ADA Compliant                                          |
| Static Load Limit                     | (ASTM F970) 1500 psi                                                               |
| Flexibility                           | (ASTMF137) Passes                                                                  |
| Resistance to Heat                    | (ASTM F1514) Passes                                                                |
| Resistance to Light                   | (ASTM F1515) Passes                                                                |
| Radiant Flux                          | (ASTM E648) Class I                                                                |
| Smoke Density                         | (ASTM E-662) ≤ 450                                                                 |
| Size & Squareness                     | (ASTM F2055) Passes, +/- 0.016 in. per linear foot                                 |
| Thickness                             | (ASTM F386) Passes                                                                 |
| Residual Indentation                  | (ASTM F1914) Passes                                                                |
| Resistance to Chemicals               | (ASTM F925) Passes                                                                 |
| Health + Environmental Specifications |                                                                                    |
| Embodied Carbon (Cradle to Gate)      | 9.2 Kg CO <sub>2</sub> /M <sup>2</sup>                                             |
| Total Recycled Content (Pre Consumer) | 39%                                                                                |
| Indoor Air Quality                    | <a href="#">GREENGUARD Gold FloorScore® SCS-FS-04366</a><br>CDPH 01350 compliant   |
| Material Composition                  | Free of Ortho Phthalates, Added Formaldehyde and Heavy Metal Stabilizers           |
| Disclosure of Environmental Impacts   | <a href="#">Environmental Product Declaration</a>                                  |
| Disclosure of Product Ingredients     | <a href="#">Health Product Declaration</a>                                         |
| Environmental Certifications          | NSF/ANSI 332, Meets Certification Guidelines                                       |
| LEED v4                               | Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR                       |
| Packaging                             |                                                                                    |
| Quantity per Carton                   | 26.91 ft <sup>2</sup> (2.5 m <sup>2</sup> )                                        |
| Pieces per Carton                     | 10                                                                                 |
| Weight Per Carton                     | 40 lb (18 kg )                                                                     |
| Cartons per Pallet                    | 40                                                                                 |
| Pallets per Truckload                 | 20                                                                                 |
| Technical Information                 |                                                                                    |
| Installation                          | <a href="#">Interface LVT Installation Guidelines</a>                              |
| Maintenance                           | <a href="#">Recommended Interface LVT Maintenance Guidelines</a>                   |
| Reclamation                           | Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada) |
| Warranty                              | <a href="#">15 Year Standard LVT Warranty</a>                                      |
| Installation Method                   | Ashlar<br>Herringbone                                                              |