



Rockfon Artic®
Rockfon

Final Assembly: Marshall County, Mississippi, USA; Cigacice, Poland
Life Expectancy: 50 Year(s)
Embodied Carbon: 2.17 kg CO2eq 
Declared Unit: 1 m2
End of Life Options: Recyclable (80%), Landfill (20%)

Ingredients:

Stone wool, biosoluble; Fiberglass; Water; Limestone; Syrups, hydrolyzed starch; Glucose; Phenol, polymer with formaldehyde¹; Polyvinyl alcohol; Caprolactam; Laurolactam; Dodecanedioic acid, polymer with decanedioic acid, hexahydro-2H-azepin-2-one, 1,6-hexanediamine and hexanedioic acid; Hexamethylenediamine; Hexanedioic acid; Calcium carbonate; Urea; Urea, polymer with formaldehyde¹; Titanium dioxide; Residual oils (petroleum), solvent-dewaxed; Undisclosed (< 0.3%)²; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate; Clay; Talc; Lubricating oils (petroleum), C>25, solvent-extd., deasphalted, dewaxed, hydrogenated; Undisclosed (< 0.1%)²; Undisclosed (< 0.1%)²; Undisclosed (< 0.1%)²; Undisclosed (< 0.1%)²; n-Butyl acrylate; Styrene; Cellulose, ethyl ether

¹LBC Temp Exception RL-009 - Formaldehyde
²LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- | | |
|---|------------------------------|
| <input type="checkbox"/> LBC Red List Free | % Disclosed: 99.3% at 100ppm |
| <input checked="" type="checkbox"/> LBC Red List Approved | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared | |

I-10 Interior Performance: CDPH Standard Method v1.2-2017
I-14 Responsible Sourcing: Not Applicable

RXL-0012
EXP. 01 FEB 2026
Original Issue Date: 2021