




Rockfon® Education Plus Rockfon

Final Assembly: Marshall County, Mississippi, USA
Life Expectancy: 50 Year(s)
Embodied Carbon: 2.96kg CO2-Eq 
Declared Unit: 1 m2 of installed ceiling tile
End of Life Options: Recyclable (89%), Landfill (11%)

Ingredients:

Stone wool, biosoluble; Aluminum hydroxide; Fiberglass; Syrups, hydrolyzed starch; Phenol, polymer with formaldehyde¹; Limestone; Water; Polyvinyl alcohol; Undisclosed (< 0.7%)²; Urea; Caprolactam; Laurolactam; Dodecanedioic acid, polymer with decanedioic acid, hexahydro-2H-azepin-2-one, 1,6-hexanediamine and hexanedioic acid; Hexamethylenediamine; Hexanedioic acid; Urea, polymer with formaldehyde¹; Residual oils (petroleum), solvent-dewaxed; Titanium dioxide; 2-Propenoic acid, butyl ester, polymer with ethenyl acetate

¹LBC Temp Exception RL-009 - Formaldehyde
²LBC Temp Exception RL-004b - Proprietary Ingredients in Declare

Living Building Challenge Criteria: Compliant

I-13 Red List:

- ☐ LBC Red List Free
- ☒ LBC Red List Approved
- ☐ Declared
- % Disclosed: 99.3% at 100ppm

VOC Content: Not Applicable

I-10 Interior Performance: CDPH Standard Method v1.2-2017
I-14 Responsible Sourcing: Not Applicable

RXL-0015
EXP. 01 JAN 2026
Original Issue Date: 2021