



Collective Pursuit

Product Specification

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Tarkett Collective Pursuit plank and tile is a high-performance solution in a non-PVC option, rivaling luxury tile.

1.2. **Manufacturer:**

Tarkett North America Phone (800) 899-8916
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkett.com
E-mail: info@tarkett.com

1.3. **Proprietary Product Description:**

1.3.2. **Construction:** Collective Pursuit is constructed on a Non-PVC polymeric calendared layer, with non-PVC print film and wear layer. Collective Pursuit is protected from scratching, abrasion, scuffing, and staining by a durable polyurethane top coat.

1.3.3. **Styles:**

- **Finish:** Matte Polyurethane
- **Embossing:** Standard
- **Edge treatment:** Micro Bevel*
* Open Path & Confluent Path: Square Edge
- **Overall thickness:** 0.10" (2.5 mm)
- 6 collections (Refer to chart below)

2. PERFORMANCE AND TECHNICAL DATA

- 2.1 **Dimensional Stability** (ASTM F2199): Passes
- 2.2 **Flexibility** (ASTM F137): Passes
- 2.3 **Static Load Recovery** (ASTM F970): 250 psi, $\leq 0.005''$
- 2.4 **Residual Indentation** (ASTM F1914): Passes (10 min under 140 lbs. with 0.178" flat foot)
- 2.5 **Slip Resistance** (ASTM D2047): SCOF ≥ 0.5
- 2.6 **Resistance to Heat** (ASTM F1514): $\Delta\Sigma \leq 8.0$
- 2.7 **Resistance to Light** (ASTM F1515): $\Delta\Sigma \leq 8.0$
- 2.8 **Chemical Resistance** (ASTM F925): Passes
- 2.9 **Fire Resistance** (ASTM E648/NFPA 253): CRF ≥ 0.45 watts/cm², Class I
- 2.10 **Smoke Density** (ASTM E662): ≤ 450
- 2.11 **CAN/ULC S102.2:** FSR 15 / SDC 55

3. INSTALLATION

3.1 See Tarkett Collective Pursuit Installation Instructions for complete details.

3.2 **Adhesives:**

- **Tarkett 975 Two-Part Urethane Adhesive**
1/32x1/16x1/32 U-notch trowel
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett 996 Two-Part Epoxy Adhesive**
1/32x1/16x1/32 U-notch trowel
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour/Event/Latitude Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com
Contact Technical Support at (800) 899-8916 or E-mail:
Resilient.TechnicalSupport@Tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. LIMITED WARRANTY

Limited 15-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkett.com



Collective Pursuit

Product Specification

	SIZES AVAILABLE		
	7.2x48	12x24	9x48
Confluent Path 16 tiles / 48 sq.ft. per box Vertical Ashlar			•
Kyoto Stone (SKS): 20 tiles / 48 sq.ft. per box Quarter Turn, Vertical Ashlar, Horizontal Ashlar		•	
Monteverde Oak (SMV): 20 tiles / 48 sq.ft. per box Unidirectional, Herringbone	•		
North Island Oak (SNI): 20 tiles / 48 sq.ft. per box Unidirectional, Herringbone	•		
Open Path 16 tiles / 48 sq.ft. per box Vertical Ashlar			•
Umbria Oak (SBK): 20 tiles / 48 sq.ft. per box Unidirectional, Herringbone	•		

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com

www.tarkett.com

© 2024 Tarkett USA Inc. 07/2024