

RollSmart™

Fast-Drying Vinyl Flooring Adhesive

Speed to Occupancy

- RollSmart is recommended under all of Tarkett's 2mm vinyl sheet flooring
- Eliminates trowel marks and spray pattern telegraphing
- Fast-drying formulation
- Approved for immediate heat welding
- Designed for use under hospital beds
- Increased moisture limits
- No traffic restrictions after installation – foot traffic and rolling loads
- Increased coverage per gallon
- Solvent-free adhesive
- Supports recycling of flooring
- Speed to occupancy significantly decreases the downtime of those critical spaces such as operating rooms
- Maintenance can be performed immediately after installation when sheet material is heat welded
- Allows for immediate occupancy

RollSmart

RollSmart is a solvent-free, easy-to-apply adhesive specifically formulated for installing the following Commercial LVT and vinyl sheet products*:

Vinyl Sheet		Luxury Vinyl Tile	
Accent	iQ Eminent Unisense	iQ Optima®	Contour®
Accent Flourish™	iQ Granit™ Sense	Melodia®	Event†
Aria®	iQ Granit	Performa®	iD Latitude™
iQ® Eminent™	Granit Safe.T	Standard Plus	

*Not approved for Homogeneous Tile, Acoustic Sheet, or SD Sheet and Tile products.

RollSmart flooring adhesive is an environmentally friendly, non-toxic and non-flammable intelligent adhesive option enabling immediate occupancy, an important benefit for healthcare, education, retail and other environments where foot traffic and rolling traffic are prevalent.

The adhesive is applied using a 3/8" nap paint roller and dries quickly to facilitate fast installation times. RollSmart eliminates trowel marks telegraphing and is approved for use under hospital beds.

Technical Data	Standards	RollSmart Flooring Adhesive
Adhesive Type		Acrylic
Appearance		Light Blue
Odor		Sweet mild odor
Flash Point		> 212°F
NFPA 704 Flammability Rating		0 - Non-flammable
Storage		Store between 65-85°F (18-30°C)
Shelf Life		2 years if stored at recommended temperatures in unopened container
Open Time		10-20 minutes depending on jobsite conditions
Working Time		Up to 4 hours
VOC Content		0 gm/L
Foot traffic, rolling traffic, and furniture placement permitted		Immediately after installation
pH Tolerance ASTM F710		7.0-10.0 pH
Substrate Moisture Tolerance	ASTM F2170 ASTM F1869	95% RH 8 lbs. per 1,000 ft. 2/24 hrs.
Underfloor heating systems embedded in concrete		Yes
Please visit www.tarkett.com for the most updated specifications, installation and maintenance instructions.		



1 gal – 297038074
4 gal – 297038073

COVERAGE: 350'-400' per gallon

All flooring types listed porous & non-porous surfaces

3/8" Nap Paint Roller; not to exceed 400 sq. ft. per gallon when applied to 10-14 mil thickness per wet film thickness gauge included with each pail.



Tarkett North America

30000 Aurora Road, Solon, Ohio 44139
800.248.2878 | tarkett.com

ON THE COVER

iQ Granit 234 Warm Light Grey
iQ Eminent 883 Sand
iQ Eminent Unisense 928 Dusty Sand

©Tarkett North America 10/2023