

1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Performa heterogeneous commercial flooring designed for heavy commercial interiors. With contemporary visuals, stylish designs of wood and stone, 25 mil wear layer, and a nitrogen cured polyurethane coating.

1.1. **Manufacturer:**

Tarkett North America Phone: (800) 899-8916
30000 Aurora Rd.
Solon, Ohio 44139
Web: www.tarkett.com

1.2. **Proprietary Product Description:**

1.3.1. **Construction:** Performa has a PUR reinforced wearlayer composed of 90% binder content, with a polyurethane reinforced (PUR) construction to minimize maintenance.

1.3.2. **Styles:**

- Overall thickness: 0.080" (2.0 mm)
- Wear layer thickness: 25 mil (0.64 mm)
- Surface treatment: Nitrogen cured PU
- Pattern: Wood & Stone
- Packaging: Available in 6 ft. (1.83 m) and 12ft. (3.67 m) wide by 75' (22.9 m) long

2. PRODUCT PERFORMANCE AND TECHNICAL DATA

2.1. **Sheet material** meets ASTM F 1303, Type I, Grade 1, Class B performance sheet vinyl floorcovering with backing

2.2. **Heat Stability by Color Change** (ASTM F 1514): $\Delta E \leq 8$

2.3. **Light Stability by Color Change** (ASTM F 1515): $\Delta E \leq 8$

2.4. **Flexibility** (ASTM F 137): Passes

2.5. **Chemical Resistance** (ASTM F925): Passes

2.6. **Static coefficient of friction** (ASTM D 2047): ≥ 0.5

2.7. **Static Load Limit** (ASTM F 970): $250 \text{ psi} \leq 0.005''$

- ***Modified 2000 psi:** $\leq 0.005''$

2.8. **Acoustical** (ASTM E2179): $\Delta IIC \geq 8$

2.9. **Flammability** (Flooring Radiant Panel): ASTM E 648, Class 1

2.10. **CAN/ULC S102.2:** FRS 225 / SDC 275

3. INSTALLATION

3.1 See heterogeneous sheet flooring installation instructions for complete details.

3.2. **Adhesives:**

- **Tarkett 925 Adhesive Coverage:**

Porous Substrate: 250-300 sq. ft./gal.

Non-porous Substrate: 250-300 sq. ft. per gallon

- **Tarkett 975 Two-Part Polyurethane Adhesive Coverage:**

Porous & Non-porous Substrate: 225-250 sq. ft. per gallon

- **Tarkett 996 Two-Part Epoxy Adhesive Coverage:**

Porous & Non-porous Substrate: 225-250 sq. ft. per gallon

- **Tarkett RollSmart Adhesive Coverage:**

Approximate Coverage:

Porous & Non-porous Substrate: 350 - 400 sq. ft. per gallon
(3/8" Nap Paint Roller used with a paint tray)

- **Tarkett Cold Weld Liquid Coverage:**

175 – 200 lin. ft. per 4.5 oz. tube

4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Acczent Maintenance Instructions for complete maintenance details.

6. TECHNICAL SERVICES

Visit us on the web at www.tarkett.com

Contact Technical Support at (800) 899-8916 or E mail: Resilient.TechnicalSupport@tarkett.com

Samples: Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

7. LIMITED WARRANTY

Limited 10-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

*Static loads greater than 250 psi fall outside of the scope of the ASTM F970 Test Method. Modified static load testing does not provide information related to the long-term exposure and the residual indentation of an installed floorcovering system which includes the subfloor, adhesive, underlayment, and cementitious patching/leveling compounds. Residual indentation(s) may remain visible in any resilient flooring installation, however, overhead lighting, natural lighting and the application of a gloss floor finish may increase the appearance.

Tarkett North America

Technical Services Department
30000 Aurora Road
Solon, Ohio 44139
800.899.8916
info@tarkettna.com
www.tarkett.com