

## 1. PROPRIETARY PRODUCT/MANUFACTURER

1.1. **Proprietary Product:** Tarkett Event+ Series Luxury vinyl floor covering with Techtonic™ coating that delivers extreme durability and ease of maintenance in high traffic environments. Suitable for commercial working environments and office.

### 1.2. Manufacturer:

Tarkett North America      Phone (800) 899-8916  
30000 Aurora Rd.  
Solon, Ohio 44139  
Web: [www.tarkett.com](http://www.tarkett.com)  
E-mail: [info@tarkett.com](mailto:info@tarkett.com)

### 1.3. Proprietary Product Description:

1.3.1. **Construction:** Tarkett Event+ Series is constructed with 30 mil wear layer reinforced with a Techtonic finish in numerous wood and stone patterns to provide an affordable, natural looking flooring that is stocked for faster turnaround times.

### 1.3.2. Styles:

(See below for standard embossing, sizing availability, and packaging info)

- **Finish:** Techtonic
- **Wear layer thickness:** 30 mil (0.76 mm)
- **Edge treatment:** Square Edge (SE), optional Slight Bevel (SB)
- **Overall thickness:** 0.120" (3.0 mm)
- 32 Wood / 24 Stone patterns

## 2. PERFORMANCE AND TECHNICAL DATA

- 2.1 Meets ASTM F1700, Class III, Type B performance
- 2.2 **Static Load Limit** (ASTM F970): 250 psi,  $\leq 0.005''$
- 2.3 **Residual Indentation** (ASTM F1914): Passes
- 2.4 **Static Coefficient of Friction** (ASTM D2047):  $\text{SCOF} \geq 0.5$
- 2.5 **Dimensional Stability** (ASTM F2199): Passes
- 2.6 **Resistance to Heat** (ASTM F1514):  $\Delta\Sigma \leq 8.0$
- 2.7 **Resistance to Light** (ASTM F1515):  $\Delta\Sigma \leq 8.0$
- 2.8 **Chemical Resistance** (ASTM F925): Passes
- 2.9 **Fire Resistance** (ASTM E648):  $\text{CRF} \geq 0.45 \text{ watts/cm}^2$  NFPA, Class I
- 2.10 **CAN/ULC S102.2:** FSV 105 / SDV 340

## 3. INSTALLATION

3.1 See Tarkett Luxury Vinyl Plank installation instructions for complete details.

### 3.2 Adhesives:

- **Tarkett RollSmart Adhesive:**  
Coverage: 350 – 400 sq. per gallon  
(3/8" Nap Paint Roller used with a paint tray)
- **Tarkett 959HM High Moisture Substrate Adhesive**  
Porous Substrate: 125-150 sq. ft. per gallon  
Non-porous: 250-300 sq. ft. per gallon
- **Tarkett 975 Two-Part Urethane Adhesive**  
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon
- **Tarkett 996 Two-Part Epoxy Adhesive**  
Porous & Non-Porous Substrate: 225-250 sq. ft. per gallon

## 4. AVAILABILITY AND COST

Available through authorized Tarkett distributors nationwide.

## 5. MAINTENANCE

72 hours after installation is completed, initial maintenance procedures must be implemented in accordance with manufacturer's requirements. Refer to Tarkett Contour/Event/Latitude/Resolve Maintenance Instructions for complete maintenance details.

## 6. TECHNICAL SERVICES

Visit us on the web at [www.tarkett.com](http://www.tarkett.com)  
Contact Technical Support at (800) 899-8916 or E-mail:  
[Resilient.TechnicalSupport@Tarkett.com](mailto:Resilient.TechnicalSupport@Tarkett.com)

**Samples:** Submittal samples for verification and approval available upon request from Tarkett. Samples shall be submitted in compliance with the requirements of the contract documents. Accepted and approved samples shall constitute the standard materials which represent materials installed on the project.

## 7. LIMITED WARRANTY

Limited 20-year warranty. For complete details, contact Tarkett or an authorized Tarkett distributor.

### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
[info@tarkettna.com](mailto:info@tarkettna.com)

[www.tarkett.com](http://www.tarkett.com)



Event+

## Product Specification

### STANDARD EMBOSSING AND SIZE AVAILABILITY:

#### Woods Installation Methods:

6x36, 6x48 – Herringbone, Unidirectional

#### Stones Installation Methods:

18x18, 36x36 – Vertical Ashlar, Horizontal Ashlar, Quarter-Turn  
12x24 – Vertical Ashlar

#### Abstract Installation Methods:

18x18 – Vertical Ashlar, Horizontal Ashlar, Quarter-Turn  
12x24 – Vertical Ashlar

WOOD	Natural Grain (NG)	Third Grain (TG)	Rustic (RU)
<b>Classic Plank (PECK) 6x36</b>			
3305, 3307, 3308, 3309	STD		
3321		STD	
<b>Classic Plank (PECK) 6x48</b>			
11223	STD		
<b>Crafted Plank (PECF) 6x48</b>			
All colors <b>except 11212, 11213</b>	STD		
11212, 11213		STD	
<b>Heritage Plank (PEHP) 6x36</b>			
3350, 3354			STD
GW29		STD	
GW38	STD		
<b>Heritage Plank (PEHP) 6x48</b>			
11219, 11220, 11221, 11222			STD

ABSTRACTS	Frost (FR)	Quarry (QU)
<b>Melange (PEME) 18x18</b>		
All colors		STD
<b>Texterran (PETE) 12x24</b>		
All colors	STD	

STONE	Frost (FR)	Rock (RK)	Quarry (QU)
<b>Travertine (PETR) 18x18</b>			
7211			STD
<b>Travertine (PETR) 12x24</b>			
11195	STD		
<b>Slate (PESL) 12x24</b>			
All colors		STD	
<b>Urban Stone (PEUS) 18x18</b>			
2100, 2101, 2104, 2105		STD	
<b>Urban Stone (PEUS) 12x24</b>			
11199, 11200, 11201, 11202, 11203			STD
<b>Urban Stone (PEUS) 36x36</b>			
11204, 11205, 11206			STD
<b>Quartzite (PEQZ) 18x18</b>			
All colors			STD

### PACKAGING INFORMATION:

	Size	Pcs Per Carton	Sqft. Per Carton	Lbs. Per Carton	Cartons Per Pallet
Tile	12" x 12" (30.48 x 30.48 cm)	45	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	54
	12" x 18" (30.48 x 45.72 cm)	30	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	45
	12" x 24" (30.48 x 60.96 cm)	18	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	72
	12" x 36" (30.48 x 91.44 cm)	15	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	45
	18" x 18" (45.72 x 45.72 cm)	20	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	60
	18" x 36" (45.72 x 91.44 cm)	10	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	40
	9" x 36" (22.86 x 91.44 cm)	20	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	60
	36" x 36" (91.44 x 91.44 cm)	10	90 (8.4 m <sup>2</sup> )	90 (40.8 kg)	20
Planks	4" x 36" (10.16 x 91.44 cm)	45	45 (4.2 m <sup>2</sup> )	45 (20.4 kg)	40
	6" x 36" (15.24 x 91.44 cm)	24	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	66
	6" x 48" (15.24 x 121.92 cm)	18	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	72
	7.2" x 48" (18.29 x 121.92 cm)	15	36 (3.3 m <sup>2</sup> )	36 (16.3 kg)	60

#### Tarkett North America

Technical Services Department  
30000 Aurora Road  
Solon, Ohio 44139  
800.899.8916  
info@tarkettna.com

[www.tarkett.com](http://www.tarkett.com)

© 2024 Tarkett USA Inc. 01/2024