



# Adagio® Adagio High CAC

## MINERAL FIBER SMOOTH PANEL

The Adagio line provides a white, clean, monolithic ceiling visual. Design with products in the Symphony® f line for more complex acoustical solutions.

### Features & Benefits

- Unique composite panel with optimal sound absorption and attenuation
- Fiberglass layer provides exceptional sound absorption and acoustic comfort (0.80-0.90 NRC)
- Offers highly effective sound containment
- Can enhance space privacy compliance (assists with HIPAA requirements in healthcare spaces)
- Exceeds FGI guidelines for cleanability and acoustic performance
- Wash tested to 1,000 cycles with no sign of wear
- 30-Year System Warranty when installed with CertainTeed suspension systems

### Attributes



SAG RESISTANT



BIOSHIELD®  
MOLD/MILDEW  
RESISTANT



WASHABLE W/  
SANITIZING  
CHEMICALS



LR 0.90



RECYCLED  
CONTENT

## LEED® v4

RECYCLED CONTENT		
ADAGIO	15%	
	PRE: 14%	POST: 1%
ADAGIO HIGH CAC	51%	
	PRE: 38%	POST: 13%




- ✓ EA: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.




# Adagio®, Adagio High CAC

## MINERAL FIBER SMOOTH PANEL

### Adagio


Adagio			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Trim											
	NRC .90	1662-IOF-1	Panels	24 x 24 x 1-1/2	0.90	36	15%	8	32	45	20
		1660-IOF-1	Panels	24 x 48 x 1-1/2	0.90	38	15%	4	32	45	16
Reveal											
	NRC .90	1662B-IOF-1	Panels	24 x 24 x 1-1/2	0.90	36	15%	8	32	45	20
		1660B-IOF-1	Panels	24 x 48 x 1-1/2	0.90	38	15%	4	32	45	16
Narrow Reveal											
	NRC .90	1662F-IOF-1	Panels	24 x 24 x 1-1/2	0.90	36	15%	8	32	45	20
		1660F-IOF-1	Panels	24 x 48 x 1-1/2	0.90	38	15%	4	32	45	16

### Adagio High CAC

Adagio High CAC			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Trim											
	NRC .80	1672-IOF-1	Panels	24 x 24 x 1-1/2	0.80	40	51%	8	32	45	20
		1670-IOF-1	Panels	24 x 48 x 1-1/2	0.80	42	51%	4	32	45	16
Reveal											
	NRC .80	1672B-IOF-1	Panels	24 x 24 x 1-1/2	0.80	40	51%	8	32	45	20
		1670B-IOF-1	Panels	24 x 48 x 1-1/2	0.80	42	51%	4	32	45	16
Narrow Reveal											
	NRC .80	1672F-IOF-1	Panels	24 x 24 x 1-1/2	0.80	40	51%	8	32	45	20


CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

### Accessories


ADAGIO ACCESSORIES	PRODUCT NAME	PIECES/CARTON	USE
	1400-SEL-1	Fiberglass Edge Sealant	1
			For re-sealing cut edges; 1 quart container




## Edge Details




Trim  
9/16" EZ Stab  
Elite Narrow




Trim  
15/16" EZ Stab  
Classic




Reveal  
15/16" EZ Stab  
Classic



Narrow Reveal  
9/16" EZ Stab  
Elite Narrow



Narrow Reveal  
9/16" EZ Stab  
Bolt Slot



Narrow Reveal  
9/16" EZ Stab  
Tier Drop

## Physical Data

### MATERIAL

Composite - Mineral Fiber + Fiberglass

### FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

### ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type XX, Pattern G

ASTM E1264-23: Type XX, Pattern G

### MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

### MAINTENANCE

Clean panel using a sponge/cloth dampened with water and mild liquid detergent solution. Do not soak panel. Cleanable with sanitizing chemicals.

### WARRANTY

10-year 104/90 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at [certainteed.com/warranty](https://certainteed.com/warranty).



## CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM  
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](https://certainteed.com)