

Cashmere® Style Edge Cashmere Customline

MINERAL FIBER TEXTURED PANEL

Two lightly textured mineral fiber panels; one with face scoring for visual impact, and one with highly decorative edge detail options.

Features & Benefits

- Fine texture with highly decorative edge detail options
- Upscale appearance
- 3 Customline options with clean, face scoring
- Environmental Product Declaration (EPD) available for this product
- Health Product Declaration (HPD) available for this product
- USDA Certified Biobased content at 98%
- **Style-Edge:** 30-Year System Warranty when installed with CertainTeed suspension systems

Attributes



SAG RESISTANT



BIOSHIELD®
MOLD/MILDEW
RESISTANT



EMISSION
COMPLIANT
CERTIFIED



LR 0.83



RECYCLED
CONTENT
33 - 44%

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



HPD AVAILABLE



DeclareSM

Living Building Challenge Red List Free®

DeclareSM is a service mark of The International Living Future Institute.

LEED® v4





RECYCLED CONTENT	70%	
	PRE: 68%	POST: 2%
✓	MR: PBT Source Reduction (Healthcare)	
✓	EQ: Low-Emitting Materials	
✓	EQ: Daylight	
✓	MR: Material Ingredients (HPDs)	
✓	MR: Sourcing Raw Materials	
✓	MR: Environmental Product Declarations (EPDs)	
✓	MR: Construction and Demolition Waste Management Planning	

LEED® is a registered trademark of the U.S. Green Building Council.



Cashmere® Style Edge, Cashmere Customline

MINERAL FIBER TEXTURED PANEL

Cashmere Style Edge

Cashmere Style Edge			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Tier Narrow Reveal (9/16" grid only)											
	NRC .60	CMTS-124	Panels	24 x 24 x 3/4	0.60	35	70%	14	56	61	16
		CMTS-412	Panels	24 x 24 x 3/4	0.60	35	70%	14	56	61	16
Tier Reveal (15/16" grid only)											
	NRC .60	CMTS-124-1516	Panels	24 x 24 x 3/4	0.60	35	70%	14	56	61	16
		CMTS-412-1516	Panels	24 x 24 x 3/4	0.60	35	70%	14	56	61	16
Fluted Reveal (9/16" grid only)											
	NRC .60	CMF-124	Panels	24 x 24 x 3/4	0.60	31	70%	14	56	52	16
Ogee Reveal (9/16" grid only)											
	NRC .60	CMO-124	Panels	24 x 24 x 3/4	0.60	31	70%	14	56	52	16

Cashmere Customline

Cashmere Customline			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Reveal											
	NRC .60	CDS-224	Panels	24 x 48 x 3/4	0.60	35	70%	8	64	64	16
		CDS-448	Panels	24 x 48 x 3/4	0.60	35	70%	8	64	64	16
		CDS-812	Panels	24 x 48 x 3/4	0.60	35	70%	8	64	64	16
Narrow Reveal											
	NRC .60	CDSN-224	Panels	24 x 48 x 3/4	0.60	35	70%	8	64	64	16
		CDSN-812	Panels	24 x 48 x 3/4	0.60	35	70%	8	64	64	16

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990

Style Edge



Tier Reveal Edge (Style Edge)




Fluted Edge (Style Edge)




Ogee Edge (Style Edge)


Edge Details




Fluted Reveal
9/16" EZ Stab
Elite Narrow




Ogee Reveal
9/16" EZ Stab
Elite Narrow




Tier Reveal
9/16" EZ Stab
Elite Narrow



Tier Reveal
15/16" EZ Stab
Classic



Reveal Beveled
15/16" EZ Stab
Classic



Narrow Reveal
Beveled (Customline)
9/16" EZ Stab
Elite Narrow

Style Edge Scoring Options




24 x 24
(CMTS 412, CMTS 412-1516)


Customline Scoring Options



24 x 48
224



24 x 48
448



24 x 48
812

Physical Data

MATERIAL

Mineral Fiber

FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type III, Form 2, Pattern F

ASTM E1264-23: Type A, Form A1.2, Pattern F

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

INSTALLATION CONSIDERATION

Product is lot sensitive. Differing manufacturing dates should not be mixed in a single ceiling or unbroken area.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for added mold and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment.

WARRANTY

10-year 104/90 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.

WARRANTY (CUSTOMLINE)

1-year Limited Warranty



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 certainteed.com