

Ecophon® Akusto™Wall C Super G

FIBERGLASS TEXTURED WALLS

Akusto Wall C Super G fiberglass wall panel features an impact resistant surface.

Features & Benefits

- High impact resistance
- Use as a complement and/or alternative to acoustical ceiling panels for excellent acoustical performance within a space
- Moisture resistant
- Available in white only

Attributes



MOLD/MILDEW RESISTANT INHERENT



EMISSION COMPLIANT CERTIFIED



LR 0.78



WASHABLE

LEED® v4

RECYCLED CONTENT	53%			
	PRE: 0%	POST: 53%		

- MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-emitting Material
- ✓ MR: Sourcing Raw Materials
- MR: Environmental Product Declarations (EPDs)
- MR: Construction and Demolition Waste Management Planning
- ✓ MR: Material Ingredients (C2C)

LEED* is a registered trademark of the U.S. Green Building Council.

CERTIFICATIONS & PRODUCT DECLARATIONS





EPD AVAILABLE



Ecophon® Akusto™ Wall C Super GFIBERGLASS TEXTURED WALLS

Colors



White

Akusto™ Wall C Super G		COLOR	DIMENSIONS MM (IN.)	NRC	LR	RECYCLED CONTENT	PIECES/ CARTON	SQ. M (FT.)/ CARTON	LBS./ CARTON	
Wall Panel										
NRC .95		3557 7729	White	2700 x 600 x 40 (≈ 106 x 24 x 1-1/2)	0.95	0.78	53%	4	21.3 (≈ 70)	71
	NRO									

Edge Details



Kerfed Edge

Accessories

AKUSTO WALL C TE	XONA ACCESSORIES	PRODUCT NAME	PIECES/ CARTON	USE
	2630 0214	Connect Fixing Bracket	260	For direct fixing of Connect WP Profile to structure; Not recommended for installations requiring impact-resistance
	2631 1050	Connect WP Space Bar (Galvanized)	10	For use in conjunction with WP Profile when Akusto Wall C panels are installed vertically
	2631 1051	Connect WP Profile Connect (White 03)	8	Installed on walls and provides channel into which Akusto Wall C panels are inserted; direct-attached when installation requires impact-resistance
	2631 1052	Connect WP Profile (Natural 02)	8	Installed on walls and provides channel into which Akusto Wall C panels are inserted; direct-attached when installation requires impact-resistance
	2631 1074	Connect WP Profile (Black 01)	8	Installed on walls and provides channel into which Akusto Wall C panels are inserted; direct-attached when installation requires impact-resistance
	2631 1057	Connect WP External Corner (White 03)	4	Used in conjunction with WP Profile to create 90 degree outside corners
	2631 1058	Connect WP External Corner (Grey 02)	4	Used in conjunction with WP Profile to create 90 degree outside corners
	2631 1059	Connect WP External Corner (Black 01)	4	Used in conjunction with WP Profile to create 90 degree outside corners
	2630 0933	WP Profile Splice	4	For use when running multiple lengths of WP Profile end-to-end
	2630 1219	Connect Spline (Black)	100	For use in the kerf between Akusto Wall C panels when they are installed vertically
The state of the s	2630 0132	Connect Direct Fixing Plate (Akusto Wall C)	100	For direct fixing of Akusto Wall C panels when they are installed horizontally

 $^{^{*}}$ Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.



Physical Data

MATERIAL

Fiberglass

FLAME SPREAD/SMOKE DEV. Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less Smoke Developed: 50 or less (Class A per ASTM E1264)

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Washable with mild detergent.

WARRANTY

10-year Ecophon Warranty.
Full warranty information can
be found at <u>certainteed.com/warranty</u>.

