

Ecophon® Focus™ B, F, SQ

FIBERGLASS SMOOTH PANEL

Direct-to-deck ceiling solution, ideal for spaces where a traditional suspended ceiling is not possible or desired.

Features & Benefits

- Ideal for adding sound absorption (up to 0.80 NRC) to spaces with low or angled ceilings, exposed metal or wooden beams
- 3 direct-to-deck options available: trim, beveled or tongue & groove edges
- Direct-to-deck attachment with adhesive (Focus B, F, SQ)
- Direct-to-deck attachment by concrete screws or indirect attachment to wood furring (Focus F)
- Easy-to-clean Akutex™ FT surface in white finish has nearly perfect light diffusion (+99%)
- Fully encapsulated with tissue backing for maximum performance
- Painted, reinforced edges that resist damage from handling
- Available in 22 standard colors (Focus B & SQ Only)

Attributes



SAG RESISTANT



MOLD/MILDEW
RESISTANT
INHERENT



EMISSION
COMPLIANT
CERTIFIED



WASHABLE



LR 0.85
(WHITE ONLY)



RECYCLED
CONTENT

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



CRADLE-TO-CRADLE:
BRONZE CERTIFIED

LEED® v4

RECYCLED CONTENT	51%	
	PRE: 0%	POST: 51%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ EQ: Low-Emitting Materials
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Material Ingredients (C2C)

LEED® is a registered trademark of the U.S. Green Building Council.


Ecophon® Focus™ B, F, SQ

FIBERGLASS SMOOTH PANEL


Colors




Focus B

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Beveled											
	NRC .75	3542 2900	Panels	600 x 600 x 20 (≈24 x 24 x 3/4)	0.75	—	51%	20	7.2 (≈77.5)	49	—

Focus F

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Tongue & Groove											
	NRC .80	3542 2800	Panels	600 x 600 x 20 (≈24 x 24 x 3/4)	0.80	—	51%	20	7.2 (≈77.5)	47	—
		3542 2801	Panels	600 x 1200 x 20 (≈24 x 48 x 3/4)	0.80	—	51%	10	7.2 (≈77.5)	47	—


Focus SQ

			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Square											
	NRC .75	3540 3645	Panels	600 x 600 x 20 (≈24 x 24 x 3/4)	0.75	—	51%	20	7.2 (≈77.5)	41	—
		3540 3646	Panels	600 x 1200 x 20 (≈24 x 48 x 3/4)	0.75	—	51%	12	8.6 (≈93)	40	—


All Focus B and SQ panels listed above are white. To order colors please contact your local Sales Representative.


CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

Edge Details




Accessories

FOCUS B, F, & SQ ACCESSORIES		PRODUCT NAME	PIECES/ CARTON	USE
	2630 0691	Connect Edge Sealant White*	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container

FOCUS F ACCESSORIES		PRODUCT NAME	PIECES/ CARTON	USE
	2630 1219	Connect Spline (Black)	50	Installed on 300mm / ~24" centers along kerfed edge of Focus F

	2630 0149	Connect Direct Fixing Plate (Focus F)	100	Installed on 24 inch centers
---	-----------	---------------------------------------	-----	------------------------------

	2630 0187	Connect Wall Spring Spacer	50	For use when trim cutting panels at the perimeter
---	-----------	----------------------------	----	---

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.

Physical Data

MATERIAL

Fiberglass

FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type XII, Form 2, Pattern G

ASTM E1264-23: Type G, Form B2, Pattern G

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Cleanable with mild detergent.

WARRANTY

10-year Ecophon® Warranty.

Full warranty information can

be found at certainteed.com/warranty.



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 certainteed.com