



Ecophon® Focus™ DG

FIBERGLASS SMOOTH PANEL

Semi-concealed grid provides unique aesthetics coupled with superior sound absorption in a wide selection of sizes and colors.

Features & Benefits

- Semi-concealed, easy downward access
- Narrow gap between panels (5/16")
- Superior sound attenuation (40-43 CAC) with optional CAC Backer
- Easy-to-clean Akutex™ FT surface in white finish has nearly perfect light diffusion (+99%)
- Fully encapsulated with tissue backing for maximum performance
- Available in 22 standard colors

Attributes



SAG RESISTANT



MOLD/MILDEW
RESISTANT
INHERENT



EMISSION
COMPLIANT
CERTIFIED



WASHABLE



LR 0.85



RECYCLED
CONTENT

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



CRADLE-TO-CRADLE:
SILVER CERTIFIED

LEED® v4

RECYCLED CONTENT	51%	
	PRE: 0%	POST: 51%

- ✓ EQ: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Daylight
- ✓ EQ: Low-Emitting Materials
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning
- ✓ MR: Material Ingredients (C2C)

LEED® is a registered trademark of the U.S. Green Building Council.


Ecophon® Focus™ Dg

FIBERGLASS SMOOTH PANEL

Colors



Focus Dg

Focus Dg			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Semi-Concealed											
	NRC .90	3542 1560	Panels	24 x 24 x 3/4	0.90-0.85	23/40*	51%	20	80	44	n/a
		3542 1561	Panels	24 x 48 x 3/4	0.90-0.85	25/43*	51%	10	80	44	n/a
		3542 4239	Panels	30 x 30 x 3/4	0.90	25	51%	14	87.5	43	n/a
		3542 1565	Panels	48 x48 x 1	0.90	25	51%	6	96	64	n/a
		3542 1562	Planks	24 x 60 x 3/4	0.90	25	51%	6	60	33	n/a
		3542 1563	Planks	24 x 72 x 3/4	0.90	25	51%	6	72	36	n/a
		3542 1564	Planks	24 x 96 x 3/4	0.90	25	51%	6	96	53	n/a

*Optional CAC Backer: CertainTeed Protectone panels (sold separately). All Focus panels listed above are white. To order colors please contact your local Sales Representative.
CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990.

Accessories


FOCUS DG ACCESSORIES	PRODUCT NAME	PIECES/CARTON	USE
	2630 0547	50	For support of any cut supporting edge on 3/4" Dg or Ds (typically 1 pc. every 12 - 18 inches)
	2630 0548	50	For support of any cut supporting edge on 1" Dg 4x4 panels only (typically 1 pc. every 12 - 18 inches)
	2630 0691	1	For re-sealing cut edges (typically 100-150 lf/container); 1 liter container
	2630 0991	1	For rabbeting field-cut edges
	2630 0546	12	REQUIRED for non-supporting edges on all 1" Dg 4x4 panels only (2/panel)
	2630 0824	25	For main runner attachment to wall (typically 2/run of main runner)
	2631 1080	100	For attachment and securing of panels at the perimeter
	STBAR-2	40	For all 2x5, 2x6, 2x8 applications; typically 1 pc./panel for 2x5, 2x6, 2 pc./panel for 2x8
	2630 0196	100	For use as a hold down clip with Focus Dg and Focus Ds (typically 1 pc./sf for 2x2 and 0.65 pc./sf for 2x4)
	2630 0187	50	For use when trim cutting panels at the perimeter

*Connect Edge Sealant is available in all standard colors. Please contact your local Sales Representative or call 800-233-8990.



Photo © Garrett Rowland / Ford Foundation, New York, NY

Edge Details



Semi-concealed
15/16" EZ Stab
Classic

Physical Data

MATERIAL
Fiberglass

FLAME SPREAD/SMOKE DEV.
Per ASTM E84 — CAN/ULC S102
Flame Spread: 25 or less
Smoke Developed: 50 or less
(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION
ASTM E1264-22: Type XII, Form 2, Pattern G
ASTM E1264-23: Type B, Form B2, Pattern G

VOC EMISSIONS
Independently certified compliant with
California Department of Public Health
CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE
Fiberglass substrate is inherently resistant to
the growth of mold and mildew.

MAINTENANCE
Wipe with a soft cloth or vacuum with brush
attachment. Cleanable with mild detergent.

WARRANTY
10-year Ecophon® Warranty increases
to 15 years when installed with CertainTeed
suspension systems.
Full warranty information can be found
at certainteed.com/warranty.



CertainTeed
CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 certainteed.com