

# Gyptone® Acoustical Panels

## GYPSUM PERFORATED PANEL

Unique gypsum panels with easy plenum access.

### Features & Benefits

- Perforated, sound absorbent gypsum panel available in 4 unique patterns
- Fully finished white surface is capable of being post-painted to suit design
- Durable lay-in panel provides easy plenum access
- Proprietary Saint-Gobain formaldehyde scavenging performance (inherent to all Gyptone products)

### Attributes



EMISSION  
COMPLIANT  
CERTIFIED



LR  
0.70-0.71



RECYCLED  
CONTENT

## LEED® v4

### RECYCLED CONTENT

up to 85%

- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials

LEED® is a registered trademark of the U.S. Green Building Council.


### CERTIFICATIONS & PRODUCT DECLARATIONS



HPD AVAILABLE


# Gyptone® Acoustical Panels


## GYPSUM PERFORATED PANEL

LINE 4™	FORMAT	DIMENSIONS (IN.)	NRC*	CAC*	LR	HOLE SIZE (MM)	PERFORATED AREA	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET	
Trim													
 NRC .70	5200410258	Panels	24 x 24 x 1/2	0.70	35	0.70	6 x 95	17%	85%	6	24	39	32

Narrow Reveal														
	NRC .70	5200410261	Panels	24 x 24 x 1/2	0.70	35	0.70	6 x 95	17%	85%	6	24	39	32


\*NRC and CAC values when used with CertainTeed Sustainable™ Insulation in unfaced 3-1/2" (R-11) as an overlay above the installed panel (Without insulation NRC=0.60, CAC=17)

POINT 11™		FORMAT	DIMENSIONS (IN.)	NRC*	CAC*	LR	HOLE SIZE (MM)	PERFORATED AREA	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET	
Trim														
	NRC .80	5200410316	Panels	24 x 24 x 1/2	0.80	35	0.71	6.5	12%	85%	6	24	39	32

Narrow Reveal														
	NRC .80	5200410320	Panels	24 x 24 x 1/2	0.80	35	0.71	6.5	12%	85%	6	24	39	32


\*NRC and CAC values when used with CertainTeed Sustainable Insulation in unfaced 2-1/2" (R-8) as an overlay above the installed panel (Without insulation overlay: NRC=0.60, CAC=17)

QUATTRO 20™		FORMAT	DIMENSIONS (IN.)	NRC*	CAC*	LR	HOLE SIZE (MM)	PERFORATED AREA	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET	
Trim														
	NRC .75	5200410417	Panels	24 x 24 x 1/2	0.75	35	0.71	9	18%	85%	6	24	39	32

Narrow Reveal														
	NRC .75	5200410422	Panels	24 x 24 x 1/2	0.75	35	0.71	9	18%	85%	6	24	39	32


\*NRC and CAC values when used with CertainTeed Sustainable Insulation in unfaced 2-1/2" (R-8) as an overlay above the installed panel (Without insulation overlay: NRC=0.65, CAC=17)

SIXTO 60™	FORMAT	DIMENSIONS (IN.)	NRC*	CAC*	LR	HOLE SIZE (MM)	PERFORATED AREA	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET	
Trim													
 NRC .80	5200609848	Panels	24 x 24 x 1/2	0.80	35	0.71	11	17%	85%	6	24	39	16


Narrow Reveal													
 NRC .80	5200609840	Panels	24 x 24 x 1/2	0.80	35	0.71	11	17%	85%	6	24	39	16

\*NRC and CAC values when used with CertainTeed Sustainable Insulation in unfaced 2-1/2" (R-8) as an overlay above the installed panel (Without insulation NRC=0.70, CAC=17)


BASE 31™		FORMAT	DIMENSIONS (IN.)	NRC*	CAC*	LR	HOLE SIZE (MM)	PERFORATED AREA	RECYCLED CONTENT	PIECES/ CARTON	SQ. FT./ CARTON	LBS./ CARTON	CARTONS/ PALLET
Trim													
	5200410489	Panels	24 x 24 x 1/2	—	35	0.82	—	—	85%	6	24	44	32

Narrow Reveal													
	5200410494	Panels	24 x 24 x 1/2	—	35	0.82	—	—	85%	6	24	44	32


\*CAC values when used with CertainTeed Sustainable Insulation in unfaced 3-1/2" (R-11) as an overlay above the installed panel



Line 4




Point 11



Quattro 20




Sixto 60




Base 31


## Edge Details



Trim  
9/16" EZ Stab  
Elite Narrow



Trim  
15/16" EZ Stab  
Classic



Narrow Reveal  
9/16" EZ Stab  
Elite Narrow"

## Physical Data

### MATERIAL

Gypsum

### FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

### ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type XX, Pattern A G

ASTM E1264-23: Type G, Form G1, Pattern A G

### VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

### MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Painted surfaces can be cleaned with a damp cloth and mild detergent.



## CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM  
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](http://certainteed.com)