

Sand Micro™ Sand Micro Customline®

MINERAL FIBER TEXTURED PANEL

A finely textured, durable, mineral fiber panel that appears smooth when installed.

Features & Benefits

- Lightly textured surface provides attractive finish with excellent light reflectance
- Customline scoring option gives the appearance of 2' x 2' reveal in a 2' x 4' panel
- Fine texture gives the appearance of a smooth finish when installed
- Non-directional visual
- High humidity and sag resistant
- Health Product Declaration (HPD) available for this product
- Environmental Product Declaration (EPD) available for this product
- Sand Micro & Sand Micro Customline have USDA Certified Biobased content at 96%
- 30-Year System Warranty when installed with CertainTeed suspension systems

Attributes



SAG RESISTANT



BIOSHIELD®
MOLD/MILDEW
RESISTANT



EMISSION
COMPLIANT
CERTIFIED



LR 0.88



RECYCLED
CONTENT
33%

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



HPD AVAILABLE



DeclareSM

Living Building Challenge Red List Free®

DeclareSM is a service mark of The International Living Future Institute.

LEED® v4




RECYCLED CONTENT	33%	
	PRE: 28%	POST: 5%
✓	EA: Optimize Energy Performance	
✓	EA: Prereq. Min. Energy Performance	
✓	EQ: Interior Lighting	
✓	MR: PBT Source Reduction (Healthcare)	
✓	EQ: Low-Emitting Materials	
✓	EQ: Daylight	
✓	MR: Material Ingredients (HPDs)	
✓	MR: Sourcing Raw Materials	
✓	MR: Environmental Product Declarations (EPDs)	
✓	MR: Construction and Demolition Waste Management Planning	

LEED® is a registered trademark of the U.S. Green Building Council.



Sand Micro™, Sand Micro Customline®

MINERAL FIBER TEXTURED PANEL

Sand Micro


Sand Micro		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
Trim											
	NRC .50	SHM-157	Panels	24 x 24 x 5/8	0.50	33	33%	16	64	47	20
		SHM-197	Panels	24 x 48 x 5/8	0.50	35	33%	8	64	47	20
Reveal											
	NRC .50	SHM-154	Panels	24 x 24 x 5/8	0.50	33	33%	16	64	47	20
		SHM-194	Panels	24 x 48 x 5/8	0.50	35	33%	8	64	47	20
Narrow Reveal											
	NRC .50	SHM-150	Panels	24 x 24 x 5/8	0.50	33	33%	16	64	47	20
		SHM-190	Panels	24 x 48 x 5/8	0.50	35	33%	8	64	47	20

Sand Micro Customline


Sand Micro Customline		FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET	
Trim											
	NRC .50	SMCL-224	Panels	24 x 48 x 3/4	0.50	35	33%	8	64	62	16
Narrow Reveal											
	NRC .50	SMCLN-224	Panels	24 x 48 x 3/4	0.50	35	33%	8	64	62.5	16

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990


Edge Details




Trim (Sand Micro)
9/16" EZ Stab
Elite Narrow




Trim (Sand Micro)
15/16" EZ Stab
Classic



Reveal Beveled
15/16" EZ Stab
Classic



Narrow Reveal
Corner Bevel
9/16" EZ Stab
Elite Narrow



Narrow Reveal
Beveled (Customline)
9/16" EZ Stab
Elite Narrow

Customline Scoring Options



24 x 48
(SMCL-224)

Physical Data

MATERIAL

Mineral Fiber

FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type III, Form 2, Pattern E

ASTM E1264-23: Type A, Form A1.2, Pattern E

VOC EMISSIONS

Independently certified compliant
with California Department of Public
Health CDPH/EHLB/Standard
Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

BioShield® treatment included for
added mold and mildew resistance.

MAINTENANCE

Wipe with a soft cloth or vacuum
with brush attachment.

WARRANTY

10-year 104/90 Limited Warranty
increases to 30 years when installed
with CertainTeed suspension systems.
Full warranty information can be
found at [certainteed.com/warranty](https://www.certainteed.com/warranty).



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 [certainteed.com](https://www.certainteed.com)