

Symphony® f Rx

FIBERGLASS SMOOTH PANEL

The Symphony f Rx line provides a white, clean, monolithic ceiling visual. Superior stain resistance and water repellency make this product ideal for healthcare and kitchen applications.

Features & Benefits

- Superior sound absorption (0.95 NRC) and sound blocking (39-42 CAC) with optional CAC On-lay Backer
- Superior stain resistance and water repellency
- Certified clean room component to ISO Class 4 (highest among comparable products)
- Washable with most sanitizing solutions and wash-tested to 2,000 wash cycles
- Exceeds FGI guidelines for cleanability and acoustic performance in most healthcare applications
- Satisfies USDA/FSIS guidelines for sanitary applications (commercial kitchens)
- VOC compliant to CDPH v1.2, 2017
- 30-Year System Warranty when installed with CertainTeed suspension systems

Attributes



SAG RESISTANT



BIOSHIELD®
MOLD/MILDEW
RESISTANT



EMISSION
COMPLIANT
CERTIFIED



WASHABLE W/
SANITIZING
CHEMICALS



LR 0.90



RECYCLED
CONTENT
29-31%

CERTIFICATIONS & PRODUCT DECLARATIONS



EPD AVAILABLE



HPD AVAILABLE

LEED® v4

RECYCLED CONTENT




up to 31%

- ✓ EA: Optimize Energy Performance
- ✓ EA: Prereq. Min. Energy Performance
- ✓ EQ: Interior Lighting
- ✓ MR: PBT Source Reduction (Healthcare)
- ✓ EQ: Acoustic Performance
- ✓ EQ: Prereq. Min. Acoustic Performance (Schools)
- ✓ EQ: Low-Emitting Materials
- ✓ EQ: Daylight
- ✓ MR: Material Ingredients (HPDs)
- ✓ MR: Sourcing Raw Materials
- ✓ MR: Environmental Product Declarations (EPDs)
- ✓ MR: Construction and Demolition Waste Management Planning

LEED® is a registered trademark of the U.S. Green Building Council.

Symphony® f Rx

FIBERGLASS SMOOTH PANEL


Symphony f Rx			FORMAT	DIMENSIONS (IN.)	NRC	CAC	RECYCLED CONTENT	PIECES/CARTON	SQ. FT./CARTON	LBS./CARTON	CARTONS/PALLET
Trim											
	NRC .95	1342-RXS-1	Panels	24 x 24 x 1	0.95	23/39*	31%	24	96	34	14
		1340-RXS-1	Panels	24 x 48 x 1	0.95	23/42*	31%	12	96	34	14
Reveal											
	NRC .95	1342B-RXS-1	Panels	24 x 24 x 1	0.95	23/39*	29%	24	96	42	14
		1340B-RXS-1	Panels	24 x 48 x 1	0.95	23/42*	29%	12	96	42	14
Narrow Reveal											
	NRC .95	1342F-RXS-1	Panels	24 x 24 x 1	0.95	23/39*	29%	24	96	42	14
		1340F-RXS-1	Panels	24 x 48 x 1	0.95	23/42*	29%	12	96	42	14

*Optional CAC On-Lay Backer: CertainTeed Protectone panels (ordered & sold separately)


CAC range of 26-27 achieved with CAC foil backing. CAC Foil Backing is available for the Symphony f Rx line as a special order.

CAN'T FIND A SIZE? Contact your local Sales Representative or call 800-233-8990


Accessories

SYMPHONY® f ACCESSORIES		PRODUCT NAME	PIECES/CARTON	USE
	1400-SEL-1	Fiberglass Edge Sealant	1	For re-sealing cut edges; 1 quart container


Edge Details




Trim
9/16" EZ Stab
Elite Narrow




Trim
15/16" EZ Stab
Classic




Reveal
15/16" EZ Stab
Classic



Narrow Reveal
9/16" EZ Stab
Elite Narrow



Narrow Reveal
9/16" EZ Stab
Bolt Slot



Narrow Reveal
9/16" EZ Stab
Tier Drop

Photo: © Michael Cooper

Physical Data

MATERIAL

Fiberglass

FLAME SPREAD/SMOKE DEV.

Per ASTM E84 — CAN/ULC S102

Flame Spread: 25 or less

Smoke Developed: 50 or less

(Class A per ASTM E1264)

ASTM E1264 CLASSIFICATION

ASTM E1264-22: Type XII, Form 2, Pattern G

ASTM E1264-23: Type B, Form B2, Pattern G

VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017.

MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

MAINTENANCE

Wash tested to 2,000+ cycles. Cleanable with sanitizing chemicals.

WARRANTY

10-year 104/95 Limited Warranty increases to 30 years when installed with CertainTeed suspension systems. Full warranty information can be found at certainteed.com/warranty.



CertainTeed

CEILINGS • GYPSUM • INSULATION • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 800-233-8990 certainteed.com