





Xanadu 5512



WINE 5539



CAPPUCCINO 5506



XANADU 5512



MONARCH 5502



BALTIC 5515



SMOKE 5503



FLINT 5501

> Specification Information

	Description	Soft Knit
	Content	100% Polyester
	Repeat	None
	Size	Sold in specific dimensions
	Weight	16.0 oz. / sq. yard
	Backing	None
	Performance	
*	Physical Properties	Passes Brush Pill ASTM D3511. Class 4 min. Pilling is the formation of fuzzy balls of fiber on the surface of a fabric that remain attached to the fabric. Passes Breaking Strength ASTM D5034. 185 lbs. minimum in machine directions and cross direction. Breaking strength is the measurement of stress exerted to pull a fabric apart under tension. Passes Tear ASTM D2261. 30 lbs. minimum in machine direction and cross direction.
•	Colorfastness to Crocking	Passes AATCC 8, Grade 4 for dry crocking and Grade 3 for wet crocking. Crocking is the transfer of dye from the surface of a dyed or printed fabric onto another surface by rubbing. Passes AATCC 107, class 3 for staining, class 4 for color change.
**	Colorfastness to Light	Passes AATCC 16 Option 3, 40 hrs. min. Colorfastness to light refers to a material's degree of resistance to the fading effect of light.
**	Flammability	Passes California Technical Bulletin #117 Section E - Class 1. UFAC Class 1. NFPA 260 Class 1. Flammability is the measurement of a fabric's performance when it is exposed to specific sources of ignition.
W-S	Cleaning	Clean with water-based cleaning agents, foam, or pure, water-free solvents. Vacuuming or light brushing is recommended to prevent dust and soil build up. May be cleaned with a 10% bleach-to-water solution. Rinse well after cleaning.
A	Abrasion	Passes Abrasion Resistance (ASTM D4157) 250,00 double rubs wire screen. Abrasion resistance is the surface wear of a fabric caused by rubbing and contact with another fabric.

Colors may vary slightly between dye lots. Soft Knit fabric is available only on Impress and Impress Ultra task chairs.

This information may include discontinued colors. For current color availability, refer to ki.com.

