PRODUCT SPECIFICATIONS

ValueLite® Tables

November 2019

TECHNICAL SPECIFICATIONS

Tabletop

The top is composed of .070" thick, high impact polyethylene. The blow-molded top is seamless, eliminating the possibility of separation. Added UV inhibitors prevent fading and maintain appearance. The polyethelyene tops are impervious to stains and easy to clean.

Rectangular Table Leg Inset

Table legs are 24.5" wide at the base. Table legs are inset 8" from the side edge of the table and 6" from the end of the table.

Round Table Leg Inset

Table legs are 24.5" wide at the base. Table legs are inset 10" on 60" diameter tables and 12" on 72" diameter tables.

Table Legs

Fixed-height legs and frame are constructed of 19-gauge, $1^{1}/_{8}$ " tubing O.D., seam-welded tubular steel with non-marring feet (24" x 48" leg and frame are 21-gauge). Folding linkage, hinges, locks and fastening hardware are of heavy-duty die-formed steel. The gravity operated chain link leg lock puts 200% more material at the point of stress. The $24^{3}/_{4}$ " leg stance adds strength and stability. Leg brace below the bend is stronger than common U-shaped legs.

Legs and mechanisms are furnished in a high quality, black hammertone powder-coat finish.

Size and Weight Specifications

Height	Weight	Stack Height
29"	35 lb	21/8"
29"	38 lb	21/8"
29"	47 lb	21/4"
29"	34 lb	$3^{5}/_{8}$ "
29"	53 lb	3 ⁵ / ₈ "
29"	73 lb	35/8"
	29" 29" 29" 29" 29"	29" 35 lb 29" 38 lb 29" 47 lb 29" 34 lb 29" 53 lb

Warranty

Five years against defects in materials and craftsmanship.



