

PRODUCT SPECIFICATIONS ■

Tributaire Collection

Café Tables

April 2025

TECHNICAL SPECIFICATIONS

Table Base

C-Leg Base (café tables)

Café C-leg bases feature four cast aluminum feet and framework making up two pair of connected leg sets. To form each connected leg set, a pair of cast aluminum feet are joined together with a cross-brace of pill-shaped, tubular steel. Each foot contains a machined-in side pocket to accept the tubular cross-brace. Extending up from each foot of the feet and cross-brace set is a stylized pill-shaped leg upright of 8-gauge extruded aluminum. At each side of the assembly, the foot, cross-brace and leg upright are secured together from underneath using $\frac{5}{16}$ -18 x 5" hex washer head screws. Atop each extruded aluminum leg upright is a 7-gauge steel table mounting plate, secured to the upright using $\frac{5}{16}$ -18 x 2 $\frac{1}{2}$ " Torx flat head screws. The table mounting plate then secures to the underside of the tabletop using #12 x 1" Phillips flat head tapping screws at pre-drilled mounting holes. Each connected leg set is joined to the next leg set with a rectangular shaped stringer of tubular seam-welded steel, making up the four foot base. Stringer attachment at each leg set is at a welded-on lower bracket on the foot-to-foot steel cross-brace, using two $\frac{1}{4}$ -20 x $\frac{5}{8}$ " Torx pan head screws at each end of the stringer.

Each C-leg table foot extends out 13.5" from its respective extruded aluminum leg upright and is threaded at the floor level to accept either casters or low-profile adjustable glides. Steel cross-braces between feet are the same length regardless of table width. Conference table bases support tables at 29" high.

X-Base (café tables)

Café X-bases are of cast aluminum, attached via four $\frac{5}{16}$ -18 x 5" hex washer head cap head screws from underneath to a 10-gauge extruded aluminum upright. The fluted upright is 2 $\frac{5}{8}$ " diameter and has the same profile as the mating surface of the X-base. Atop the upright, a 10" diameter cast aluminum table mounting plate is secured to the top of the upright using four $\frac{5}{16}$ -18 x 2" hex washer head cap head screws from above. The table mounting plate then secures to the underside of the tabletop using #12 x 1" Phillips flat head tapping screws at pre-drilled mounting holes.

The four feet of the X-base each extend out 15" from the center upright and each foot is threaded at the floor level to accept low-profile adjustable glides. The entire base assembly has an open channel in the center for seamless cable management. The upright's length varies depending if the table is 29", 36", or 42" high.

Double X-Base (café tables)

Double X-base tables consist of two individual X-base assemblies mounted to the underside of the table. Café X-bases are of cast aluminum, attached via four $\frac{5}{16}$ -18 x 5" hex washer head cap head screws from underneath to a 10-gauge extruded aluminum upright. The fluted upright is 2 $\frac{5}{8}$ " diameter and has the same profile as the mating surface of the X-base. Atop the upright, a 10" diameter cast aluminum table mounting plate is secured to the top of the upright using four $\frac{5}{16}$ -18 x 2" hex washer head cap head screws from above. The table mounting plate then secures to the underside of the tabletop using #12 x 1" Phillips flat head tapping screws at pre-drilled mounting holes.

The four feet of the X-base each extend out 15" from the center upright and each foot is threaded at the floor level to accept low-profile adjustable glides. The entire base assembly has an open channel in the center for seamless cable management. The upright's length varies depending if the table is 29", 36", or 42" high.

Base Finish

Café bases are either all powder-coat painted, or are chrome-plated. See Product Color Options in the Tributaire Collection pricelist for color options offered.



TECHNICAL SPECIFICATIONS

Tabletops

Tabletops are nominal 1 1/4" overall thickness with a .030" thick high-pressure laminate top surface and a .028" phenolic backer bottom surface. The density of the particleboard core in standard tops is 45 lb/cu ft. Tributaire conference tables are available with the 2 mm (74P) edge or knife edge.

Tabletops come pre-drilled with mounting holes for their corresponding table bases and various accessories. They may also have one or two optional grommet cutouts in the table surface, which allows for a power module or a grommet cover.

Laminate color options can be found in the Product Color Options page in the Tributaire Collection Pricelist.

Casters

All café tables specified with casters ship from the factory with two locking and two non-locking, twin-wheeled molded nylon casters. Caster wheels are 2.50" (65 mm) in diameter, with a total mounted height of 2.75" (70 mm). Caster wheel treads are soft for ease of mobility on carpet or hard floors. Casters are not compatible or interchangeable with glides, as glide and caster installed heights are different. Casters come in three color options: all Black, all Warm Grey or a two-tone combination of Cottonwood body with Warm Grey tread and brake lock. Casters are mounted with 1/2" diameter friction ring fit posts, requiring no tools to install.

Low Profile Glides

All legs specified with glides are shipped with four adjustable-height glides. Glides are 1 1/2" in diameter at the base and have a 3/16"-18 x 3/4" threaded stem, allowing for an adjustment range of 1/2". Glides are only available in black nylon.

Grommets

Dean & Nacre Flip-Top Grommets

Flip-top grommets are surface-mounted, constructed of 18-gauge steel and have a flip-up door. The grommets may be fastened with wood screws into the 6.94" x 3" tabletop cutouts. Flip-top grommets are sized the same as Nacre or Dean power modules (sold separately), which allows for retrofitting of corresponding power modules at a later date. The grommet's flip-up door allows cords to pass through to a power source while closed, and allows for more cord routing space when the flip-up door is opened. One grommet ships per table with cutout, located at the center, rear of the tabletop. Grommets are field installed.

Flip-top grommets are finished in powder-coat paint colors found in the Tributaire Collection Pricelist, on the Product Color Options page.

Node Circular Grommet

The Node circular grommet is an open top, surface mounted grommet constructed of aluminum. The grommet may be fastened with wood screws into the tabletop cutout. Circular grommet is sized the same as the Node power module, which allows for retrofitting of the tabletop corresponding power module at a later date. The circular grommet opening allows cords to pass through to a power source. The overall diameter is 3.15" and it fits into a 3" diameter cutout in the surface. One grommet ships per table with cutout, located at the center, rear of the tabletop. Grommet is field installed.

Circular grommets are finished in powder-coat paint colors found in the Tributaire Collection Pricelist, on the Product Color Options page. Not available in chrome.

CODE COMPLIANCE



Power Modules



Dean In-Surface Power Module

Dean in-surface power module consists of two simplex receptacle ports (rated at 15 amps/125 volts), one USB-A port and one USB-C port, 2 amps per port, and one data jack opening. The module can be adapted to fit various brands of data jacks using the data tree, which ships with Dean in-surface power module. Data connectors are not supplied with the module and are purchased by the customer. The Dean In-Surface module is 8.12" long by 2.31" wide by 2.5" high and fits securely into a 7.81" x 1.93" cutout. The power module is secured to the worksurface with screws from the underside of the table. The module has a molded plastic faceplate with steel trim and an aluminum housing. The Dean In-Surface power module with 3-prong plug is rated at 15 amps/120 volts, and is UL listed.

Cord length options are either 9' or 15' with a 3-prong plug. Color options are Black, Warm Grey, Cool Grey, or Cottonwood.

Dean Undersurface Power Module

The Dean undersurface power module consists of two simplex receptacles ports (rated at 15 amps/125 volts), one USB-A port and one USB-C port, 2 amps per port. The module mounts flush under the bottom, front edge of the tabletop with two #12 x 3/4" screws through the mounting plate. The module is made of a molded plastic body with an anodized aluminum housing and a steel mounting plate. Tabletops come pre-drilled with holes at recommended mounting locations, but users may pre-drill mounting locations where they prefer. The Dean undersurface power module with 3-prong plug is rated at 15 amps/120 volts and is UL listed. Dean undersurface power modules are only available on café tables with a double X-base.

Cord length options are either 9' or 15' with a 3-prong plug. Color options are Black, Warm Grey, Cool Grey, or Cottonwood.

Dubbel™ Undersurface Power Module

Dubbel Undersurface power module consists of two simplex receptacle ports (rated at 15 amps/125 volts), one USB-A port and one USB-C port, 2 amps per port. Dubbel is 7.63" wide by 5.25" deep by 1.75" tall, and mounts flush with the bottom, front edge of the tabletop with two #10 x 3/4" screws included. The module is made of a molded plastic body with a molded plastic face. Tabletops come pre-drilled with holes at recommended mounting locations, but users may pre-drill mounting locations where they prefer. The Dubbel Undersurface power module with 3-prong plug is rated at 15 amps/120 volts and is UL listed. Dubbel undersurface power modules are only available on café tables with a double X-base.

Cord length options are either 9' or 15' with a 3-prong plug. Color options are Black, Warm Grey, Cool Grey, or Cottonwood.

Nacre In-Surface Pop-Up Power Module

Nacre in-surface pop-up power module consists of two simplex receptacle ports (rated at 15 amps/125 volts), one USB-A port and one USB-C port, 2 amps per port, and one data jack opening. The module can be modified to fit various brand data jacks. Data tree ships with Nacre power modules, providing different data face plates to accompany different data connectors. Data connectors are not supplied with the module and are purchased separately by the customer. The Nacre power module is 7.25" long by 3.31" wide by 2.92" high and fits securely into a 6.94" x 3" cutout. The power module is press fit into the worksurface cutout and secured with spring loaded metal tabs. The module has a molded plastic face that can rotate via a dampened spring-loaded mechanism inside a molded plastic sleeve. The Nacre in-surface pop-up power module with 3-prong plug is rated at 15 amps/120 volts, and is UL listed.

Cord length options are either 9' or 15' with a 3-prong plug. Color options are Black, Warm Grey, Cool Grey, or Cottonwood.

TECHNICAL SPECIFICATIONS

Power Modules (cont.)

Node® In-Surface Power Module

Node in-surface power module consists of one simplex receptacle port (rated at 15 amps/125 volts), includes one USB-A port, and one USB-C port, 2 amps per port. Node is 3.38" in diameter by 3.30" tall and fits securely into a 3" diameter cutout. The module is secured from underneath the table with a twist-on clamping collar. The module housing is made of plastic with a powder-coat painted aluminum faceplate. The Node power module with 3-prong plug is rated at 15 amps/120 volts and is UL listed.

Cord length options are either 9' or 15' with a 3-prong plug. Color options are Black, Warm Grey, Cool Grey, or Cottonwood.

Wire Management

Vertical Wire Manager

Vertical wire manager is 16-gauge aluminum extrusions designed to route cords from the tabletop, down the leg and toward the power source. Each wire manager is cut to length and powder-coat painted in the color of the corresponding table base. The wire manager is user installed on a C-leg or X-base using the provided double sided tape. Once installed, cords can be pushed through the extrusion's opening, which helps provide table to floor management. Vertical wire managers are only available on café tables with a C-leg base or double X-base.

CODE COMPLIANCE

