

# PRODUCT SPECIFICATIONS

## Tributaire Collection

### Conference Tables

April 2025

## TECHNICAL SPECIFICATIONS

### Table Bases

Conference table bases feature a pair of cast aluminum feet joined together with a cross-brace of pill-shaped, tubular steel. Each foot contains a machined-in side pocket to accept the tubular cross-brace. Extending up from each foot of the foot and cross-brace set, is a stylized pill-shaped leg upright of 8-gauge extruded aluminum. At each side of the assembly, the foot, cross-brace and leg upright are secured together from underneath using  $\frac{5}{16}$  - 18 x 5" hex washer head screws. Atop each extruded aluminum leg upright is a 7-gauge steel table mounting plate, secured to the upright using  $\frac{5}{16}$  - 18 x 2  $\frac{1}{2}$ " Torx flat head screws. The table mounting plate then secures to the underside of the tabletop using #12 x 1" Phillips flat head tapping screws at pre-drilled mounting holes. Each conference table base assembly is joined to the next base with a rectangular shaped stringer of tubular seam-welded steel. Stringer attachment at each base assembly is at a welded-on lower bracket on the foot-to-foot steel cross-brace, using two  $\frac{1}{4}$  - 20 x  $\frac{5}{8}$ " Torx pan head screws at each end of the stringer.

Each conference table foot extends out 13.5" from its respective extruded aluminum leg upright and is threaded at the floor level to accept low profile adjustable glides. Steel cross-braces between feet are different lengths depending on table width. Each conference table has four to twelve table base assemblies depending on table length. Conference table bases support tables at 29" high.

### Base Finishes

Conference table bases are either all powder-coat painted, or are chrome-plated aluminum feet and leg columns, with a black powder-coat texture painted stringers.

See Product Color Options page in the Tributaire Collection Pricelist for color options offered.

### Tabletops

Tabletops are nominal 1  $\frac{1}{4}$ " overall thickness with a .030" thick high-pressure laminate top surface and a .028" phenolic backer bottom surface. The density of the particleboard core in standard tops is 45 lb/cu ft. Tributaire conference tables are available with the 2 mm (74P) edge or knife edge.

Tabletops come pre-drilled with mounting holes for their corresponding table bases and various accessories. They may also have one or two optional grommet cutouts in the table surface, which allows for a power module or a grommet cover. Tables above 144" consist of two separate pieces that must be joined together during assembly.

Laminate color options can be found in the Product Color Options page in the Tributaire Collection Pricelist.

### Low Profile Glides

All legs specified with glides are shipped with adjustable-height glides. Glides are 1  $\frac{1}{2}$ " in diameter at the base and have a  $\frac{5}{16}$  - 18 x  $\frac{3}{4}$ " threaded stem, allowing for an adjustment range of  $\frac{1}{2}$ ". Glides are only available in black nylon.



Furnishing Knowledge®

## Grommets



### Dean & Nacre Flip-Top Grommets

Flip-top grommets are surface-mounted, constructed of 18-gauge steel and have a flip-up door. The grommets may be fastened with wood screws into the 6.94" x 3" tabletop cutouts. Flip-top grommets are sized the same as Nacre or Dean power modules (sold separately), which allows for retrofitting of corresponding power modules at a later date. The grommet's flip-up door allows cords to pass through to a power source while closed, and allows for more cord routing space when the flip-up door is opened. One grommet ships per table with cutout, located at the center, rear of the tabletop. Grommets are field installed.

Flip-top grommets are finished in powder-coat paint colors found in the Tributaire Collection Pricelist, on the Product Color Options page.

### Node Circular Grommet

The Node circular grommet is an open top, surface mounted grommet constructed of aluminum. The grommet may be fastened with wood screws into the tabletop cutout. Circular grommet is sized the same as the Node power module, which allows for retrofitting of the tabletop corresponding power module at a later date. The circular grommet opening allows cords to pass through to a power source. The overall diameter is 3.15" and it fits into a 3" diameter cutout in the surface. One grommet ships per table with cutout, located at the center, rear of the tabletop. Grommet is field installed.

Circular grommets are finished in powder-coat paint colors found in the Tributaire Collection Pricelist, on the Product Color Options page. Not available in chrome.

## Power Modules

### Dean In-Surface Power Module

Dean In-Surface power module consists of two simplex receptacle ports (rated at 15 amps/125 volts), one USB-A port and one USB-C port, 2 amps per port, and one data jack opening. The module can be adapted to fit various brands of data jacks using the data tree, which ships with Dean in-surface power module. Data connectors are not supplied with the module and are purchased by the customer. The Dean In-Surface module is 8.12" long by 2.31" wide by 2.5" high and fits securely into a 7.81" x 1.93" cutout. The power module is secured to the worksurface with screws from the underside of the table. The module has a molded plastic faceplate with steel trim and an aluminum housing. The Dean In-Surface power module with 3-prong plug is rated at 15 amps/120 volts, and is UL listed. The Dean in-surface power module with the Pattern connector is rated at 15 amps/120 volts and is ETL listed.

Cord length options are either 9' or 15' with a 3-prong plug, or is 20' with a Pattern connector. Color options are Black, Warm Grey, Cool Grey, or Cottonwood.

### Double Ellora B In-Surface Power Module

Double Ellora B In-Surface power module is a two-sided, in-surface power module which consists of two simplex receptacle ports (rated at 15 amps/125 volts), one USB, one USB-A and one USB-C port, 2 amps per port, on each side of the double power module. Module area is 10.19" long by 8.31" wide by 2.71" high when open. The pop-up module housing is of painted aluminum and steel, with smooth plastic faceplates for the ports. The surface trim and hinged soft-close covers are of painted aluminum. The covers allow for cable routing when closed. All metal surfaces of the module are powder-coat painted in four select colors. The Double Ellora B In-Surface power module with 3-prong plug is rated at 15 amps/120 volts and is UL listed. The Double Ellora B in-surface power module with the Pattern connector is rated at 15 amps/120 volts and is ETL listed.

Cord length options are either 9' or 15' with a 3-prong plug, or is 20' with a Pattern connector. Color options are Black, Warm Grey, Cool Grey, or Cottonwood.



### Power Modules (cont.)



#### Nacre In-Surface Pop-Up Power Module

Nacre In-Surface Pop-Up power module consists of two simplex receptacle ports (rated at 15 amps/125 volts), one USB-A port and one USB-C port, 2 amps per port, and one data jack opening. The module can be modified to fit various brand data jacks. Data tree ships with Nacre power modules, providing different data face plates to accompany different data connectors. Data connectors are not supplied with the module and are purchased separately by the customer. The Nacre power module is 7.25" long by 3.31" wide by 2.92" high and fits securely into a 6.94" x 3" cutout. The power module is press fit into the worksurface cutout and secured with spring loaded metal tabs. The module has a molded plastic face that can rotate via a dampened spring-loaded mechanism inside a molded plastic sleeve. The Nacre in-surface pop-up power module with 3-prong plug is rated at 15 amps/120 volts, and is UL listed. The Nacre in-surface pop-up power module with the Pattern connector is rated at 15 amps/120 volts and is ETL listed.

Cord length options are either 9' or 15' with a 3-prong plug, or is 20" with a Pattern connector. Color options are Black, Warm Grey, Cool Grey, or Cottonwood.

#### Node® In-Surface Power Module

Node In-Surface power module consists of one simplex receptacle port (rated at 15 amps/125 volts), includes one USB-A port, and one USB-C port, 2 amps per port. Node is 3.38" in diameter by 3.30" tall and fits securely into a 3" diameter cutout. The module is secured from underneath the table with a twist-on clamping collar. The module housing is made of plastic with a powder-coat painted aluminum faceplate. The Node power module with 3-prong plug is rated at 15 amps/120 volts and is UL listed. The Node power module with the Pattern connector is rated at 15 amps/120 volts and is ETL listed.

Cord length options are either 9' or 15' with a 3-prong plug, or is 20" with a Pattern connector. Color options are Black, Warm Grey, Cool Grey, or Cottonwood.

### Electrical

#### Pattern Single-Circuit Electrical System

Pattern electrical system is a single circuit system that allows up to 2 power modules to be powered from a single 15-amp power supply cord. Tables ordered with the Pattern Electrical System include associated Pattern power modules and wire management. Pattern infeeds must be ordered separate from the tables and depend on how many total tables and configuration.

Pattern is a non-sequential system with a ground fault interrupter (GFI/GFCI) compatible infeed. The Pattern electrical system is ETL Listed, evaluated to safety standard UL 962A (USA) and CAN/CSA-C22.2 No. 308 (Canada).

#### Pattern Power Distribution Blocks

Pattern power distribution blocks are standalone connectors, each containing four port locations. Distribution blocks are included with appropriate power jumper and power infeed kits, so do not need to be ordered separately. Distribution blocks bring the power infeed, power jumpers, and power modules together and allow power to be efficiently supplied to each table. Two distribution block types are included with the Pattern system, two grey Pattern power distribution blocks.

#### Pattern Power Infeed Kits

The Pattern power infeed kit must be ordered separately. Kit comes with two grey Pattern power distribution blocks, one power jumper, and Pattern power infeed cord. Power infeed consists of a 15-amp plug on one end of the 108" cord and a keyed connector at the opposite end of the cord. A Pattern quick-release tool is also included to assist with disconnecting connector ends from distribution blocks.



### Wire Management

#### Vertical Wire Manager

Vertical wire manager is 16-gauge aluminum extrusions designed to route cords from the tabletop, down the leg and toward the power source. Each wire manager is cut to length and powder-coat painted in the color of the corresponding table base. The wire manager is user installed on a table leg using the provided double sided tape. Once installed, cords can be pushed through the extrusion's opening, which helps provide table to floor management.

#### Velcro Wire Manager

The Velcro wire manager is constructed of a 2" x 4 1/2" Velcro hook and loop material and is mounted under the tabletop using screws, or with it's adhesive backing. Tabletops are pre-drilled for locating screw mounted wire managers, but a wire manager may be installed in any convenient location. Two or four Velcro wire managers are included (and must be used) for tables with the Pattern single-circuit electrical system, but must be ordered as a separate accessory for all other tables. Simple wire clips are provided in place of Velcro wire managers for tables that have a power module with 3-prong plug.

