

NAPOLI
FRAGMENTS

STONESOURCE





FLOOR
CENERE Natural 36"x36" Rectified
CENERE Rubel Deco Natural 36"x36" Rectified

WALL
CENERE Natural 24"x48" Rectified
CENERE Rubel Deco Natural 12"x12" Rectified



CENERE Rubel Deco Natural 12"x12" Rectified



CENERE Natural 36"x36" Rectified



CALCITE Rubel Deco Natural 36"x36" Rectified



GRAFITE Natural 12"x24" Rectified
GRAFITE Hydro Exa Natural 12"x12" Rectified



GRAFITE Natural 36"x36" Rectified
GRAFITE Rubel Deco Natural 12"x12" Rectified



GRAFITE Natural 36"x36" Rectified
GRAFITE Rubel Deco Natural 12"x12" Rectified





CEMENT Natural 12"x24" Rectified
CEMENT Palladiana Tumbled Natural 12"x12"

FLOOR

CENERE Rubel Deco Natural 36"x36" Rectified

WALL

CENERE Natural 36"x36" Rectified
Deco 1 Natural 12"x12" Rectified



A PROFOUND
NEW TAKE ON
MATERIAL





FIELD

NAPOLI FRAGMENTS

TILES

NAPOLI FRAGMENTS

COLOR BODY PORCELAIN STONEWARE

FIELD TILES - COLOR AVAILABILITY

CALCITE



CENERE




CEMENT



GRAFITE



FIELD TILES - SIZE AVAILABILITY




36"x36" Rectified

Thickness: **10mm**
Finishes: **Natural**
Available in all colors



24"x48" Rectified

Thickness: **10mm**
Finishes: **Natural**
Available in all colors.



24"x24" Rectified

Thickness: **10mm**
Finishes: **Natural**
Available in all colors except Calcite, Grafite, Cement.



12"x24" Rectified

Thickness: **10mm**
Finishes: **Natural**
Available in all colors except Calcite.

SHADE VARIATION V3

NAPOLI FRAGMENTS

COLOR BODY PORCELAIN STONEWARE

DECORS

Hydro Exa 12"x12" Rectified


Finish: **Natural** (Sheet made up of 48 pieces)




CALCITE



CENERE



CEMENT



GRAFITE

Deco_1 12"x12" Rectified

Thickness: **10mm** - Finish: **Natural**



Palladiana 12"x12"

Finish: **Tumbled Natural**



CALCITE



CENERE




CEMENT



GRAFITE

Deco_1 12"x12" Rectified

Thickness: **10mm** - Finish: **Natural**



SPECIAL PIECES



Bullnose

Size: **3"x24" Rectified**

Finishes: **Natural**

Colors: **Calcite / Cenere / Cement / Grafite**



RUBELL

NAPOLI FRAGMENTS

DECCO

NAPOLI FRAGMENTS
COLOR BODY PORCELAIN STONEWARE

RUBEL DECO

CALCITE RUBEL DECO



CENERE RUBEL DECO




CEMENT RUBEL DECO




GRAFITE RUBEL DECO



RUBEL DECO - SIZE AVAILABILITY



Rubel Deco 36"x36" Rectified
Thickness: 10mm
Finishes: **Natural**
Available in all colors



Rubel Deco 12"x12" Rectified
Thickness: 10mm
Finishes: **Natural**
Available in all colors

SHADE VARIATION V4

NAPOLI FRAGMENTS

COLOR BODY PORCELAIN STONEWARE

PACKAGING

SIZES	SIZES (CM)	PCS/BOX	SQM/BOX	KG/BOX	BOX/PAL	SQM/PAL	KG/PAL	THICKNESS
36”x36” Rectified	90x90	2	1.62	36	20	32.4	730	10mm
24”x48” Rectified	60x120	2	1.44	32	24	34.56	778	10mm
24”x24” Rectified	60x60	4	1.44	31.5	30	43.20	955	10mm
12”x24” Rectified	30x60	6	1.08	23.5	40	43.20	950	10mm
Rubel Deco 36”x36” Rectified	90x90	2	1.62	36	20	32.4	730	10mm
Rubel Deco 12”x12” Rectified	30x30	12	1.08	21.5	48	51.84	1042	10mm
Deco_1 12”x12” Rectified	30x30	12	1.08	21.5	48	51.84	1042	10mm
Deco_2 12”x12” Rectified	30x30	12	1.08	21.5	48	51.84	1042	10mm
Hydro Exa 12”x12” Rectified*	30x30	5	0.365	13	-	-	-	-
Palladiana 12”x12”	30x30	11	0.99	20	-	-	-	-
Bullnose 3"x24" Rectified	7.5x60	22	13.2	22	-	-	-	-

TECHNICAL FEATURES EN 14411: 2012 Annex G Group Bla GL

TECHNICAL FEATURES	TEST METHOD	REQUIRED MINIMUM STANDARDS	RESULTS
SIZES AND LOOK OF THE TILE	ISO 10545-2	LENGTH AND WIDTH: ± 0.6% / ± 2.0mm THICKNESS: ± 5% / ± 0.5mm STRAIGHTNESS OF SIDES: ± 0.5% / ± 1.5mm RECTANGULARITY: ± 0.5% / ± 2.0mm SURFACE FLATNESS: ± 0.5% / ± 2.0mm <i>SURFACE QUALITY: 95% OF TILES WITH NO DEFAULTS</i>	Compliant Compliant Compliant Compliant Compliant
WATER ABSORPTION	ISO 10545-3	≤ 0.5%	0.06% (average values referred to the last production)
AVERAGE BENDING STRENGTH	ISO 10545-4	35 N/mm² min.	38.9 N/mm² (average values referred to the last production)
BREAKING STRENGTH	ISO 10545-4	Thickness ≥ 7.5mm: 1300N min.	Compliant
RESISTANCE TO SURFACE ABRASION	ISO 10545-7	State the PEI rate and covered cycles	Calcite: Class 4 (6000 rotations) Cenere/Cement/Grafite: Class 4 (2100 rotations)
CRAZING RESISTANCE	ISO 10545-11	Required	Compliant
FROST RESISTANCE	ISO 10545-12	Required	Compliant
CHEMICAL RESISTANCE <i>ACID AND ALKALI LOW CONCENTRAION</i>	ISO 10545-13	According to the classification stated by the manufacturer	GLA class
CHEMICAL RESISTANCE <i>DOMESTIC USE AND SWIMMING POOL CHEMICALS</i>	ISO 10545-13	Min. GB	Compliant
STAIN RESISTANCE	ISO 10545-14	Min. Class 3	Class 5
			NATURAL
SLIP RESISTANCE	DCOF ANSI A 1371-2012 (Section 9.6)	≥ 0.42 Wet	0.62 Wet
	DIN 51130	-	R10



STONESOURCE