

PALMA
BASALTINE

STONESOURCE



PALMA BASALTINE
PURE

PALMA BASALTINE


	Technical Specifications	Reference Standard	Standard Requirements	Test Results
	Water Absorption	UNI EN ISO 10545-03	< 0.5 %	Meets requirements
	Breaking Strength	UNI EN ISO 10545-04	Minimum: 1300 N	2500 N
	Modulus of Rupture	UNI EN ISO 10545-04	Minimum: 35 N/mm²	> 40 N/mm²
	Shock Resistance	UNI EN ISO 10545-05	Suggested Minimum: e > 0.55	> 0.70
	Resistance to Deep Abrasion	UNI EN ISO 10545-06	Maximum: 175 mm³	175 mm³
	Thermal Shock Resistance	UNI EN ISO 10545-09	Resistant	Meets requirements
	Frost Resistance	UNI EN ISO 10545-12	As Reported	Meets requirements
	Chemical Resistance	UNI EN ISO 10545-13	Domestic Chemical Products: UB / GB Acids and Alkalis: As Reported	GLA / GHA GA
	Stain Resistance	UNI EN ISO 10545-14	Minimum: Class 3	Class 3
PEI	PEI Rating (Scratch Resistance)	ASTM C 1027	As Reported	IV
DCOF	Dynamic Coefficient of Friction (DCOF)	ANSI A137.1	For Level Interior Spaces Expected to be Walked Upon When Wet : > 0.42	0,60
V.2	Shade Variation	Not Available	As Reported	V.2
	Thickness	Not Available	As Reported	10.5
	Number of Screens	Not Available	As Reported	32

1/2 BROKEN JOINT NOT RECOMMENDED



NO

MANUFACTURE RECOMMENDS 1/3 OR LESS STAGGERED SPACING



YES

STONESOURCE



PALMA
BASALTINE



PALMA BASALTINE
NEUTRAL



PALMA BASALTINE PURE

PALMA BASALTINE NEUTRAL

PALMA BASALTINE SLATE

PALMA BASALTINE RAVEN




PALMA BASALTINE RAVEN

PALMA BASALTINE

TECHNICAL PORCELAIN

PURE




24"x48"
RECTIFIED EDGE



15"x30"
RECTIFIED EDGE




24"x24"
RECTIFIED EDGE




12"x24"
RECTIFIED EDGE

3"x24" Bullnose




2"x2" Mosaic
12"x12" sheet



2"x2" Mix Mosaic
12"x12" sheet


NEUTRAL




24"x48"
RECTIFIED EDGE



15"x30"
RECTIFIED EDGE




24"x24"
RECTIFIED EDGE




12"x24"
RECTIFIED EDGE

3"x24" Bullnose




2"x2" Mosaic
12"x12" sheet



2"x2" Mix Mosaic
12"x12" sheet


SLATE




24"x48"
RECTIFIED EDGE



15"x30"
RECTIFIED EDGE




24"x24"
RECTIFIED EDGE




12"x24"
RECTIFIED EDGE

3"x24" Bullnose




2"x2" Mosaic
12"x12" sheet




2"x2" Mix Mosaic
12"x12" sheet


RAVEN



24"x48"
RECTIFIED EDGE



15"x30"
RECTIFIED EDGE




24"x24"
RECTIFIED EDGE




12"x24"
RECTIFIED EDGE

3"x24" Bullnose




2"x2" Mosaic
12"x12" sheet



2"x2" Mix Mosaic
12"x12" sheet


COORDINATING OUTDOOR 2CM (3/4") THICK PAVER
COLLECTION ALSO AVAILABLE

PURE



24"x24" 2CM

NEUTRAL SLATE RAVEN



24"x24" 2CM



24"x24" 2CM



24"x24" 2CM

