



**Mid mesh back heavy duty task 3607M-HVD**


Overall dimensions	27.5"w x 27.5"d x 37/41"h	Weight	40.75 lbs. (armless) 49.75 lbs. (arms) (CR11)
Seat dimensions	20.25"w x 19"d x 17.5/21.5"h	Cubic feet	13 (KND) carton 18.25 (FLA) carton
Seat to top of back	21.25"	COM	1 yd.
Back width	18.5"	COL	20 sq. ft.
Top of arm to floor	25/33" (CR11)		
Top of arm to seat	7.25/11.25" (CR11)		

**Mid upholstered back heavy duty task 3607-HVD**

Overall dimensions	27.5"w x 27.5"d x 37/41"h	Weight	42.75 lbs. (armless) 51.75 lbs. (arms) (CR11)
Seat dimensions	20.25"w x 19"d x 17.5/21.5"h	Cubic feet	13 (KND) carton 18.25 (FLA) carton
Seat to top of back	21.25"	COM	1.25 yds.
Back width	18.5"	COL	25 sq. ft.
Top of arm to floor	25/33" (CR11)		
Top of arm to seat	7.25/11.25" (CR11)		

**Mid impression back heavy duty task 3607T-HVD**

Overall dimensions	27.5"w x 27.5"d x 37/41"h	Weight	41.75 lbs. (armless) 50.75 lbs. (arms) (CR11)
Seat dimensions	20.25"w x 19"d x 17.5/21.5"h	Cubic feet	13 (KND) carton 18.25 (FLA) carton
Seat to top of back	21.25"	COM	1 yd.
Back width	18.5"	COL	20 sq. ft.
Top of arm to floor	25/33" (CR11)		
Top of arm to seat	7.25/11.25" (CR11)		




Standard features	Options available
<ul style="list-style-type: none">• Mid back• Upholstered back will have black mesh backer (3607-HVD)• Tailored seat• Armless• Carbon frame• Body balance control• Upholstered seat with molded seat foam• Carbon nylon base• Hard wheel casters	<ul style="list-style-type: none">• Mesh, Upholstered or Impression back• Arms:<ul style="list-style-type: none">- Height adjustable• Seven mesh colors: Deep Blue, Grey, Pitch, Platinum, Poppy, Snow or Storm• Two impression colors: Pitch or Platinum• Adjustable lumbar support• Polished aluminum base• Soft wheel casters or glides• Fully assembled chair in carton

High mesh back heavy duty task 3615M-HVD

Overall dimensions	27.5"w x 27.5"d x 39.5/43.5"h
Seat dimensions	20.25"w x 19"d x 17.5/21.5"h
Seat to top of back	23.25"
Back width	19.25"
Top of arm to floor	25/33" (CR11)
Top of arm to seat	7.25/11.25" (CR11)

Weight	41.5 lbs. (armless) 50.5 lbs. (arms) (CR11)
Cubic feet	13 (KND) carton 21 (FLA) carton
COM	1 yd.
COL	20 sq. ft.


High elastomer back heavy duty task 3615E-HVD


Overall dimensions	27.5"w x 27.5"d x 39.5/43.5"h
Seat dimensions	20.25"w x 19"d x 17.5/21.5"h
Seat to top of back	23.25"
Back width	19.25"
Top of arm to floor	25/33" (CR11)
Top of arm to seat	7.25/11.25" (CR11)

Weight	43.25 lbs. (armless) 52.25 lbs. (arms) (CR11)
Cubic feet	13 (KND) carton 21 (FLA) carton
COM	1 yd.
COL	20 sq. ft.


High upholstered back heavy duty task 3615-HVD


Overall dimensions	27.5"w x 27.5"d x 39.5/43.5"h
Seat dimensions	20.25"w x 19"d x 17.5/21.5"h
Seat to top of back	23.25"
Back width	19.25"
Top of arm to floor	25/33" (CR11)
Top of arm to seat	7.25/11.25" (CR11)

Weight	43.5 lbs. (armless) 52.5 lbs. (arms) (CR11)
Cubic feet	13 (KND) carton 21 (FLA) carton
COM	1.25 yds.
COL	25 sq. ft.


High impression back heavy duty task 3615T-HVD

Overall dimensions	27.5"w x 27.5"d x 39.5/43.5"h
Seat dimensions	20.25"w x 19"d x 17.5/21.5"h
Seat to top of back	23.25"
Back width	19.25"
Top of arm to floor	25/33" (CR11)
Top of arm to seat	7.25/11.25" (CR11)

Weight	42.5 lbs. (armless) 51.5 lbs. (arms) (CR11)
Cubic feet	13 (KND) carton 21 (FLA) carton
COM	1 yd.
COL	20 sq. ft.





Standard features	Options available
<ul style="list-style-type: none">• High back• Upholstered back will have black mesh backer (3615-HVD)• Tailored seat• Armless• Carbon frame• Body balance control• Upholstered seat with molded seat foam• Carbon nylon base• Hard wheel casters	<ul style="list-style-type: none">• Mesh, Elastomer, Impression or Upholstered back• Arms:<ul style="list-style-type: none">- Height adjustable• Seven mesh colors: Deep Blue, Grey, Pitch, Platinum, Poppy, Snow or Storm• Eight elastomer colors: Clay, Sage, Oat, Deep Blue, Pitch, Platinum, Snow or Storm• Two impression colors: Pitch or Platinum• Adjustable lumbar support• Polished aluminum base• Soft wheel casters or glides• Fully assembled chair in carton

Standard textile selection

<https://ofs.com/resources/textiles>

Frame construction

Seat	<ul style="list-style-type: none">• 5/8" One-piece, multi-core hardwood plywood• Fitted with riveted "T" nuts fixed on both sides of the plywood
Back	<ul style="list-style-type: none">• Polypropylene and nylon• Mesh: 40% elastomer, 60% polyester• Elastomer: Thermoplastic polyurethane• Impression: Inner foam laminated with polyester fabric on both sides, a line design is pressed into material
Upholstery	<ul style="list-style-type: none">• Mesh: 100% high tenacity polyester breathable material that curves across the chair back
Arms	<ul style="list-style-type: none">• Height adjustable arms
Lumbar support	<ul style="list-style-type: none">• Matches frame color• Height from seat = 5.25" / 8.25", Range = 3"
Controls	<ul style="list-style-type: none">• BDB3 – body balance: Weight activated, adjusts to user's body weight, seat height adjustment, back angle adjustment with 3 position limiter, tension control, back height adjustment
Base	<ul style="list-style-type: none">• Nylon: solid injection-molded and fiber glass-reinforced nylon resin• Polished aluminum: manufactured of die-casting process• All bases pass the ANSI/BIFMA strength standards
Cylinder	<ul style="list-style-type: none">• Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria
Casters	<ul style="list-style-type: none">• Heavy-duty nylon twin wheel casters are manufactured of injection-molded engineer grade nylon• 60 mm diameter large pivot barrels
Assembly	<ul style="list-style-type: none">• Self-locking, hardened steel, hex/socket/Phillips head bolts• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration

Foam

Seat	<ul style="list-style-type: none">• 3D Molded foam• 40 IFD• 2 lb. Density• CAL TB 117-2013 Conformant
------	--

Mid mesh back task 3607M

Overall dimensions	27.5"w x 27.5"d x 37.25/41.25"h (STT8) 27.5"w x 27.5"d x 37/41"h (BDB4)	Weight	40.75 lbs. (armless) 44.7 lbs. (arms) (CR13) 45 lbs. (arms) (CR20)	
Seat dimensions	20.25"w x 19"d x 16/20"h	Cubic feet	12.75	
Seat to top of back	21.25"	COM	1 yd.	
Back width	18.5"	COL	20 sq. ft.	
Top of arm to floor	24.5/32.5" (CR13) 26.5/29.75" (CR20)			
Top of arm to seat	7/11" (CR13) 8" (CR20)			

Mid upholstered back task 3607

Overall dimensions	27.5"w x 27.5"d x 37.25/41.25"h (STT8) 27.5"w x 27.5"d x 37/41"h (BDB4)	Weight	42.75 lbs. (armless) 46.75 lbs. (arms) (CR13) 47 lbs. (arms) (CR20)	
Seat dimensions	20.25"w x 19"d x 16/20"h	Cubic feet	12.75	
Seat to top of back	21.25"	COM	1.25 yds.	
Back width	18.5"	COL	25 sq. ft.	
Top of arm to floor	24.5/32.5" (CR13) 26.5/29.75" (CR20)			
Top of arm to seat	7/11" (CR13) 8" (CR20)			

Mid impression back task 3607T

Overall dimensions	27.5"w x 27.5"d x 37.25/41.25"h (STT8) 27.5"w x 27.5"d x 37/41"h (BDB4)	Weight	41.75 lbs. (armless) 46 lbs. (arms) (CR20) 45.75 lbs. (arms) (CR13)	
Seat dimensions	20.25"w x 19"d x 16/20"h	Cubic feet	12.75	
Seat to top of back	21.25"	COM	1 yd.	
Back width	18.5"	COL	20 sq. ft.	
Top of arm to floor	24.5/32.5" (CR13) 26.5/29.75" (CR20)			
Top of arm to seat	7/11" (CR13) 8" (CR20)			

Standard features	Options available
<ul style="list-style-type: none"> Mid back Upholstered back will have black mesh backer (3607) Tailored seat Armless Carbon frame Synchro tilt control with side tension knob Upholstered seat with molded seat foam Carbon nylon base Hard wheel casters 	<ul style="list-style-type: none"> Mesh, Upholstered or Impression back Arms: <ul style="list-style-type: none"> 4D pivoting arms Polished aluminum cantilever arms Seven mesh colors: Deep Blue, Grey, Pitch, Platinum, Poppy, Snow or Storm Two impression colors: Pitch or Platinum Body balance control Seat slider Adjustable lumbar support Polished aluminum base Adjustable headrest Soft wheel casters or glides Fully assembled chair in carton

Standard textile selection

<https://ofs.com/resources/textiles>

Frame construction


Seat	<ul style="list-style-type: none"> 5/8" One-piece, multi-core hardwood plywood Fitted with riveted "T" nuts fixed on both sides of the plywood
Back	<ul style="list-style-type: none"> Polypropylene and nylon: carbon Mesh: 40% elastomer, 60% polyester Impression: Inner foam laminated with polyester fabric on both sides, a line design is pressed into material
Upholstery	<ul style="list-style-type: none"> Mesh: 100% high tenacity polyester breathable material that curves across the chair back
Arms	<ul style="list-style-type: none"> 4D pivoting arms Fixed cantilever aluminum arms
Head rest	<ul style="list-style-type: none"> Material is FoamMesh or upholstery to match seat Added height to chair = 6"/ 9.25", range of upholstered pad = 1.5"
Lumbar support	<ul style="list-style-type: none"> Matches frame color Height from seat = 5.25"/ 8.25", Range = 3"
Controls	<ul style="list-style-type: none"> STT8 - Synchro tilt with side tension knob: adjusts to user's body weight and can tilt free or lock in three positions - optional SS3 seat slider BDB4 - Body balance: weight activated, adjusts to user's body weight, seat height adjustment, back angle adjustment with 2 position limiter, tension control, back height adjustment - optional SS3 seat slider
Seat Slider	<ul style="list-style-type: none"> Range: 2.25" 5 Locking positions
Base	<ul style="list-style-type: none"> Nylon: Solid injection-molded and fiber glass-reinforced nylon resin - Carbon Polished aluminum: Manufactured of die-casting process All bases pass the ANSI/BIFMA strength standards
Cylinder	<ul style="list-style-type: none"> Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria
Casters	<ul style="list-style-type: none"> Heavy-duty nylon twin wheel casters are manufactured of injection-molded engineer grade nylon 60 mm diameter large pivot barrels
Assembly	<ul style="list-style-type: none"> Self-locking, hardened steel, hex/socket/phillips head bolts Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration

Foam

Seat	<ul style="list-style-type: none"> 3D Molded foam 40 IFD 2 lb. Density CAL TB 117-2013 Conformant
------	---

High mesh back task 3615M


Overall dimensions	27.5"w x 27.5"d x 39.75/43.75"h (SST8) 27.5"w x 27.5"d x 39.25/43.25"h (BDB4)	Weight	41.5 lbs. (armless) 45.5 lbs. (arms) (CR13) 45.75 lbs. (arms) (CR20)
Seat dimensions	20.25"w x 19"d x 16.5/20.5"h (SST8) 20.25"w x 19"d x 16/20"h (BDB4)	Cubic feet	12.75
Seat to top of back	23.25"	COM	1 yd.
Back width	19.25"	COL	20 sq. ft.
Top of arm to floor	24.5/32.5" (SST8) 24/32" (BDB4) (CR13) 26.5/29.75" (SST8) 25.5/29.25" (BDB4) (CR20)		
Top of arm to seat	7/11" (CR13) 8" (CR20)		


High elastomer back task 3615E


Overall dimensions	27.5"w x 27.5"d x 39.75/43.75"h (SST8) 27.5"w x 27.5"d x 39.25/43.25"h (BDB4)	Weight	43.25 lbs. (armless) 47.75 lbs. (arms) (CR13) 47.25 lbs. (arms) (CR20)
Seat dimensions	20.25"w x 19"d x 16.5/20.5"h (SST8) 20.25"w x 19 d x 16/20"h (BDB4)	Cubic feet	12.75
Seat to top of back	23.25"	COM	1 yd.
Back width	19.25"	COL	20 sq. ft.
Top of arm to floor	24.5/32.5" (SST8) 24/32" (BDB4) (CR13) 26.5/29.75" (SST8) 25.5/29.25" (BDB4) (CR20)		
Top of arm to seat	7/11" (CR13) 8" (CR20)		


High upholstered back task 3615

Overall dimensions	27.5"w x 27.5"d x 39.75/43.75"h (SST8) 27.5"w x 27.5"d x 39.25/43.25"h (BDB4)	Weight	43.5 lbs. (armless) 47.5 lbs. (arms) (CR13) 47.75 lbs. (arms) (CR20)
Seat dimensions	20.25"w x 19"d x 16.5/20.5"h (SST8) 20.25"w x 19"d x 16/20"h (BDB4)	Cubic feet	12.75
Seat to top of back	23.25"	COM	1.25 yds.
Back width	19.25"	COL	25 sq. ft.
Top of arm to floor	24.5/32.25" (SST8) 24/32" (BDB4) (CR13) 26.5/29.75" (SST8) 25.5/29.25" (BDB4) (CR20)		
Top of arm to seat	7/11" (CR13) 8" (CR20)		


High impression back task 3615T

Overall dimensions	27.5"w x 27.5"d x 39.75/43.75"h (SST8) 27.5"w x 27.5"d x 39.25/43.25"h (BDB4)	Weight	42.5 lbs. (armless) 46.5 lbs. (arms) (CR13) 46.75 lbs. (arms) (CR20)
Seat dimensions	20.25"w x 19"d x 16.5/20.5"h (SST8) 20.25"w x 19"d x 16/20"h (BDB4)	Cubic feet	12.75
Seat to top of back	23.25"	COM	1 yd.
Back width	19.25"	COL	20 sq. ft.
Top of arm to floor	24.5/32.5" (SST8) 24/32" (BDB4) (CR13) 26.5/29.75" (SST8) 25.5/29.25" (BDB4) (CR20)		
Top of arm to seat	7/11" (CR13) 8" (CR20)		





Standard features	Options available
<ul style="list-style-type: none">• High back• Upholstered back will have black mesh backer (3615)• Tailored seat• Armless• Synchro tilt control with side tension knob• Upholstered seat with molded seat foam• Hard wheel casters	<ul style="list-style-type: none">• Mesh, Elastomer, Impression or Upholstered back• Black, Graphite or Chalk frame (Note: base, arm extension and seat pan match frame color)• Arms:<ul style="list-style-type: none">- 4D pivoting- Polished aluminum cantilever• Seven mesh colors: Deep Blue, Grey, Pitch, Platinum, Poppy, Snow or Storm• Eight elastomer colors: Clay, Sage, Oat, Deep Blue, Pitch, Platinum, Snow or Storm• Two impression colors: Pitch or Platinum• Body balance control• Seat slider• Adjustable lumbar support: Black, Graphite or Chalk (matches frame choice)• Polished aluminum base• Adjustable headrest• Soft wheel casters or glides• Fully assembled chair in carton

Standard textile selection

<https://ofs.com/resources/textiles>


Frame construction

Seat	<ul style="list-style-type: none">• 5/8" One-piece, multi-core hardwood plywood• Fitted with riveted "T" nuts fixed on both sides of the plywood
Back	<ul style="list-style-type: none">• Polypropylene and nylon: carbon, graphite and chalk• Mesh: 40% elastomer, 60% polyester• Elastomer: Thermoplastic polyurethane• Impression: Inner foam laminated with polyester fabric on both sides, a line design is pressed into material
Upholstery	<ul style="list-style-type: none">• Mesh: 100% high tenacity polyester breathable material that curves across the chair back
Arms	<ul style="list-style-type: none">• 4D pivoting arms• Fixed cantilever aluminum arms
Head rest	<ul style="list-style-type: none">• Material is FoamMesh or upholstery to match seat• Added height to chair = 6"/ 9.25", range of upholstered pad = 1.5"
Lumbar support	<ul style="list-style-type: none">• Matches frame color choice• Height from seat = 5.25"/ 8.25", Range = 3"
Controls	<ul style="list-style-type: none">• STT8 - Synchro tilt with side tension knob: adjusts to user's body weight and can tilt free or lock in three positions - optional SS3 seat slider• BDB4 - Body balance: Weight activated, adjusts to user's body weight, seat height adjustment, back angle adjustment with 2 position limiter, tension control, back height adjustment - optional SS3 seat slider
Seat slider	<ul style="list-style-type: none">• Range: 2.25"• 5 Locking positions
Base	<ul style="list-style-type: none">• Nylon: solid injection-molded and fiber glass-reinforced nylon resin - Carbon, Graphite or Chalk• Polished aluminum: manufactured of die-casting process• All bases pass the ANSI/BIFMA strength standards
Cylinder	<ul style="list-style-type: none">• Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria
Casters	<ul style="list-style-type: none">• Heavy-duty nylon twin wheel casters are manufactured of injection-molded engineer grade nylon• 60 mm diameter large pivot barrels
Assembly	<ul style="list-style-type: none">• Self-locking, hardened steel, hex/socket/Phillips head bolts• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration


Foam

Seat	<ul style="list-style-type: none">• 3D Molded foam• 40 IFD• 2 lb. Density• CAL TB 117-2013 Conformant
------	--


Mesh back task 3703M - BST4

Overall dimensions	27.5"w x 27.5"d x 31.25/36.25"h	Weight	32 lbs. (armless) 33 lbs. (arms)	
Seat dimensions	19.25"w x 18"d x 15.25/20.25"h	Cubic feet	12.75	
Seat to top of back	13.25"	COM	1 yd.	
Back width	19.75"	COL	20 sq. ft.	
Top of arm to floor	24.25/29.25"			
Top of arm to seat	7.5"			


Mesh back task 3703M - SWT2

Overall dimensions	27.5"w x 27.5"d x 31.5/36.25"h	Weight	34 lbs. (armless) 35 lbs. (arms)	
Seat dimensions	19.25"w x 18"d x 15.5/20.5"h	Cubic feet	12.75	
Seat to top of back	13.25"	COM	1 yd.	
Back width	19.75"	COL	20 sq. ft.	
Top of arm to floor	24.75/29.75"			
Top of arm to seat	7.5"			


Mesh back task 3703M - SWT4

Overall dimensions	27.5"w x 27.5"d x 32/37"h	Weight	33.75 lbs. (armless) 35 lbs. (arms)	
Seat dimensions	19.25"w x 18"d x 15.75/20.75"h	Cubic feet	12.75	
Seat to top of back	13.25"	COM	1 yd.	
Back width	19.75"	COL	20 sq. ft.	
Top of arm to floor	25/30"			
Top of arm to seat	7.5"			


Upholstered back task 3703 - BST4

Overall dimensions	27.5"w x 27.5"d x 31.25/36.25"h	Weight	32.5 lbs. (armless) 33.5 lbs. (arms)	
Seat dimensions	19.25"w x 17"d x 15.25/20.25"h	Cubic feet	12.75	
Seat to top of back	13.25"	COM	1 yd.	
Back width	19.75"	COL	20 sq. ft.	
Top of arm to floor	24.25/29.25"			
Top of arm to seat	7.5"			

Upholstered back task 3703 - SWT2

Overall dimensions	27.5"w x 27.5"d x 31.5/36.5"h	Weight	34.5 lbs. (armless) 35.5 lbs. (arms)	
Seat dimensions	19.25"w x 17"d x 15.5/20.5"h	Cubic feet	12.75	
Seat to top of back	13.25"	COM	1 yd.	
Back width	19.75"	COL	20 sq. ft.	
Top of arm to floor	24.75/29.75"			
Top of arm to seat	7.5"			

Upholstered back task 3703 - SWT4

Overall dimensions	27.5"w x 27.5"d x 32/37"h	Weight	34.25 lbs. (armless) 35.5 lbs. (arms)	
Seat dimensions	19.25"w x 17"d x 15.75/20.75"h	Cubic feet	12.75	
Seat to top of back	13.25"	COM	1 yd.	
Back width	19.75"	COL	20 sq. ft.	
Top of arm to floor	25/30"			
Top of arm to seat	7.5"			

Impression back task 3703T

Overall dimensions	27.5"w x 27.5"d x 31.25/36.25"h (BST4) 27.5"w x 27.5"d x 31.5/36.5"h (SWT2) 27.5"w x 27.5"d x 32/27"h (SWT4)	Weight	32.25 lbs. (armless) (BST4) 34.25 lbs. (armless) (SWT2) 34 lbs. (armless) (SWT4) 33.25 lbs. (arms) (BST4) 35.25 lbs. (arms) (SWT2) 35.25 lbs. (arms) (SWT4)	
Seat dimensions	19.25"w x 18"d x 15.25/20.25"h (BST4) 19.25"w x 18"d x 15.5/20.5"h (SWT2) 19.25"w x 18"d x 15.75/20.75"h (SWT4)	Cubic feet	12.75	
Seat to top of back	13.25"	COM	1 yd.	
Back width	19.75"	COL	20 sq. ft.	
Top of arm to floor	24.25/29.25" (BST4) 24.75/29.75" (SWT2) 25/30" (SWT4)			
Top of arm to seat	7.5"			

Standard features	Options available
<ul style="list-style-type: none"> • Armless • Basic task control • Upholstered seat with molded seat foam • Carbon nylon base • Hard wheel casters 	<ul style="list-style-type: none"> • Mesh, Impression or Upholstered back • Black or Silver frame • Seven mesh colors: Deep Blue, Grey, Pitch, Platinum, Poppy, Snow or Storm • Two impression colors: Pitch or Platinum • Fixed arms (black only) • Controls: <ul style="list-style-type: none"> - SWT2 swivel tilt - SWT4 swivel tilt • Polished aluminum base • Soft wheel casters • Glides • Fully assembled chair in carton

Standard textile selection

<https://ofs.com/resources/textiles>


Frame construction

Seat	<ul style="list-style-type: none"> • Polypropylene
Back	<ul style="list-style-type: none"> • Polypropylene and nylon • Mesh: 40% elastomer, 60% polyester • Impression: Inner foam laminated with polyester fabric on both sides, a line design is pressed into material
Upholstery	<ul style="list-style-type: none"> • Mesh: 100% high tenacity polyester breathable material that curves across the chair back
Arms	<ul style="list-style-type: none"> • Fixed
Controls	<ul style="list-style-type: none"> • BST4 - Basic task: Seat height adjustment • SWT2 - Swivel tilt: Seat height adjustment, seat and back tilt adjustment and tension control • SWT4 - Swivel tilt: Tilt seat, seat height adjustment
Base	<ul style="list-style-type: none"> • Nylon: Solid injection-molded and glass-reinforced nylon resin • Polished aluminum: Manufactured of die-casting process • All bases pass the ANSI/BIFMA strength standards
Cylinder	<ul style="list-style-type: none"> • Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria
Casters	<ul style="list-style-type: none"> • Nylon twin wheel casters are manufactured of injection-molded engineer grade nylon • 60 mm diameter large pivot barrels
Assembly	<ul style="list-style-type: none"> • Self-locking, hardened steel, hex/socket/Phillips head bolts • Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration • Back and seat are held together with upholstery clips


Foam

Seat	<ul style="list-style-type: none"> • 3D Molded foam • 5.58 lb. Density • 36 IFD • CAL TB 117-2013 Conformant
------	--


Mesh back conference task 3705M

Overall dimensions	29.25"w x 29.25"d x 33"h (BST4) 29.25"w x 29.25"d x 34"h (SWT3)	Weight	32 lbs. (armless) (BST4) 33.25 lbs. (arms) (SWT3) 33.5 lbs. (armless) (BST4) 34.75 lbs. (arms) (SWT3)	
Seat dimensions	19.25"w x 18"d x 18"h (BST4) 19.25"w x 18"d x 18.25"h (SWT3)	Cubic feet	10.5	
Seat to top of back	13.25"	COM	1 yd.	
Back width	19.75"	COL	20 sq. ft.	
Top of arm to floor	26.25" (BST4) 27" (SWT3)			
Top of arm to seat	7.5"			

Upholstered back conference task 3705

Overall dimensions	29.25"w x 29.25"d x 33"h (BST4) 29.25"w x 29.25"d x 34"h (SWT3)	Weight	32.5 lbs. (armless) (BST4) 33.75 lbs. (arms) (BST4) 34 lbs. (armless) (SWT3) 35.25 lbs. (arms) (SWT3)	
Seat dimensions	19.25"w x 17"d x 18"h (BST4) 19.25"w x 17"d x 18.25"h (SWT3)	Cubic feet	12.75	
Seat to top of back	13.25"	COM	1 yd.	
Back width	19.75"	COL	20 sq. ft.	
Top of arm to floor	26.25" (BST4) 27" (SWT3)			
Top of arm to seat	7.5"			

Impression back conference task 3705T

Overall dimensions	29.25"w x 29.25"d x 33"h (BST4) 29.25"w x 29.25D x 34"h (SWT3)	Weight	32.25 lbs. (armless) (BST4) 33.5 lbs. (arms) (BST4) 33.5 lbs. (armless) (SWT3) 35 lbs. (arms) (SWT3)	
Seat dimensions	19.25"w x 18"d x 18"h (BST4) 19.25"w x 18"d x 18.25"h (SWT3)	Cubic feet	10.5	
Seat to top of back	13.25"	COM	1 yd.	
Back width	19.75"	COL	20 sq. ft.	
Top of arm to floor	26.25" (BST4) 27" (SWT3)			
Top of arm to seat	7.5"			

Standard features	Options available
<ul style="list-style-type: none"> • Armless • Basic task control • Upholstered seat with molded seat foam • Polished aluminum 4-star base • High glides 	<ul style="list-style-type: none"> • Mesh, Impression or Upholstered back • Seven mesh colors: Deep Blue, Grey, Pitch, Platinum, Poppy, Snow or Storm • Two impression colors: Pitch or Platinum • Black or Silver frame • Fixed arms (black only) • Control: basic swivel • Fully assembled chair in carton



Standard textile selection

<https://ofs.com/resources/textiles>

Frame construction

- | | |
|------------|---|
| Seat | <ul style="list-style-type: none">• Polypropylene |
| Back | <ul style="list-style-type: none">• Polypropylene and nylon• mesh: 40% elastomer, 60% polyester• Impression: Inner foam laminated with polyester fabric on both sides, a line design is pressed into material |
| Upholstery | <ul style="list-style-type: none">• Mesh: 100% high tenacity polyester breathable material that curves across the chair back |
| Arms | <ul style="list-style-type: none">• Fixed |
| Controls | <ul style="list-style-type: none">• BST4 - Basic control suitable for general office tasking and occasional typing or computer use• SWT3 - Basic swivel control, basic control suitable for general office tasking and occasional typing or computer use |
| Base | <ul style="list-style-type: none">• Four-star polished aluminum base |
| Cylinder | <ul style="list-style-type: none">• Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria |
| Glides | <ul style="list-style-type: none">• Nylon<ul style="list-style-type: none">- Height from seat: 1 1/4" h x 2" diameter base- 7/16" D-ring stem |
| Assembly | <ul style="list-style-type: none">• Self-locking, hardened steel, hex/socket/phillips head bolts• Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration• Back and seat are held together with upholstery clips |

Foam

- | | |
|------|---|
| Seat | <ul style="list-style-type: none">• 3D Molded foam• 5.58 lb. Density• 36 IFD• CAL TB 117-2013 Conformant |
|------|---|

Light task 3805

Overall dimensions	27.5"w x 27.5"d x 28.5/33.75"h (BST4) 27.5"w x 27.5"d x 29.5/34.75"h (SWT2)	Weight	33.5 lbs. (armless) (BST4) 36.5 lbs. (arms) (SWT2) 35.5 lbs. (armless) (BST4) 38.75 lbs. (arms) (SWT2)	
Seat dimensions	17.75"w x 17.5"d x 14.75/20"h (plastic) 18.5"w x 17.75"d x 15.5/20.75"h (upholstered)	Cubic feet	12.75	
Seat to top of back	12.75"	COM	1 yd.	
Back width	18"	COL	20 sq. ft.	
Top of arm to floor	22.25/27.5"			
Top of arm to seat	7.5"			

Standard features	Options available
<ul style="list-style-type: none"> Molded plastic back Armless Basic task control Black nylon base Hard wheel casters 	<ul style="list-style-type: none"> Graphite or Chrome frame Fixed arms (arm colors match plastic) Plastic or upholstered seat with molded seat foam or plastic seat Five plastic colors: Deep Blue, Pitch, Platinum, Snow or Storm Control: Swivel tilt Fully assembled chair in carton Soft wheel casters Glides Polished aluminum base

Standard textile selection

<https://ofs.com/resources/textiles>

Frame construction

Seat	<ul style="list-style-type: none"> Polypropylene
Back	<ul style="list-style-type: none"> Polypropylene
Arms	<ul style="list-style-type: none"> Fixed arms with polypropylene arm caps
Controls	<ul style="list-style-type: none"> BST4 - Basic task: Seat height adjustment SWT2 - Swivel tilt: Seat height adjustment, seat and back tilt adjustment and tension control
Base	<ul style="list-style-type: none"> Nylon: solid injection-molded and glass-reinforced nylon resin Polished aluminum: manufactured of die-casting process All bases pass the ANSI/BIFMA strength standards
Cylinder	<ul style="list-style-type: none"> Variety of class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria
Casters	<ul style="list-style-type: none"> Nylon twin wheel casters are manufactured of injection-molded engineer grade nylon 60 mm diameter large pivot barrels
Assembly	<ul style="list-style-type: none"> Self-locking, hardened steel, hex/socket/phillips head bolts Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration

Foam

Seat	<ul style="list-style-type: none"> 3D Molded foam 58 IFD 5.14 Density CAL TB 117-2013 Conformant
------	--