

Mingle

European Beech

Mid back F45016

Overall dimensions	27"w x 26"d x 40/42.75"h	Weight	63 lbs.
Seat dimensions	20.25"w x 18.5"d x 18.5/21.25"h	Cubic feet	35
Seat to top of back	22.25"	СОМ	3.25 yds.
Top of arm to floor	25.75-28.5"	COL	65 sq. ft.
Top of arm to seat	7.25"		



Mid back F45216

Exposed wood

Overall dimensions	27"w x 26"d x 40/42.75"h	Weight	63 lbs.
Seat dimensions	20.25"w x 18.5"d x 18.5/21.25"h	Cubic feet	35
Seat to top of back	22.25"	COM	3 yds.
Top of arm to floor	25.75-28.5"	COL	60 sq. ft.
Top of arm to seat	7.25"		



Exposed wood	l European	Beech

Standard features	Optional features
Mid back	Wood base caps
 Molded curved plywood shell 	 5-prong steel swivel base with solid wood base caps
Pneumatic knee tilt	5 dual wheel hooded - Black or Brass
Fully upholstered arms	5 dual wheel hardwood floor - Black or Brass
5-prong black polyurethane bases	Brass hooded ball
Dual-wheel hooded black casters	Edge guards
	Wood base caps

Mid back F46016

26"w x 25"d x 39/41.75"h	Weight	63 lbs.	
21"w x 18"d x 18.5/21.25"h	Cubic feet	35	
22"	COM	3 yds.	
25-27.75"	COL	60 sq. ft.	
6.5"			06888 06880
European Beech			
	21"w x 18"d x 18.5/21.25"h 22" 25-27.75" 6.5"	21"w x 18"d x 18.5/21.25"h	21"w x 18"d x 18.5/21.25"h Cubic feet 35 22" COM 3 yds. 25-27.75" COL 60 sq. ft. 6.5"



Overall dimensions	25.75"w x 25"d x 39/41.75"h	Weight	63 lbs.	
Seat dimensions	21"w x 18"d x 18.5/21.25"h	Cubic feet	35	<u> </u>
Seat to top of back	22"	СОМ	3 yds.	
Top of arm to floor	25-27.75"	COL	60 sq. ft.	
Top of arm to seat	6.5"			6666 66600
Exposed wood	European Beech			



ofs.com imagine a place* 800.521.5381 Spec sheet 1 of 2



Mingle

Standard textile & finish selection

https://ofs.com/resources/textiles http://ofs.com/resources/finishes

Frame construction

Seat • Upholstery grade molded plywood shell

Back • Upholstery grade molded plywood shell

Upholstery • All fabric and leather pieces are cut with automated cutters that utilize precise patterns

Upholstered arms: The arm is made of polyurethane free rising foam that is reinforced with a fiberglass
 closus insert and is environd with foam and upholstery.

sleeve insert and is covered with foam and upholstery

• Wood arms: A solid hardwood assembly that is attached to the shell with brackets

Assembly • Wood, metal and plastic components fastened by bolts with thread locker

Foam

Seat • 3" Premium grade foam

• 40 lb. Compression

• 2.2 Density

• .75 oz. Fiber overlay on top

k • 1.75" Premium grade foam

• 21 lb. Compression

• 1.1 Density

• .75 oz. Fiber overlay on top

Base caps

• 5-prong steel swivel base with solid wood base cap options



ofs.com imagine a place* **800.521.5381** Spec sheet 2 of 2