


Mesh back sled base 114036


Overall dimensions	23.5"w x 24.25"d x 35.25"h	Weight	19 lbs.
Seat dimensions	20"w x 17.75"d x 18.5"h	Cubic feet	15
Seat to top of back	1"	COM	.75 yd.
Top of arm to floor	26.25"	COL	15 sq. ft.
Top of arm to seat	7.75"		



Standard features	Options available
<ul style="list-style-type: none"> • Mesh back with upholstered seat • Powder coated base • Fixed arms 	<ul style="list-style-type: none"> • Frame in Carbon or Chalk • All standard and studio powder coats on base • Seven mesh colors

Mesh back 5 star base 114015

Overall dimensions	26"w x 27"d x 33.5/38"h	Weight	21 lbs.
Seat dimensions	20"w x 17.75"d x 16.5/21"h	Cubic feet	15
Seat to top of back	18"	COM	.75 yd.
Top of arm to floor	26"/29.5"	COL	15 sq. ft.
Top of arm to seat	7.75"		



Standard features	Options available
<ul style="list-style-type: none"> • Mesh back with upholstered seat • Nylon base with caster • Fixed arms • Knocked down 	<ul style="list-style-type: none"> • Frame in Carbon or Chalk • Carbon or Chalk nylon base • Black hard wheel or soft wheel casters • Seven mesh colors • Fully assembled

Mesh back 4 star base 114115

Overall dimensions	23.5"w x 23.75"d x 35.5"h	Weight	21 lbs.
Seat dimensions	20"w x 17.75"d x 18"h	Cubic feet	15
Seat to top of back	18"	COM	.75 yd.
Top of arm to floor	26.25"	COL	15 sq. ft.
Top of arm to seat	7.75"		



Standard features	Options available
<ul style="list-style-type: none"> • Mesh back with upholstered seat • Powder coated base • Fixed arms 	<ul style="list-style-type: none"> • Frame in Carbon or Chalk • All standard and studio powder coateds on base • Glides, black hard wheel or soft wheel casters • Seven mesh colors



Standard textile selection

<https://ofs.com/resources/textiles>

Frame construction

Shell	<ul style="list-style-type: none">• Injection-molded, glass-reinforced nylon resin
Upholstery	<ul style="list-style-type: none">• Mesh: constructed of 40% elastomer, 60% polyester• All mesh colors conform to CAL Tech Bulletin 117-2013
Arms	<ul style="list-style-type: none">• Integrated fixed loop arms
Seat Foam	<ul style="list-style-type: none">• Molded foam with a density of 3 pounds per cubic foot• CAL TB 117-2013 compliant
Control	<ul style="list-style-type: none">• 114015 only: Swivel tilt with 1 position lock
Base	<ul style="list-style-type: none">• 5 star Injection molded, glass reinforced nylon resin on model 114015• 4 star cast aluminum on model 114115• Cantilever steel tube base on model 114036
Cylinder	<ul style="list-style-type: none">• Class 4 gas cylinder provides height adjustment of 4.5" on model 114015• Swivel post without height adjustment on model 114115
Casters	<ul style="list-style-type: none">• Twin wheel casters manufactured of injection molded nylon resin• 60mm diameter hoodless design
Assembly	<ul style="list-style-type: none">• Self locking, hardened steel, hex/Phillips head bolts