


Edge	
 <p>Square</p>	 <p>Miter detail</p>

Standard finish selection

<https://ofs.com/resources/finishes>

- | | |
|--------|---|
| Veneer | <ul style="list-style-type: none"> • Grain runs horizontal on vertical surfaces • Quartered veneers |
| Paint | <ul style="list-style-type: none"> • White available on overlays and door/drawer fronts |

Worksurfaces

- 1.5" thick worksurfaces feature 3-ply construction
- Primary worksurfaces are profiled on approach and user sides
- Semi-fill finish on worksurfaces
- Trapezoid conference tables have the end panels mitered to the worksurface
- All overlay models create a layered vertical and horizontal plane
- Drawer fronts and doors overlay tops/worksurfaces

Drawers

- Drawer sides and back are .4375" thick 9-ply baltic birch plywood and is assembled using dowel construction
- Drawer bottoms are .25" thick.
- Interiors are sanded and UV finished
- High quality suspensions with positive cushioned in-out stops, steel ball bearings, and zinc finish to ensure a smooth ride
- Filing hardware is black powder coated to prevent corrosion
- File drawers accommodate letter or legal filing
- Credenza drawers are full-extension touch release suspensions

Chassis assembly

- Butt-joint construction
- Structural joints secured by 16-gauge steel angle brackets, post and cam and wood glue blocks for ultimate stability
- Adjustable levelers feature insert nuts to prevent glide tear-out
- Ships fully assembled

Tops

- Tops are 1.5" thick and are supported with stretcher rails
- Conference tables and extension tops have a square edge
- Conference tops have a veneer edge
- Under-top mending plates and butterfly bolts ensure permanent connection on multiple piece tops
- Multi-piece tops are joined together with metal plates and wood screws

Conference base

- Panel base

Wire management

- Grommet in media console center credenza

Features

- SCS Indoor Advantage Gold Certified