




High mesh back task 88017 (low cylinder)

Overall dimensions	27.5"w x 27.5"d x 40.25/43.25"h	Weight	27 lbs. (armless) 31 lbs. (arms)	
Seat dimensions	20"w x 18"d x 16.5/19.5"h	Cubic feet	12.75	
Seat to top of back	23.75"	COM	1.25 yds.	
Back width	18.25"	COL	25 sq. ft.	
Top of arm to floor	25.25/32.25"			
Top of arm to seat	8/12"			

High mesh back task 88017 (standard cylinder)

Overall dimensions	27.5"w x 27.5"d x 40.25/44.25"h	Weight	28 lbs. (armless) 32 lbs. (arms)	
Seat dimensions	20"w x 18"d x 17.5/21.5"h	Cubic feet	12.75	
Seat to top of back	23.75"	COM	1.25 yds.	
Back width	18.25"	COL	25 sq. ft.	
Top of arm to floor	25.75/33.75"			
Top of arm to seat	8/13"			

High mesh back task 88017 (high cylinder)

Overall dimensions	27.5"w x 27.5"d x 41.25/46.25"h	Weight	29 lbs. (armless) 33 lbs. (arms)	
Seat dimensions	20"w x 18"d x 18.5/22.5"h	Cubic feet	12.75	
Seat to top of back	23.75"	COM	1.25 yds.	
Back width	18.25"	COL	25 sq. ft.	
Top of arm to floor	26.75/35.75"			
Top of arm to seat	8/14"			

Standard features	Options available
<ul style="list-style-type: none"> • High back • Mesh back • Armless • Body balance control • Hard wheel casters • ANSI/BIFMA X5.1 Conformant • CAL TB 117-2013 Conformant 	<ul style="list-style-type: none"> • Six mesh colors: Dove, Granite, Indigo, Ocean, Raven, Toast • 4D pivoting arms • Carbon or Graphite arm pads • Carbon, Chalk or Graphite frame • Carbon, Chalk or Graphite lumbar support • Low, standard or high cylinder • Seat slider • Carbon, Chalk or Graphite nylon base • Polished aluminum base • Soft wheel casters • Glides • Fully assembled chair in carton

Standard textile selection

- <https://ofs.com/resources/textiles>
- All textiles meet CAL TB 117-2013

Frame construction

Seat	<ul style="list-style-type: none"> 5/8" One-piece multi core hardwood plywood seat Fitted with riveted "T" nuts fixed on both sides of the plywood
Back	<ul style="list-style-type: none"> Plastic: Injection-molded, glass-reinforced nylon resin
Upholstery	<ul style="list-style-type: none"> Mesh: Woven Polyester yarn (58.7%) and Polyelastomer monofilament (41.3%) All mesh colors and fabrics meet CAL Tech Bulletin 117-2013
Arms	<ul style="list-style-type: none"> 4D Pivoting arms: A multi-adjustable arm rest with height adjustment, width adjustment (arm pads only), frontward/rearward sliding (arm pads only), and inward/outward pivot (arm pads only)
Arm Pads	<ul style="list-style-type: none"> 2 Color options: Carbon or Graphite <ul style="list-style-type: none"> (Pad color options available on Carbon and Graphite arms only, Chalk arms come standard with Graphite arm pads)
Lumbar Support	<ul style="list-style-type: none"> 3 Color options: Carbon, Chalk or Graphite <ul style="list-style-type: none"> - Depending on back frame color selection Height from seat = 6.75/8.5", Range = 1.75"
Control	<ul style="list-style-type: none"> R4 - Body Balance: Ergonomic and weight activated, adjusts to user's body weight with a 3 position tilt limiter - optional SS8 Seat Slider
Seat Slider	<ul style="list-style-type: none"> Range: 2.25" 5 Locking positions
Base	<ul style="list-style-type: none"> 4 color options: Carbon, Chalk, Graphite, or Polished aluminum Nylon: solid injection-molded and glass-reinforced nylon resin Polished Aluminum: manufactured of die cast Aluminum All bases pass the ANSI/BIFMA strength and durability standards
Cylinder	<ul style="list-style-type: none"> 3 Cylinder height options: Low, standard or high Variety of Class 4 gas cylinders meet all applicable ANSI/BIFMA performance standards and GSA intensive use performance standards; including cyclic bending resistance criteria
Casters	<ul style="list-style-type: none"> Twin wheel casters manufactured of injection-molded engineer grade nylon 60 mm diameter large pivot barrels
Assembly	<ul style="list-style-type: none"> Self-locking, hardened steel, slotted/Phillips head bolts Bolts treated with "NYLOK", a locking compound designed to prevent bolts from loosening due to vibration

Foam

- | | |
|------|---|
| Seat | <ul style="list-style-type: none"> 2.25" 3D Molded foam 42 IFD 4.6 lb. Density CAL TB 117-2013 Conformant |
|------|---|