

Style	Assimilate	Concentric
Construction	Hand Tufted, Tip-Sheared	Hand Tufted, Cut Pile
Face Fiber	100% New Zealand Wool	85% New Zealand Wool/15% Vicose
Face Weight	88 oz/yd² (2,983 g/m²)	88 oz/yd² (2,983 g/m²)
Pile Thickness	0.314" (8 mm)	0.433" (11 mm)
Fiber Count	226 Tex., 1/20 Dewsbury	226 Tex., 1/20 Dewsbury(Wool)/3.96 Nm 2/16 (Viscose)
Rows per Inch	6 (23.62 per 10 cm)	6 (23.62 per 10 cm)
Stitches Per Inch	5 (19.68 per 10 cm)	5 (19.68 per 10 cm)
Twist	125 twists per m (Wool)	125 twists per m (Wool)
Ply	5 Ply Wool	5 Ply Wool/ 5 Ply Viscose
Dye Method	Skein	Skein
Colors*	2	4
Mothproofing	Perigen	Perigen
Backing Weave	Basket Weave	Basket Weave
Backing Content	Cotton and Polyester	Cotton and Polyester
Sizes*	5'x 8' (1.52 m x 2.44 m)	5'x 8' (1.52 m x 2.44 m)
	8' x 11' (2.44 m x 3.35 m)	8' x 11' (2.44 m x 3.35 m)
	10' x 14' (3.05 m x 4.27 m)	10' x 14' (3.05 m x 4.27 m)
ADA Compliant	Manufactured to meet ADA Requirements	Manufactured to meet ADA Requirements
Testing		
Flammability 16 CFR 1631	Passes	Passes
(Methenamine Pill Test - ASTM D2859)		
Warranty		

Limited 2-year Repair or Replacement

^{*}Custom colors and sizes available



Style	Lines II	Lumiere
Construction	Hand Tufted, Cut Pile	Hand Tufted, Cut Pile
Face Fiber	70% New Zealand Wool/30% Viscose	50% New Zealand Wool/50% Viscose
Face Weight	88 oz/yd² (2,983 g/m²)	96 oz/yd² (3,250 g/m²)
Pile Thickness	0.433" (11 mm)	0.393" (10 mm)/ 0.433" (11 mm)**
Fiber Count	226 Tex., 1/20 Dewsbury(Wool)/3.96 Nm 2/16 (Viscose)	226 Tex., 1/20 Dewsbury(Wool)/3.96 Nm 2/16 (Viscose)
Rows per Inch	6 (23.62 per 10 cm)	6 (23.62 per 10 cm)
Stitches Per Inch	5 (19.68 per 10 cm)	7 (27.56 per 10 cm)
Twist	125 twists per m (Wool)	125 twists per m (Z)
Ply	5 Ply Wool/5 Ply Viscose	2 Ply Wool/ 2 Ply Viscose
Dye Method	Skein	Skein
Colors*	4	4
Mothproofing	Perigen	Perigen
Backing Weave	Basket Weave	Basket Weave
Backing Content	Cotton and Polyester	Cotton and Polyester
Sizes*	5'x 8' (1.52 m x 2.44 m)	5'x 8' (1.52 m x 2.44 m)
	8' x 11' (2.44 m x 3.35 m)	8' x 11' (2.44 m x 3.35 m)
	10' x 14' (3.05 m x 4.27 m)	10' x 14' (3.05 m x 4.27 m)
ADA Compliant	Manufactured to meet ADA Requirements	Manufactured to meet ADA Requirements
Testing		
Flammability 16 CFR 1631	Passes	Passes
(Methenamine Pill Test - ASTM D2859)		
Warranty		

Limited 2-year Repair or Replacement

All products are handmade and there may be slight variations from the above chart in the final product.

The above specifications are subject to change without prior notice as and when required for maintaining high product quality standards

^{*} Custom colors and sizes available

^{**} Loop pile height/ Cut pile height



Style	Progression	Seville Row
Construction	Hand Tufted, Cut & Loop	Hand Tufted, Cut Pile
Face Fiber	100% New Zealand Wool	50% New Zealand Wool/50% Viscose
Face Weight	88 oz/yd² (2,983 g/m²)	121 oz/yd² (4,102 g/m²)
Pile Thickness	0.314" (8mm)/ 0.354" (9 mm)**	0.314" (8mm)/ 0.354" (9 mm)**
Fiber Count	226 Tex., 1/20 Dewsbury (Wool)	226 Tex., 1/20 Dewsbury(Wool)/3.96 Nm 2/16 (Viscose)
Rows per Inch	6 (23.62 per 10 cm)	6 (23.62 per 10 cm)
Stitches Per Inch	5 (19.68 per 10 cm)	5 (19.68 per 10 cm)
Twist	125 twists per m (Wool)	125 twists per m (Wool)
Ply	5 Ply Wool	5 Ply Wool/ 5 Ply Viscose
Dye Method	Skein	Skein
Colors*	2	4
Mothproofing	Perigen	Perigen
Backing Weave	Basket Weave	Basket Weave
Backing Content	Cotton and Polyester	Cotton and Polyester
Sizes*	5'x 8' (1.52 m x 2.44 m)	5'x 8' (1.52 m x 2.44 m)
	8' x 11' (2.44 m x 3.35 m)	8' x 11' (2.44 m x 3.35 m)
	10' x 14' (3.05 m x 4.27 m)	10' x 14' (3.05 m x 4.27 m)
ADA Compliant	Manufactured to meet ADA Requirements	Manufactured to meet ADA Requirements
Testing		
Flammability 16 CFR 1631	Passes	Passes
(Methenamine Pill Test - ASTM D2859)		
Warranty		

Limited 2-year Repair or Replacement

All products are handmade and there may be slight variations from the above chart in the final product.

The above specifications are subject to change without prior notice as and when required for maintaining high product quality standards

^{*} Custom colors and sizes available

^{**} Loop pile height/ Cut pile height



Style	Structure	Urban Grid
Construction	Hand Tufted, Cut Pile	Hand Tufted, Cut & Loop
Face Fiber	85% New Zealand Wool/15% Viscose	100% New Zealand Wool
Face Weight	88 oz/yd² (2,983 g/m²)	121 oz/yd² (4,102 g/m²)
Pile Thickness	0.433" (11 mm)	0.314" (8 mm)/ 0.472" (12 mm)**
Fiber Count	226 Tex., 1/20 Dewsbury(Wool)/3.96 Nm 2/16 (Viscose)	226 Tex., 1/20 Dewsbury (Wool)
Rows per Inch	6 (23.62 per 10 cm)	6 (23.62 per 10 cm)
Stitches Per Inch	5 (19.68 per 10 cm)	5 (19.68 per 10 cm)
Twist	125 twists per m (Wool)	125 twists per m (Wool)
Ply	5 Ply Wool/ 5 Ply Viscose	5 Ply Wool
Dye Method	Skein	Skein
Colors*	4	2
Mothproofing	Perigen	Perigen
Backing Weave	Basket Weave	Basket Weave
Backing Content	Cotton and Polyester	Cotton and Polyester
Sizes*	5'x 8' (1.52 m x 2.44 m)	5'x 8' (1.52 m x 2.44 m)
	8' x 11' (2.44 m x 3.35 m)	8' x 11' (2.44 m x 3.35 m)
	10' x 14' (3.05 m x 4.27 m)	10' x 14' (3.05 m x 4.27 m)
ADA Compliant	Manufactured to meet ADA Requirements	Manufactured to meet ADA Requirements
Testing		
Flammability 16 CFR 1631 (Methenamine Pill Test - ASTM D2859)	Passes	Passes
Warranty		

Limited 2-year Repair or Replacement

^{*} Custom colors and sizes available

^{**} Loop pile height/ Cut pile height