

## Carthage Legacy

Style	Carthage Legacy 20oz (Modular)	Carthage Legacy 26oz (Modular)
Construction	Graphic Loop Pile	Graphic Loop Pile
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Yarn/Solution	Yarn/Solution
Guage	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10 (39.37 per 10 cm)	12 (47.24 per 10 cm)
Density	7,500 (278.68 kg/m <sup>3</sup> )	9,176 (340.96 kg/m <sup>3</sup> )
Pile Thickness	0.096" (2.44 mm)	0.102" (2.59 mm)
Weight	20 oz/yd <sup>2</sup> (678 g/m <sup>2</sup> )	26 oz/yd <sup>2</sup> (881 g/m <sup>2</sup> )
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular
Size	24" x 24" (60.96 cm x 60.96 cm)	24" x 24" (60.96 cm x 60.96 cm)
Colors	20	20
Packagaing	8 yd <sup>2</sup> / 18 Tiles	8 yd <sup>2</sup> / 18 Tiles
Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive
Installation Method	Monolithic	Monolithic
<b>Testing</b>		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5 - severe	3.5 - severe
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing Warranty	
	Limited 15-Year XGUARD® Stain Resistant Warranty	
	Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.