



Color Anchor II Collection

Mannington
COMMERCIAL



Cover: Color Anchor II (Modular) - Walnut 82010 and Inlet 34019
Installation Method - Vertical Ashlar

Above: Color Anchor II (Modular) - Walnut 82010 and Inlet 34019
Installation Method - Vertical Ashlar

Color Anchor II solids are recommended to be used as accents, inserts and borders to enhance your design.



Color Anchor II (Modular) - Onyx 95007
Installation Method - Vertical Ashlar



Color Anchor II (Modular) - Onyx 95007 and Terra Cotta 64018
Color Anchor LVT Stride - London Fog C139
Installation Method - Vertical Ashlar, Custom

Proven by Third-Party Testing

Every carpet we make at Mannington Commercial is third-party tested and proven to exceed industry standards in appearance retention, texture retention, fire safety factors and static generation, and our modular carpet exceeds industry standards in dimensional stability – so you can be sure that the carpet you specify will perform for years to come.



Easier to Maintain

- > XGUARD® Stain Resistant Technology provides long-term stain resistance for our space dye products.
- > ColorSafe® Bleach Resistant Technology resists color fade-out from bleach spills for our space dye products.
- > Moisture-barrier backings are built to withstand aggressive wet cleanings.

Backing Advantages

- > Infinity® 2 Modular backing provides exceptional performance with a moisture barrier.
- > Infinity® 2 Modular backing offers superior tuft bind and dimensional stability with a limited lifetime warranty.

Sustainable Solutions

- > Supported with third party verified EPDs and HPDs.
- > Infinity® 2 backing is NSF/ANSI 140 Gold Certified and contains recycled content.
- > Recognizing the impact that the built environment can have on Earth's climate and health, Mannington Commercial is improving operations and offsetting cradle-to-gate embodied carbon by 105% on this collection, as part of our commitment to helping customers take positive action through their projects

TARR

- > Color Anchor carpet tile was specifically designed with a minimum of 4.0 TARR rating for use in severe environments with rigorous foot traffic. This includes public areas, lobbies and dining facilities as well as transportation service areas such as airports. Our TARR rating is tested and verified by an independent lab.

No Moisture Testing Required*

Solutions crafted for high-moisture conditions. Defeat moisture issues with carpet backings that do not require moisture testing*.

We have solutions for broadloom and modular carpet to make moisture worries evaporate. From backing options to adhesives to a dry installation system, explore solutions that defeat moisture concerns while enhancing the performance of your floor.

	Infinity 2 Pressure Sensitive Adhesive	XpressStep™ Spray Adhesive	FreLock Tabs	Integra-2 Adhesive	Ultra Adhesive
Infinity® 2 Modular Backing	✓	✓	✓		
Infinity® 2 MG Modular Backing	✓	✓	✓		
Infinity® 2 MG Cushion Modular Backing	✓	✓			
Integra® HP Broadloom Backing				✓	
UltraBac® RE Broadloom Backing					✓

* Assumes intact vapor barrier, no standing water or stained concrete, no hydrostatic pressure, and for our broadloom backings (Integra® HP and UltraBac® RE) pH levels must never exceed 10. Please refer to our installation instructions for further details.

Color Anchor II

Style	Color Anchor II (Modular)
Construction	Patterned Loop
Face Fiber	Type 6,6 Nylon
Dye Method	Solution
Gauge	1/12 (47.24 per 10 cm)
Stitches Per Inch	9.33 (36.73 per 10 cm)
Density	5,934 (220.50 kg/m³)
Pile Thickness	0.091" (2.31 mm)
Weight	15 oz/yd² (509 g/m²)
Backing Type	Infinity® 2 Modular
Sizes	12" x 36" (30.48 x 91.44 cm) 24" x 24" (60.96 x 60.96 cm)
Colors	24*
Packaging	12 x 36 - 5.328 yd² / 16 Tiles 24 x 24 - 8 yd² / 18 Tiles
Adhesive	Infinity 2 Adhesive
Installation Method	Horizontal Brick Ashlar, Vertical Ashlar, Monolithic, Herringbone
*Color Anchor II solids are recommended to be used as accents, inserts and borders to enhance your design.	
Testing	
Dimensional Stability (Aachen Test)	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²
Smoke Density (ASTM E662)	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR	4.0
Environmental Data	
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	Third Party Verified EPD, HPD
Carbon Offset	105% Cradle to Gate (A1-A3), see website for additional information
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered
Warranty	
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262