



Glitch Art Collection

Mannington
COMMERCIAL



Cover: **Cross Talk** (Modular) - Plasma Effect 34411
Above: **Cross Talk** (Modular) - Video Decoder 14403
Installation - Horizontal Brick Ashlar



Hub (Modular) - Plasma Effect 34411
Installation - Horizontal Brick Ashlar



Hub (Modular) - Video Decoder 14403
Installation - Horizontal Brick Ashlar



Mainboard (Modular) - Plasma Effect 34411
Installation - Horizontal Brick Ashlar



Mainboard (Modular) - Audio Tag 12401
Installation - Horizontal Brick Ashlar



Circuit (Modular) - Plasma Effect 34411
Installation - Horizontal Brick Ashlar



Circuit (Broadloom) - Video Decoder 14403



Hub, Cross Talk (Modular) - Video Decoder 14403
Installation - Horizontal Brick Ashlar

Custom Accent Colors

Select your own accent stripe color in Mainboard, Hub or Cross Talk patterns for a personalized space. Available in 30 colors with a 500 square yard minimum order.

					
Chablis486	Bean Sprout297	Raw Silk278	Warm Pewter276	Silver170	Granite152
					
Pigeon144	Brownstone203	Peppercorn130	Obsidian114	Dark Rosewood341	Majestic Purple852
					
Autumn Glory381	Cayenne391	Raspberry333	Dress Blues738	Blue Velvet770	Slate Blue753
					
Atlantis693	Tungsten625	Blackened Teal731	Saguaro516	Jungle Green527	Chartreuse484
					
Bold Gold490	Medallion487	Firecracker401	Copperplate424	Spice465	Gold470

Glitch Art Collection

Style	Circuit (Modular)	Cross Talk (Modular)	Hub (Modular)
Construction	Patterned Loop	Patterned Loop	Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	10.66 (41.97 per 10 cm)	9.83 (38.70 per 10 cm)	9.83 (38.70 per 10 cm)
Density	6,667 (247.73 kg/m³)	6,667 (247.73 kg/m³)	6,667 (247.73 kg/m²)
Pile Thickness	0.108" (2.74 mm)	0.108" (2.74 mm)	0.108" (2.74 mm)
Weight	20 oz/yd² (678 g/m²)	20 oz/yd² (678 g/m²)	20 oz/yd² (678 g/m²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular	Infinity® 2 Modular
Width	24" x 24" (60.69 x 60.69 cm)	24" x 24" (60.69 x 60.69 cm)	24" x 24" (60.69 x 60.69 cm)
Colors	12	12	12
Packaging	8 yd² / 18 Tiles	8 yd² / 18 Tiles	8 yd² / 18 Tiles
Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive
Installation Method	Horizontal Brick Ashlar	Horizontal Brick Ashlar	Horizontal Brick Ashlar
Testing			
Dimensional Stability (Aachen Test)	Passes		
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV		
Flooring Radiant Panel (ASTM E648)	Passes - Class 1 ≥ 0.45 watts/cm²		
Smoke Density (ASTM E662)	Passes ≤ 450		
Methenamine Pill Test (ASTM D2859)	Passes		
Hexapod (ASTM D5252) TARR	3.5 - severe		
Environmental Data			
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold		
Recycled Content	Contains recycled content		
Indoor Air Quality	CRI Green Label Plus Certified		
Product Declarations	Third Party Verified EPD, HPD		
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information		
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials		
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information		
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered		
Warranty			
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Glitch Art Collection

Style	Mainboard (Modular)	Circuit (Broadloom)
Construction	Patterned Loop	Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	9.5 (37.40 per 10 cm)	10.66 (41.97 per 10 cm)
Density	6,667 (247.73 kg/m³)	6,667 (247.73 kg/m³)
Pile Thickness	0.108" (2.74 mm)	0.108" (2.74 mm)
Weight	20 oz/yd² (678 g/m²)	20 oz/yd² (678 g/m²)
Backing Type	Infinity® 2 Modular	UltraBac® RE, Integra HP®
Size	24" x 24" (60.69 x 60.69 cm)	12'6" (3.81 m)
Colors	12	12
Pattern Repeat	N/A	18 3/4" W x 19 1/2" L
Packaging	8 yd² / 18 Tiles	N/A
Adhesive	Infinity 2 Adhesive	M-Guard Ultra Adhesive Integra 2 Adhesive
Installation Method	Herringbone, Horizontal Brick Ashlar, Vertical Ashlar	N/A
Testing		
Dimensional Stability (Aachen Test)	Passes	
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1 ≥ 0.45 watts/cm²	
Smoke Density (ASTM E662)	Passes ≤ 450	
Methenamine Pill Test (ASTM D2859)	Passes	
Hexapod (ASTM D5252) TARR	3.5 - severe	
Environmental Data		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold, UltraBac® RE - Gold, Integra® HP - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered	
Warranty		
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.