

Echoing Threads Collection

Style	Sensory Weave	Tactile Foundation
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	14 (55.12 per 10 cm)	12 (47.24 per 10 cm)
Density	5,489 (203.96 kg/m³)	5,162 (191.81 kg/m³)
Pile Thickness	.101" (2.57 mm)	.106" (2.69 mm)
Weight	15 oz/yd² (509 g/m²)	15 oz/yd² (509 g/m²)
Backing Type	Infinity® 2 Modular-rEvolve® II Modular	Infinity® 2 Modular-rEvolve® II Modular
Sizes	12 x 36 (30.48 X 91.44 cm)	12 x 36 (30.48 X 91.44 cm)
Packaging	5.33 yd² / 16 Tiles	5.33 yd² / 16 Tiles
Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive
	XpressStep Spray Adhesive	XpressStep Spray Adhesive
	FreLock Tabs (Infinity 2	FreLock Tabs (Infinity 2
	Modular only)	Modular only)
Installation Method	Vertical Ashlar	Vertical Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Radiant Panel (ASTM E648)	≥ 0.45 watts/cm², Passes (Class 1)	≥ 0.45 watts/cm², Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR Rating	3.5	3.0
Environmental Data		
NSF/ANSI 140 Certification	Infinity 2 Modular - Gold / rEvolve® II Modular -Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients (HPDs); IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information Calhoun, GA (USA) - ISO 14001 Registered	
Warranty		
	Limited Lifetime Wear & Backing Limited 15-Year XGUARD® Stain Resistant Limited 15-Year ColorSafe® Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
 - Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
 - As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
 - Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
 - This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
 - The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
 - Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262