



Top Notch and Top Shelf

Mannington
COMMERCIAL



Cover: **Top Shelf** (Modular) - Choice 13760

Installation: Brick Ashlar


Above: **Top Shelf** (Modular) - Favored 12761, **Top Notch** (Modular) - Unparalleled 14765

Installation: **Top Shelf** - Horizontal Brick Ashlar, **Top Notch** - Horizontal Brick Ashlar




Top Notch (Modular) - Grand 83746
Installation - Three-Step Vertical Ashlar

Crafted to Coordinate



- 1. Self Assembly, Gansey, Cable
- 2. Top Notch, Choice
- 3. Top Shelf, Grand
- 4. Teles®, Ivory Coast
- 5. Amtico Signature®, Stone, Cadence Aeria
- 6. Mannington Select®, Wood, Chandler Oak
- 7. Amtico Signature®, Wood, Union Oak



1. Origami, Mountain Fold, Crane
2. Teles®, Misty Bay
3. The Portland Project® LVT, Burnside, Twinflower
4. Top Shelf, Excel

5. Top Shelf, Unparalleled
6. BioSpec® Choices, BioSpec MD®, Salt
7. Moire, Visible Light, Lumens



BurkeBase® Premium TS Molded Wall Base- 204 Grey; Intrinsic, Confluence - Security 63014; Optimism 81010

Available Profile Heights	BurkeBase® Premium TS Molded 1/8"	BurkeBase® Type TP 1/8"	BurkeBase® Type TV 1/8"	BurkeBase® Type TV .080"
	4" (102 mm)	2.5" (64 mm)	2.5" (64 mm)	2.5" (64 mm)
	6" (152 mm)	4" (102 mm)	4" (102 mm)	4" (102 mm)
		4.5" (114 mm)	4.5" (114 mm)	6" (152 mm)
		6" (152 mm)	6" (152 mm)	
	Coved	Coved or Toeless	Coved or Toeless	Coved or Toeless

Warranty This product is backed by our Limited 5-Year Commercial Warranty.

Corners BurkeBase® Premium Type TS factory molded corners are available with 4" and 6" coved corners. Must be ordered at time of wall base order to ensure color match.

BurkeBase® Type TP/TV pre-formed corners are available in all profile heights. Must be ordered at time of wall base order to ensure color match.

Custom Colors Minimums apply.

Please make final selection for all colors from actual product samples.

For samples and information, visit manningtoncommercial.com or call 800.241.2262.



BurkeBase® - Pecan 504 (ACCORD color), **English Walnut** - Kelen 5684R

Thermoset Rubber

BurkeBase® Premium TS Molded Wall Base Benefits

- Vulcanized thermoset rubber to prevent shrinkage or expansion
- Molded to provide dimensional stability
- Smooth satin finish and inherent flexibility helps hide substrate irregularities
- Available in 4' lengths
- 25 standard colors

Thermoplastic Rubber

BurkeBase® Rubber Wall Base Type TP Benefits

- Heavy gauge rubber base
- Flexible formulation easily forms to curves and corners for clean installation
- Will not fade or crack
- Scuff and scratch resistant
- Available in 4' lengths and 100' seamless rolls
- 100 standard colors


Vinyl

BurkeBase® Vinyl Wall Base Type TV Benefits

- Engineered for heavy traffic and high maintenance areas
- Scuff and abrasion resistant
- Tough matte finish helps hide substrate irregularities
- Available in .080" and .125" gauges
- Available in 4' lengths and 100' seamless rolls
- 100 standard colors

Proven by Third-Party Testing

All of our carpet products are third-party tested and proven to exceed industry standards in appearance retention, texture retention, fire safety factors and static generation, and our modular carpet exceeds industry standards in dimensional stability – so you can be sure that the carpet you specify will perform for years to come.



Easier to Maintain

- > The molecular strength of type 6,6 nylon delivers greater resilience against matting and resists abrasive wear, keeping carpet looking better longer.
- > XGUARD® Stain Resistant Technology provides long-term stain resistance for our space dye products.
- > ColorSafe® Bleach Resistant Technology resists color fade-out from bleach spills for our space dye products.
- > Moisture-barrier backings are built to withstand aggressive wet cleanings.

Backing Advantages

- > Infinity® 2 Modular backing provides exceptional performance with a moisture barrier and allows for installations in areas with up to 99% RH.
- > Infinity® 2 Modular backing offers superior tuft bind and dimensional stability with a limited lifetime warranty.

Sustainable Solutions

- > Supported with EPDs and HPDs.
- > Infinity® 2 Modular backing is CRI Green Label Plus Certified and NSF/ANSI 140 Gold Certified.
- > Infinity® 2 Modular backing contains recycled content.

TARR

- > Top Notch and Top Shelf carpets were specifically designed with a 3.0 TARR rating for use in heavy commercial traffic areas such as conference rooms, open offices, entryways and areas where large numbers of people congregate. The TARR rating on our carpets is tested and verified by an independent lab.



Design Solutions


Whether you're looking for design support from the start of a project or in the final phase, Mannington's Design Solutions team can help. Our team of designers is here to support you, our customers, through every step of the design process, from concept to installation.

Your Vision Realized

Our team of designers with diverse backgrounds in interior design, graphic design and textile design will work with you to provide solutions, knowledge and options to simplify the design process and bring your vision to life.

Deliverables

- > Product Palettes
- > 2D and 3D Renderings
- > Composites
- > Configurations
- > Finished Plans
- > Rendered Floor Plan
- > Estimates
- > Installation Diagrams
- > Revit Files
- > Construction Documents



No Moisture Testing Required*

Solutions crafted for high-moisture conditions. Defeat moisture issues with carpet backings that do not require moisture testing*.

We have solutions for broadloom and modular carpet to make moisture worries evaporate. From backing options to adhesives to a dry installation system, explore solutions that defeat moisture concerns while enhancing the performance of your floor.

	Infinity 2 Pressure Sensitive Adhesive	XpressStep™ Spray Adhesive	FreLock Tabs	Integra-2 Adhesive	Ultra Adhesive
Infinity® 2 Modular Backing	✓	✓	✓		
Infinity® 2 MG Modular Backing	✓	✓	✓		
Infinity® 2 MG Cushion Modular Backing	✓	✓			
Integra® HP Broadloom Backing				✓	
UltraBac® RE Broadloom Backing					✓

* Assumes intact vapor barrier, no standing water or stained concrete, no hydrostatic pressure, and for our broadloom backings (Integra® HP and UltraBac® RE) pH levels must never exceed 10. Please refer to our installation instructions for further details.

Top Notch and Top Shelf

Style	Top Notch (Modular)	Top Shelf (Modular)
Construction	Tip-Sheared Patterned Loop	Tip-Sheared Patterned Loop Type
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution
Guage	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	12 (47.24 per 10 cm)	11.6 (45.67 per 10 cm)
Density	5,454 (202.66 kg/m³)	5,373 (199.65 kg/m³)
Pile Thickness	0.132" (3.35 mm)	0.134" (3.40 mm)
Weight	20 oz/yd² (678 g/m²)	20 oz/yd² (678 g/m²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular
Sizes	12" x 36" (30.48 x 91.44 cm) 24" x 24" (60.96 x 60.96 cm)	12" x 36" (30.48 x 91.44 cm) 24" x 24" (60.96 x 60.96 cm)
Colors	7	7
Packaging	12" x 36" - 5.33 yd² / 16 Tiles 24" x 24" - 8 yd² / 18 Tiles	12" x 36" - 5.33 yd² / 16 Tiles 24" x 24" - 8 yd² / 18 Tiles
Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive
Installation Method	Horizontal Brick Ashlar, Monolithic, Quarter-turn (24" x 24" only)	Horizontal Brick Ashlar, Monolithic, Quarter-turn (24" x 24" only)
Testing		
Dimensional Stability (Aachen Test)	Passes	
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Methenamine Pill Test (ASTM D2859)	Passes	
Hexapod (ASTM D5252) TARR	3.0 - heavy	
Environmental Data		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered	
Warranty		
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.