

**Color Anchor LVT Collection**

Style	Groove, Stride
Construction	Luxury Vinyl Tile Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B
Total Thickness	0.098" (2.5 mm)
Wear Layer Thickness	20 mil (0.51 mm)
Wear Layer	Quantum Guard Elite®
Edge Treatment	Micro-beveled or Unbevel
Sizes	6" x 36" (152 x 915 mm) 12" x 24" (305 x 610 mm) 18" x 18" (457 x 457 mm)
Colors	29 colors per style
Packaging	6" x 36" - 30 pcs, 45 ft <sup>2</sup> (4.181 m <sup>2</sup> ), 33.53 lbs (15.21 kg) 12" x 24" - 18 pcs, 36 ft <sup>2</sup> (3.345 m <sup>2</sup> ), 26.82 lbs (12.17 kg) 18" x 18" - 12 pcs, 27 ft <sup>2</sup> (2.508 m <sup>2</sup> ), 20.12 lbs (9.126 kg) Packaging may differ for QuickStix®
Adhesive	Porous & Non-porous Substrates: V-88 Full Spread MoistureLoc Full Spread, One Component V95 Full Spread, 2-part Epoxy XpressStep for LVT & Sheet Vinyl Full Coverage Spray <small>Note: Must use V-95, MoistureLoc, QuickStix or XpressStep adhesive under stationary heavy point loads. In more abusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only V-95, MoistureLoc or QuickStix should be used.</small>
QuickStix®	Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas.
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.
<b>Testing</b>	
HUD/FHA	Passes
Flexibility (ASTM F137)	Passes - 1" Mandrel - No Crack/Break
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/in ft
Squareness (ASTM F540)	Passes - Max 0.010"
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent ≤ 0.005"
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Resistance to Light (ASTM F1515)	Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes
<b>Environmental Data</b>	
Rapidly Renewable Content	Contains 2% rapidly renewable resource content
Indoor Air Quality	FloorScore Certified; CDPH v1.22017
Product Declarations	Third Party Verified EPD, HPD
Carbon Offset	105% (Cradle to Gate (A1-A3); visit website for more information)
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information
Manufacturing	Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered, +Vantage Vinyl™ Verified Silver
<b>Warranty</b>	
	Limited 15-Year Commercial Warranty Limited 15-Year Quantum Guard Elite® Wear Warranty

Due to the unique nature of this pattern and tonal variations, shading may appear when mixing tiles during installation and in certain lighting conditions. This characteristic is not a defect, but rather adds depth and dimension to the final look and contributes to the overall aesthetic. We always recommend reviewing the tile arrangement to achieve your desired aesthetic.