



Craft Your Oasis

Step into the serene world of the White Sands Collection. Inspired by the sacred geometry and breathtaking landscapes of White Sands National Monument, this LVT collection brings a sense of tranquil calm and rejuvenation to any space. By exploring the delicate balance between symmetry and asymmetry found in nature, the intersecting paths in White Sands mirror our connection with the celestial realm, creating a soothing atmosphere suitable for schools, offices, healthcare facilities, and retail spaces.



















White Sands

At Mannington Commercial, we proudly manufacture the vast majority of our LVT right here in North America, including White Sands. By controlling the process from start to finish, from design to material sourcing to delivery, we are able to bring you hard surface flooring products that are optimized to fit your needs.

Crafted by the Industry Leader in LVT

2.5 mm Thickness

Natural Beauty, Outstanding Performance

 Abstract visuals coordinate beautifully with Mannington Commercial's other collections

Quantum Guard Elite®

- Best in class abrasion resistance
- Easy maintenance
- Stain resistance that endures

15-Year Quantum Guard Elite® warranty

105% Carbon Offset

 Recognizing the impact that the built environment can have on Earth's climate and health, Mannington Commercial is improving operations and offsetting cradle to gate embodied carbon by 105% on our domestically manufactured flooring products as part of our commitment to helping customers take positive action through their projects.









Success Is in Our Science

Quantum Guard Elite is a proven, patented technology that provides the ultimate solution for all aspects of LVT performance.

- Highest scratch resistance in the industry
- Engineered for best-in-class dimensional stability
- Superior impact resistance
- Cuts cleanly for highest quality installation
- Easy no-polish maintenance significantly reduces overall life cycle cost and total cost of ownership
- Advanced stain resistance

Outperforms in Scratch Resistance

Quantum Guard Elite

Leading Competitor






With a patented two-part wear layer and aluminum oxide infused top coat, Quantum Guard Elite offers superior scratch resistance vs. the leading competitor.

Complete Multi-Layered Protection


Quantum Guard Elite combines a hard wear layer and a flexible wear layer for superior durability with the added protection of our proprietary aluminum oxide technology.



Best-in-Class Dimensional Stability

Quantum Guard Elite

Leading Competitor





LVT with Quantum Guard Elite is fully engineered to offer the perfect balance of hardness and flexibility, which helps prevent product failures in commercial environments. (Products exposed to 80°C for six hours.)

Warranted to Work

Products with Quantum Guard Elite feature our Limited Quantum Guard Elite Wear Warranty and Limited Commercial Warranty.



Edge Effects Wall Base Collection

An architectural accent, creating the elegant effect of a milled wood base without the expensive installation, indentations, scuffs, and abrasions. Requires no nailing, priming, or painting. Co-extruded thermoplastic rubber (type tp) engineered for flexible application to walls, corners, and columns.

40 Colors

17 Styles

In a smooth, matte finish for a flawless look in any room.

7 Profile Heights

Style-dependent, in four thicknesses.

Sustainability

- > FloorScore
- > mindful MATERIALS
- > HPD

Warranty

> Limited 5-Year Commercial



Cetera EECET



Etched EEETC



Illusion EEILL





View Edge Effects Online

Defeat Damp Spaces

Your job just got easier. With our comprehensive moisture solutions for LVT, you can defeat the most extreme high moisture conditions.

Best Solutions for:

Any Slab Condition

NO Moisture Testing Required - NO RH limit, NO Testing*

Adhesive

MoistureLoc

* Conditions

No hydrostatic pressure | No standing water or visible water stains | Slab is at least 45 days old

Best Solutions for:

Slabs with Intact Vapor Barier (Class B or better)

Quick pH Testing Required**

Adhesive	рН
V-88	12
MoistureLoc	None
QuickStix® with Moisture Resistant Primer**	12

** Conditions

Intact Class B or better vapor barrier | No hydrostatic pressure | No standing water or visible water stains | Slab is at least 45 days old

Best Solutions for:

Unknown Slab Conditions

Moisture Testing Required

Adhesive	RH%	MVER	рН
V-88	95	10	12
MoistureLoc	None	None	None
XpressStep LVT & Sheet	98	10	12
QuickStix® with Premium Universal Primer (with IVB)	99	18	12
QuickStix® with Premium Universal Primer (No IVB)	95	10	12
V-95	85	5	9

White Sands Product Availability

Product Name	Product Code	Style	Color / Pattern Variability	Surface Finish - Ceramic	Quantum Guard Elite®	Micro-beveled Edges	12" x 24" (305 x 610 mm)	7.25" × 48" (184 × 1219 mm)
ABSTRACT								
Glyph Oasis	WS100	Abstract	Low	•	•	•	•	•
Glyph Haven	WS200	Abstract	Low	•	•	•	•	•
Glyph Sanctuary	WS210	Abstract	Low	•	•	•	•	•
Crystalline Rosemary	WS110	Abstract	Low	•	•	•	•	•
Crystalline Selenite	WS111	Abstract	Low	•	•	•	•	•
Crystalline Mint	WS112	Abstract	Low	•	•	•	•	•
Crystalline Lake	WS210	Abstract	Low	•	•	•	•	•
Crystalline Gypsum	WS211	Abstract	Low	•	•	•	•	•
Crystalline Sumac	WS212	Abstract	Low	•	•	•	•	•
Crystalline Rainstorm	WS310	Abstract	Low	•	•	•	•	
Crystalline Prairie	WS311	Abstract	Low	•	•	•	•	•
Crystalline Raven	WS312	Abstract	Low	•	•	•	•	
Zephyr Rosemary	WS120	Abstract	Low	•	•	•	•	•
Zephyr Mint	WS121	Abstract	Low	•	•	•	•	•
Zephyr Lake	WS220	Abstract	Low	•	•	•	•	•
Zephyr Sumac	WS221	Abstract	Low	•	•	•	•	
Zephyr Rainstorm	WS320	Abstract	Low	•	•	•	•	•
Zephyr Raven	WS321	Abstract	Low	•	•	•	•	•

Color/Pattern Variability

Color and visual variation are inherent in all resilient products. Variability can fluctuate from slight or significant, and from tile to tile. Our pattern variability ratings range from low (little variation) to high (significant variation).







Medium Moderate variation



High Substantial variation



White Sands Collection

Style	Crystalline, Glyph, Zephyr
Construction	Luxury Vinyl Tile
	Non-ortho Pthalate
Classification	ASTM F1700 Class III, Type B
Total Thickness	.098" (2.5 mm)
Wear Layer Thickness	20 mil (0.51 mm)
Wear Layer	Quantum Guard Elite®
Edge Treatment	Micro-beveled or Unbeveled
Sizes	7.25" x 48" (184 x 1219 mm)
	12" x 24" (305 x 610 mm)
Colors	18
Environmental Data	
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017
Product Declarations	Third party verified EPD, HPD
Carbon Offset	105% Cradle to Gate (A1-A3), see website for additional information
LEED	May contribute to LEED credits:
	Building Product Disclosure & Optimization - EPDs
	Building Product Disclosure & Optimization - Sourcing Raw Materials
	Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information
Manufacturing	Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered, +Vantage Vinyl Verified Silver
Warranty	
	Limited 15-Year Commercial Warranty



Limited 15-Year Quantum Guard Elite® Wear Warranty



View full collection specs.