

## Attune

Style	Attune
Construction	7mm Heterogeneous Sheet (Non-ortho phthalate construction)
Classification	ASTM F1303 Type I, Grade 1, Class B
Total Thickness	0.275" (7.0 mm)
Wear Layer Thickness	20mil (0.51 mm)
Wear Layer	Quantum Guard Elite®
Width	5' 10" (1.78 m)
Colors	28
Pattern Repeat	Style Dependent 36" L x 72" W - Boardwalk, English Walnut, Maple Creek, Persian Walnut, Ironside Oak, Suber, Wellspring 48" L x 48" W - Maple Grove, Southern Oak 48" L x 72" W - Antique Oak
Packaging	Roll Size 5'10" x 30 LF (Approximately 175 SF/roll) - 6 rolls per pallet
Weight	1.5lbs/SF (2.04kg/m2)
Adhesive	<b>Porous &amp; Non-porous Substrates:</b> MR-710 Full Spread, Single Component Urethane
QuickStix®	Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas.
Seam Method	Heat Weld Only - Mannington Commercial Weld Rods
Testing	
HUD/FHA	Meets / Exceeds
ADAG (American Disability Act Guidelines)	Passes
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes - 500 PSI; Residual Indent ≤ 0.005"
Dynamic Rolling Load (ASTM F2753)	Pass
G-Max ( Clegg)	343 Avg.
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm²
Pill Test (ASTM 2859)	Passes
Slip Resistance (ASTM D2047)	Passes - .50
Acoustic (ASTM 3133)	L wa 72 dB
Acoustic IIC (ASTM E492)	66 - 6" Concrete with Drop Ceiling 55 - 6" Concrete
Acoustic STC (ASTM E90)	61 - 6" Concrete with Drop Ceiling 52 - 6" Concrete
Acoustic Δ IIC (E2179)	23 - 6" Concrete
Resistance to Light (ASTM F1515)	Passes - < 8 Delta E Color Change
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Environmental Data	
Recycled Content	60% post-consumer recycled content by total product weight
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017
Product Declarations	EPD, HPD
Carbon Offset	105% Cradle to Gate (A1-A3), visit website for more information
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information
Manufacturing	Salem, NJ (USA)- ISO 14001 EMS & ISO 9001 QMS Registered, +Vantage Vinyl Verified Silver
Warranty	
	Limited 15-Year Commercial Warranty Limited 15 Year Quantum Guard Elite Wear Warranty

**Note:** Visual/Color variations can occur from roll to roll. This variation does not affect product performance.