


Risers are available in coordinating colors.

Square Profile | Square Nose & Visually Impaired*



A = 13" B = 1.813" C = .18" D = .13" E = 2"

F = 80° G = 7"



Sculptured Profile | Square Nose & Visually Impaired*

A = 13"	* Refer to architect fold-	A = 13"
B = 1.813"	er for actual texture	B = 1.813'
C = .18"	and color	C = .18"
D = .13''		D = .13"
F = 80°		E = 2"
G = 7"		F = 80°
H = .125''		G = 7"
		H = .125"

* Refer to architect folder for actual texture and color

Technical Data

PRODUCT	LENGTHS	VI STRIPS	PROFILE
1/8" Square Profile	3', 4', 5', 6'	Optional	Square
1/8" Sculptured Profile	3', 4', 5', 6'	Optional	Sculptured
1/8" Risers (7" height w/toe)	3', 4', 5', 6'	n/a	none
1/8" Risers (6" Cove)	4'	n/a	none
1/8" Skirting (10" toeless base)	4'	n/a	none

Applicable Standards: Treads: ASTM F2169, Type TS, Class 2, Group 1 & 2 Risers & Skirting: ASTM F1861, Type TS, Group 1, Style A & B Indentation Resistance: ASTM F970 - .000" residual indent at 600 PSI Flame Resistance: ASTM E648, Class 1

Nose filler NOT REQUIRED. The superior construction of our ColorSpec Type TS Rubber stair treads do not require nose filler at installation.



ColorScape® Stair Treads & Risers

Round Profile | Square Nose & Visually Impaired*



Square Profile | Square Nose & Visually Impaired*

A = 13"		A = 13"
B = 1.813"		B = 1.813"
C = .18"		C = .18"
D = .13"		D = .13"
F = 80°		E = 2"
	•	F = 80°

Sculptured Profile | Square Nose & Visually Impaired*

A = 13" B = 1.813" C = .18" D = .13" F = 80°	* Refer to architect fold- er for actual texture and color	A = 13" B = 1.813" C = .18" D = .13" E = 2"	* Refer to architect fold- er for actual texture and color
		F = 80°	

Technical Data

PRODUCT	LENGTHS	VI STRIPS	PROFILE
1/8" Round Profile	3', 4', 5', 6'	Optional	Round
1/8" Square Profile	3', 4', 5', 6'	Optional	Square
1/8" Sculptured Profile	3', 4', 5', 6'	Optional	Sculptured
1/8" Risers (7" height w/toe)	3', 4', 5', 6'	n/a	None
1/8" Risers (6" Cove)	4′	n/a	None
1/8" Skirting (10" toeless base)	4′	n/a	None

Applicable Standards: Treads: ASTM F2169, Type TS, Class 2, Group 1 & 2 Risers & Skirting: ASTM F1861, Type TS, Group 1, Style A & B Indentation Resistance: ASTM F970 - .000" residual indent at modified 600 PSI Flame Resistance: ASTM E648, Class 1

Nose filler NOT REQUIRED. The superior construction of our ColorScape Type TS Rubber stair treads do not require nose filler at installation.






ConnectStep® Single Piece Stair Tread and Riser Combination: Square Nose and Visually Impaired

ConnectStep speeds installation, reduces maintenance and provides a uniform, seamless and contoured look. ConnectStep automatically adjusts for step depths of between 9.5 inches and 13 inches. This also allows for adjustments to varying

riser heights. Available in ColorSpec's Sculptured Profile and ColorScape's Round or Sculptured Profiles with optional VI strip inserts.





Superior Rubber Formulation

- Superior indention resistance, color retention and slip-resistance
- Superior scratch-resistance due to low clay and high pigment content
- Quieter underfoot

Built-in, Long Lasting Migrating Wax

- No wax required, low maintenance option
- Self-waxing feature for superior appearance retention
- Lower life cycle costs


Superior Profile Design

- Profile design allows for enhanced cleanability
- Available with or without visually impaired strip




Flexible Nose For Easy Compliance

All Linear Series Stair Treads have a notch behind the nose for increased flexibility. The ADA requires nosing angles to be between 60° and 90° from the horizontal. This product modification will allow the nosing position of these products to more easily conform to the steps' nosings that have been built to the severest angle allowed by the ADA (60°).



ADA



Commercial 250 - Heavy Traffic | Vinyl & Rubber




Commercial 150 - Light Traffic | Vinyl Only

A = 12"	Full Depth	_
B = 1.5"	Corrugation	
C = .15''		
D = .125"		

Commercial 210 - Normal Traffic | Vinyl Only

A = 12"	Pyramidal Gripper
B = 1.5''	Square Nose Only
C = .21''	
D = .125"	





Risers are available in coordinating colors.



Technical Data

PRODUCT 1/8" Risers (7" height w/toe)

1/8" Risers (6" Cove)

LENGTHS 3', 4', 5', 6' 4′

VI STRIPS n/a n/a

PROFILE Smooth Smooth

Stair Nosings

510 Top-Set Nosing (Square Nose)

Covers leading edge of step. May be used over vinyl and sheet goods.

Packing: 20-12' secs., 240 lin. ft. per carton



565 Double Undercut Carpet Stair Nosing

For 1/4" and 5/16" carpet. Accommodates step and riser; with ribbed surface.

Packing: 10-12' secs., 120 lin. ft. per carton



570 Superior Carpet Stair Nosing

Friction-Grip nosing for use when only step is covered. Undercut for 1/4" and 5/16" carpet.

Packing: 10-12' secs., 120 lin. ft. per carton





575 Overlap Stair Nosing


Nosing with deep grooves and overlap lip. Accepts material to 1/8" with lip, to 3/16" without lip.

Packing: 10-12' secs., 120 lin. ft. per carton



Square step nosing for 1/8" material. Ribbed surface.

Packing: 10-12' secs., 120 lin. ft. per carton



585 Top-Set Nosing for 1/4", 1/8" or .080" Material

Ribbed surface nosing can be cut along pre-grooved channels to adjoin 1/4", 1/8" or .080" resilient flooring materials.

Packing: 10-12' secs., 120 lin. ft. per carton



Visually Impaired Safety Treads meet California Disabled Access Regulation, Title 24, Section 3306 for the visually impaired when used with contrasting strip color. Available in any of the 36 Accord System colors and the 10 Abrasive Strip Insert colors below. Tape may be ordered separately for onsite installations.




Visually Impaired Safety Nosings

558 Visual Abrasive Safety Nosing for 1/4" Material

Contrasting insert for Visually Impaired. Accepts 1/4" with lip. Available in any interchangeable combination of colors. Pick a color for the nosing and the strip from 10 available colors and abrasive strip inserts.


Packing: 6-12' secs, 72 lin ft per carton



578 Visual Abrasive Safety Nosing for 1/8" Material

Visual Abrasive Safety Nosing for 1/8' Material. Pick a color for the nosing from the 36 Accord colors and a color from the 10 abrasive tape colors.

Packing: 10-12' secs., 120 lin. ft. per carton



Durability Meets Design

Our superior recipe with proper curing allows our rubber products to look better and be easier to maintain long-term.

- > Carefully engineered profiles provide better acoustics and greater comfort underfoot
- Never needs to be waxed, thanks to a proprietary combination of inherent waxes
- Superior thermoset rubber retains color, resists indentation and crackling, and is quiet underfoot
- Superior scratch-resistance due to low clay and high pigment content
- > No finish or stripping, lowers maintance costs
- > Low emission: FloorScore Certified
- > Excellent wear resistance
- > Slip resistant
- > Quiet under wheeled traffic
- > Profile design allows for enhanced cleanability



American Made

At Mannington Commercial, we are very proud to craft all of our resilient sheet, rubber, carpet and more than 90% of our LVT right here in the USA. It means supporting local economies and employing generations of American families. And it means providing you with the industry's most innovative flooring solutions.

Learn more at manningtoncommercial.com

