

Sleep chair 1759-S

Overall Dimensions	32"w x 35"d x 33.5"h	Weight	150 lbs.
Seat Dimensions	25.5"w x 22"d x 18"h	Cubic Feet	29
Seat to Top of Back	20"	COM	8.25 yds.
Top of Arm to Floor	25"		
Extended Length	85.5"		
Sleep Surface Length	82		



Standard Features	Options Available
<ul style="list-style-type: none"> • Multi-position steel frame mechanism • Upholstered arms, seat and back • Tight cushion • Non-marring adjustable glides 	<ul style="list-style-type: none"> • Wood arm caps • Black poly arm caps • Casters

Standard Textile & Finish Selection

<http://carolina.ofs.com/design/textiles>
<http://carolina.ofs.com/design/finishes>

Frame Construction

Seat	<ul style="list-style-type: none"> • Frame constructed of 5/4 WHND kiln dried maple
Back	<ul style="list-style-type: none"> • Frame constructed of 5/4 WHND kiln dried maple
Arms	<ul style="list-style-type: none"> • Top/bottom rail and front back post 5/4 WHND kiln dried maple • Front post and top filler 8/4 WHND kiln dried maple • Front/back top post 5/4 WHND kiln dried maple • Top block 5/4 WHND kiln dried maple • Bottom roll rail 5/4 WHND kiln dried maple
Assembly	<ul style="list-style-type: none"> • Joints are assembled using glue, dowels, screws, and corner blocks • The seat, back, arms and mechanism are assembled using 1/4" - 20 bolts and T-nuts No. 9 and No. 12 wood screws

Foam

Seat	<ul style="list-style-type: none"> • 4 1/2" premium grade fire retardant foam • 35 lb. compression • 1.8 density • Covered in 1.25 oz. of polyester fiber then cemented to the frame
Back	<ul style="list-style-type: none"> • 2 1/2" premium grade fire retardant foam • 30 lb. compression • 1.8 density • Covered in .75 oz of polyester fiber then cemented to the frame • All foam is contour cut to fit the design