

Three-position recliner closed arms 1677

Overall Dimensions	26.5"w x 33.25"d x 44"h	Weight	87 lbs.
Seat Dimensions	21"w x 20"d x 19"h	Cubic Feet	36
Seat to Top of Back	25"	COM	6 yds.
Top of Arm to Floor	25.25"		
Extended Length	68.5"		



Standard Features	Options Available
- Upholstered seat, back, and arms - Upholstered arms with no arm caps are standard - European beech wood legs - Non-marring adjustable glides - Durable steel three-position recliner mechanism - Foot ottoman is extended by pressing on the recliner's arms - Tight cushion - Wall-saver design	- Wood, poly, or solid surface arm caps - Left-side facing drop table is available in 3DL - Drop table features a cup holder - Drainage bag hook (field installed) - Back bump guard

Three-position recliner open arms 1677-OA

Overall Dimensions	26.5"w x 33.25"d x 44"h	Weight	87 lbs.
Seat Dimensions	21"w x 20"d x 19"h	Cubic Feet	36
Seat to Top of Back	25"	COM	4.25 yds.
Top of Arm to Floor	25.25"		
Extended Length	68.5"		



Standard Features	Options Available
- Upholstered seat and back - Open arm frame with wood arm cap is standard - European beech wood frame - Non-marring adjustable glides - Durable steel three-position recliner mechanism - Foot ottoman is extended by pressing on the recliner's arms - Tight cushion - Wall-saver design	- Wood, poly, or solid surface arm caps - Drainage bag hook (field installed) - Back bump guard

Three-position recliner closed arms with casters 1677C

Overall Dimensions	26.5"w x 33.25"d x 44"h	Weight	87 lbs.
Seat Dimensions	21"w x 20"d x 19"h	Cubic Feet	36
Seat to Top of Back	25"	COM	6 yds.
Top of Arm to Floor	25.25"		
Extended Length	68.5"		



Standard Features	Options Available
- Upholstered seat, back, and arms - Upholstered arms with no arm caps are standard - European beech wood frame 5" Individual locking back casters are standard in black - Durable steel three-position recliner mechanism - Foot ottoman is extended by pressing on the recliner's arms - Tight cushion - Wall-saver design	- Wood, poly, or solid surface arm caps - Drainage bag hook (field installed) - Back bump guard

Standard Textile & Finish Selection

<http://carolina.ofs.com/design-resources/textiles>
<http://carolina.ofs.com/design-resources/finishes>

Frame Construction

- | | |
|------------|---|
| Seat | <ul style="list-style-type: none"> • All components are made of WHAD kiln dried maple |
| Back | <ul style="list-style-type: none"> • Frame back post 7/8 plywood • Pull rail 8/4 WHND kiln dried maple • All other back frame components 5/4 WHND kiln dried maple |
| Upholstery | <ul style="list-style-type: none"> • 4.25 yds. required based on 54" wide, plain goods • Covers are upholstered to the frame using 1/2" stainless steel staples |
| Arms | <ul style="list-style-type: none"> • Front post 6/4 WHAD kiln dried maple • Bottom, center and top rail 5/4 WHAD • Bottom filler 60 x 60 x 38 Baltic Birch • Joints are assembled using dowels, glue and corner blocks • The seat, back, arms and mechanism are assembled using 1/4 - 20 bolts and T-nuts No. 9 and No. 12 wood screws |

Foam

- | | |
|------|--|
| Seat | <ul style="list-style-type: none"> • 4.5" premium grade fire retardant foam • 30 lb. compression • 1.8 density • Covered in .75 oz. of polyester fiber then cemented to the frame |
| Back | <ul style="list-style-type: none"> • 2.5" premium grade fire retardant foam • 30 lb. compression • 1.8 density • Covered in .75 oz. of polyester fiber then cemented to the frame • All foam is contour cut to fit the design |