

Guest chair 1472

Single textiles

Overall Dimensions	25"w x 26.5"d x 33"h	COM 54"	1.25 yds.
Seat Dimensions	21.5"w x 20"d x 17.75"h	Weight	60 lbs.
Seat to Top of Back	15.25"	Cubic Feet	24
Top of Arm to Floor	25.5"		
Exposed Metal	Luster Grey		



Guest chair 1472-MT

Multiple textiles

Overall Dimensions	25"w x 26.5"d x 33"h	COM 54" - Seat	1 yd
Seat Dimensions	21.5"w x 20"d x 17.75"h	COM 54" - Back	1 yds.
Seat to Top of Back	15.25"	Weight	70 lbs.
Top of Arm to Floor	25.5"	Cubic Feet	33
Exposed Metal	Luster Grey		



Guest loveseat 1472-L

Single textiles

Overall Dimensions	45.5"w x 26.5"d x 33"h	COM 54"	2.75 yds.
Seat Dimensions	42.25"w x 20"d x 17.75"h	Weight	70 lbs.
Seat to Top of Back	15.25"	Cubic Feet	33
Top of Arm to Floor	25.5"		
Exposed Metal	Luster Grey		



Guest loveseat 1472-L-MT

Multiple textiles

Overall Dimensions	45.5"w x 26.5"d x 33"h	COM 54" - Seat	1.5 yd
Seat Dimensions	42.25"w x 20"d x 17.75"h	COM 54" - Back	1.5 yds.
Seat to Top of Back	15.25"	Weight	70 lbs.
Top of Arm to Floor	25.5"	Cubic Feet	33
Exposed Metal	Luster Grey		



Standard Features	Options Available
<ul style="list-style-type: none"> Upholstered seat and back Wall-saver design Clean-thru design Tight cushion Luster Grey powder coat on all exposed metal Black poly arm caps Non-marring adjustable glides 	<ul style="list-style-type: none"> Poly arm caps (black, taupe, and grey) Wood arm caps Solid surface arm caps Removable covers

Standard Textile & Finish Selection

<http://carolina.ofs.com/resources/textiles>
<http://carolina.ofs.com/resources/finishes>

Frame Construction

- | | |
|-------------|---|
| Seat | • Plywood seat EZ frame construction |
| Back | • Contoured plywood shape 11-ply |
| Metal Frame | • 16 gauge |
| Assembly | • All welded joints are full penetration mig/tig welds
• All bolted connections are 1/4" 20 grade 5 hardware |

Foam

- | | |
|-----------|--|
| Seat/Back | • 3 lbs, ILD 35 (3-35)
• Premium Grade Foam
• CAL TB 17 Certified Fire Retardant |
|-----------|--|

Suspension

- | | |
|------|--|
| Seat | • LEXUS webbing
• Polypropylene/latex/rubber |
| Back | • 2430 Propex
• 100% Polypropylene
• Latex coating is Paranol Acrylic 763
• Applied with 5/16 stainless steel staples |