




**Lounge chair 472-1**  
Single textiles

<b>Overall Dimensions</b>	27"w x 25.5"d x 31"h	<b>COM 54"</b>	2 yds.	
<b>Seat Dimensions</b>	23"w x 20"d x 18"h	<b>Weight</b>	48.5 lbs.	
<b>Seat to Top of Back</b>	13"	<b>Cubic Feet</b>	12.5	
<b>Top of Arm to Floor</b>	25"			


**Lounge chair 472-1-MT**  
Multiple textiles

<b>Overall Dimensions</b>	27"w x 25.5"d x 31"h	<b>COM 54" - Seat</b>	1.5 yds.	
<b>Seat Dimensions</b>	23"w x 20"d x 18"h	<b>COM 54" - Back</b>	1.75 yds.	
<b>Seat to Top of Back</b>	13"	<b>Weight</b>	48.5 lbs.	
<b>Top of Arm to Floor</b>	25"	<b>Cubic Feet</b>	12.5	


**Loveseat 472-2**  
Single textiles

<b>Overall Dimensions</b>	49"w x 25.5"d x 31"h	<b>COM 54"</b>	3.75 yds.	
<b>Seat Dimensions</b>	46"w x 20"d x 18"h	<b>Weight</b>	81 lbs.	
<b>Seat to Top of Back</b>	13"	<b>Cubic Feet</b>	23	
<b>Top of Arm to Floor</b>	25"			


**Loveseat 472-2-MT**  
Multiple textiles

<b>Overall Dimensions</b>	49"w x 25.5"d x 31"h	<b>COM 54" - Seat</b>	2 yds.	
<b>Seat Dimensions</b>	46"w x 20"d x 18"h	<b>COM 54" - Back</b>	2.75 yds.	
<b>Seat to Top of Back</b>	13"	<b>Weight</b>	81 lbs.	
<b>Top of Arm to Floor</b>	25"	<b>Cubic Feet</b>	23	

**Sofa 472-3**  
Single textiles

<b>Overall Dimensions</b>	73"w x 25.5"d x 31"h	<b>COM 54"</b>	5.5 yds.	
<b>Seat Dimensions</b>	69"w x 20"d x 18"h	<b>Weight</b>	113 lbs.	
<b>Seat to Top of Back</b>	13"	<b>Cubic Feet</b>	34	
<b>Top of Arm to Floor</b>	25"			

**Sofa 472-3-MT**  
Multiple textiles

<b>Overall Dimensions</b>	73"w x 25.5"d x 31"h	<b>COM 54" - Seat</b>	3.25 yds.	
<b>Seat Dimensions</b>	69"w x 20"d x 18"h	<b>COM 54" - Back</b>	3 yds.	
<b>Seat to Top of Back</b>	13"	<b>Weight</b>	113 lbs.	
<b>Top of Arm to Floor</b>	25"	<b>Cubic Feet</b>	34	

Standard Features	Options Available
<ul style="list-style-type: none"> <li>• Upholstered seat, back, and arms</li> <li>• Tight cushion</li> <li>• Wall-saver design</li> <li>• Luster Grey powder coat on all exposed metal</li> <li>• Black poly arm caps</li> <li>• Non-marring adjustable glides</li> </ul>	<ul style="list-style-type: none"> <li>• Poly or solid surface arm caps</li> </ul>

**Standard Textile & Finish Selection**

---

<http://carolina.ofs.com/resources/textiles>  
<http://carolina.ofs.com/resources/finishes>

**Frame Construction**

---

- Seat • 4.5" thick plywood seat box assembly with webbed cutout in top face panel
- Back • 7/8" thick plywood assembly, webbed with 1" thick face foam
- Metal Frame • 1" x 1" 16 gauge C1018 steel posts  
• 1 1/2" w x .188" thick 7 gauge C1018 mid rails  
• 1 1/2"w x .750" thick 11 gauge C1018 cross rails
- Assembly • All welded joints are full penetration mig/tig welds  
• All bolted connections are 1/4"-20 grade 5 hardware  
• Adjustable Glides: 1/4"-20

**Foam**

---

- Seat/Back • All foam is premium grade CAL 117 certified fire retardant

**Suspension**

---

- Back • Lexus webbing (Polypropylene/latex/rubber) covering the cutout and openings in the seat and back assemblies  
• 2430 Propex applied to the back face and the back assembly  
• All applied with 5/16 stainless steel staples