



**48" Bench 689-48**

<b>Overall Dimensions</b>	48"w x 24"d x 20"h	<b>COM 54"</b>	3 yds.	
		<b>Weight</b>	40 lbs.	
		<b>Cubic Feet</b>	24	

**72" Bench 689-72**

<b>Overall Dimensions</b>	72"w x 24"d x 20"h	<b>COM 54"</b>	4.25 yds.	
		<b>Weight</b>	60 lbs.	
		<b>Cubic Feet</b>	31	

Standard Features	Options Available
<ul style="list-style-type: none"> <li>Fully upholstered</li> <li>Spring seat construction</li> <li>Clean-thru design</li> <li>Classic brushed aluminum leg</li> <li>Non-marring adjustable glides</li> </ul>	<ul style="list-style-type: none"> <li>Hairpin leg (brushed aluminum or powder-coated)</li> </ul>
	<b>Tablet:</b> <ul style="list-style-type: none"> <li>3/16" Metal top overlaid with specified veneer</li> <li>Powder-coated tablet post</li> <li>Post is 3/4" diameter with two 1/2" post offset</li> <li>Left and/or right-side facing</li> </ul>
	<b>Power:</b> <ul style="list-style-type: none"> <li>Left and/or right-facing power is available in black, white, or silver</li> <li>One 15 AMP outlet, one USB-A port, and one USB-C port</li> <li>10' Power cord</li> </ul>

**Standard Textile & Finish Selection**

	<a href="http://carolina.ofs.com/resources/textiles">http://carolina.ofs.com/resources/textiles</a> <a href="http://carolina.ofs.com/resources/finishes">http://carolina.ofs.com/resources/finishes</a>
--	--

**Frame Construction**

Seat, Back and Arms	<ul style="list-style-type: none"> <li>All rails are made up of 4/4 kiln dried WHAD Maple</li> </ul>
Exposed Wood	<ul style="list-style-type: none"> <li>Parts are made up of 6/4 kiln dried European beech</li> </ul>
Seatboard	<ul style="list-style-type: none"> <li>Plywood seat 21 3/4" x 20 5/16" x 3/4"</li> </ul>
Backboard	<ul style="list-style-type: none"> <li>21 3/4" x 17 5/8" x 3/4" plywood</li> </ul>
Assembly	<ul style="list-style-type: none"> <li>Joints on units are assembled using glue, dowels and narrow crown staples</li> </ul>

**Foam**

Seat	<ul style="list-style-type: none"> <li>Bonded glue seat: 5" thick, 2.5 lb density, 25 compression</li> <li>Front seat rail: 1.5 lb density, 45 compression</li> <li>Arms: 1.5 lb density, 45 compression</li> <li>Back panel: 1.5 lb density, 45 compression</li> </ul>
Back	<ul style="list-style-type: none"> <li>All foam is premium grade and fire retardant</li> <li>Bonded glue front back: 1.8 lb density , 20 compression</li> <li>Bonded glue rear back: 1.8 lb density, 20 compression</li> <li>False in back: 1.5 lb density, 45 compression</li> <li>Outside back: 1.5 density, 45 compression</li> </ul>