


High mesh back task 115017

| | | | |
|----------------------------|-------------------------------------|-------------------|-------------------|
| Overall dimensions | 26.5"w x 25"d x 42/46.75"h | Weight | 40 lbs. |
| Seat dimensions | 19.5"w x 17.25/19.25"d x 18/21.75"h | Cubic feet | 22 built 15 KD |
| Seat to top of back | 24" | COM | .75 yd. |
| Back width | 19" | | |
| Top of arm to floor | 23.75/31.75" | | |
| Top of arm to seat | 5.75/10" | | |



| Standard features | Options available |
|---|---|
| <ul style="list-style-type: none"> • High back • Mesh back • 4d arms • Molded seat foam • Integrated lumbar adjustment • Advanced syncro tilt with seat slide • Knocked down • ANSI/BIFMA X5.1 Conformant • CAL TB 117-2013 Conformant | <ul style="list-style-type: none"> • Carbon, Chalk or Graphite frame • Matching or contrasting seat and back • Five mesh colors • Carbon, Chalk or Graphite nylon base • Hard or soft wheel casters • Fully assembled chair in carton |

Standard textile selection

<https://ofs.com/resources/textiles>

Frame construction

| | |
|------------|---|
| Seat | <ul style="list-style-type: none"> • Injection molded, glass reinforced nylon resin |
| Back | <ul style="list-style-type: none"> • Injection molded, glass reinforced nylon resin • Integrated back height adjustment • Adjustable lumbar support |
| Upholstery | <ul style="list-style-type: none"> • Back: 100% polyester fabric on the back is available in 5 colors • Seat: Available with seat fabric matching the back or specified accent textile |
| Arms | <ul style="list-style-type: none"> • Height adjustable with 4D pivoting arm pads • Arm pads on Carbon finished arms will be Carbon • Arm pads on Graphite and Chalk finished arms will be Graphite |
| Control | <ul style="list-style-type: none"> • Advanced synchro tilt with integrated seat slider |
| Base | <ul style="list-style-type: none"> • 5 star Injection molded, glass reinforced nylon resin |
| Cylinder | <ul style="list-style-type: none"> • Class 4 gas cylinder provides height adjustment of 4.75" |
| Casters | <ul style="list-style-type: none"> • Twin wheel casters manufactured of injection molded nylon resin • 60mm diameter hoodless design |
| Assembly | <ul style="list-style-type: none"> • Self locking, hardened steel, hex/Phillips head bolts |

Foam

| | |
|------|--|
| Seat | <ul style="list-style-type: none"> • Molded foam with a density of 3 pounds per cubic foot • CAL TB 117-2013 compliant |
|------|--|