

# Specifications

## Tandem

300146

### Application

Walls

### Characteristics

Content: 43% Cotton, 29% Rayon, 17% Acrylic, 7% Polyester, 4% Linen

Finish: None

Backing: Paper

Width: 54" (137cm)

Repeat: 26" V, 27" H

(66cm V, 69cm H)

Bolt Size: 36 yards (33 m)

Weight: 20 oz/ly (600 gr/lm)

Traffic: Low Traffic

Country of Origin: Belgium

Note on Mold: Intended for use in buildings designed and maintained to avoid moisture on or within walls.

Application must conform to current Installation Guidelines included in each shipment or available at [maharam.com](http://maharam.com).

### Price

Contact your sales representative for pricing.

### Maintenance

X-Vacuum or brush lightly to remove surface dust.

### Testing

Flammability: ASTM E84 Adhered\*

\*passes with additional treatment

Lightfastness: AATCC 16.3, 40+ hours



Specifications  
Tandem  
300146

**Knoll Textiles**

**Environmental**

Greenguard Gold Certified  
LBC Red List Free  
Contains Bio-Based Content  
FR Free  
Free of Intentionally Added PFAS

**Warranty**

1 year.

© 2018 Knoll, Inc.

Complete product information at [knolltextiles.com](http://knolltextiles.com)  
800.645.3943



001 Icecap



002 Vapor



003 Ghost



004 Frequency



005 Urchin