

# EN PLEIN AIR

## FlexFORM FREE™ Resilient

Resilient Tile

### GENERAL

**Construction**

High Performance PVC-Free Tile

**Finish**

ProGuard MAX™ Coating

**Overall /Wear Layer Thickness**

2.5 mm/20 mil

**Edge Profile**

Square

### PERFORMANCE

**Critical Radiant Flux (ASTM E648)**

Pass - Class I

**Smoke Density (ASTM E662)**

Pass - ≤ 450

**Resistance to Heat (ASTM F1514)**

Pass

**Resistance to Light (ASTM F1515)**

Pass

**Resistance to Chemicals (ASTM F925)**

Pass

**Static Coefficient of Friction (ASTM D2047)**

Pass

**Dynamic Coefficient of Friction (ANSI A137)**

Pass

### CERTIFICATIONS


**Declare.**

**M/PACT™**  
CARBON NEUTRAL PROGRAM


### TILE/PLANK SIZE

**Tile/Plank Size**

Bristle / Brushstroke: 6" x 48"

Goauche: 12" x 24"

### SHIPPING

**Pieces Per Box**

6" x 48" planks: 24

12" x 24" tiles: 24

**Weight Per Box**

6" x 48" planks: 36.5 lb (16.56 kg)

12" x 24" tiles: 36.5 lb (16.56 kg)

**Quantity Per Box**

6" x 48" planks: 48.05 ft² (4.46 m²)

12" x 24" tiles: 48.05 ft² (4.46 m²)

**Quantity Per Pallet/Container**

6" x 48" planks:

60 cartons/pallet 2,882.88 ft²

18 pallets/container 51,891.84 ft²

12" x 24" planks:

60 cartons/pallet 2,882.88 ft²

18 pallets/container 51,891.84 ft²

### INSTALLATION

**Installation**

Glue Down

**Recommended Installation Methods**

Random, Herringbone

### ADHESIVES

For more information on our adhesive options, please visit our website.

See installation instructions for more information on adhesive use.

### WARRANTIES

22 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions