

DESIGNED FOR SENIOR LIVING

Majesty (Moisture-Bloc)

Broadloom

Construction

Tufted, Cut Pile

Broadloom Width

13'6" (4.11 m)

Yarn Type

XTI Continuous Filament Nylon Type 6,6

Stain Resist / Soil Release

StainSmart®

Dye Method

DDI (Digital Dye Infusion)

Tufted Face Weight

32 oz/yd² (1,085.0 g/m²)

Gauge

1/10

Stitches Per Inch

11.3

Tufts

113/in² (1,750/100 cm²)

Finished Pile Height

0.23" (5.84 mm)

Average Density (Finished)

5,009

Standard Backing

Moisture-Bloc™ Attached Cushion

Available with Cushion-Loc™ attached cushion

Nominal Total Thickness

0.44" (11.2 mm)

Nominal Total Weight

98.0 oz/yd² (3,323 g/m²)

Flammability (Radiant Panel ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or ASTM-E-662)

≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859)

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, DDI (Digital Dye Infusion)

Texture Appearance Retention Rating (TARR)

Heavy Traffic End-Use Applications

Recommended Maintenance

MilliCare® Textile and Carpet Care Service Network

Indoor Air Quality—CRI Green Label Plus™

WARRANTIES

10 Year Face Fiber Wear

10 Year Delamination of Backing

10 Year Antistatic

10 Year Edge Ravel

5 Year Matting and Crushing

10 Year Tuft Bind

Lifetime Staining/Soiling (StainSmart®)

10 Year Colorfastness

Flammability



Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.