

# METRO PARK LVT

## RIGIDFORM™ LVT

Luxury Vinyl Tile

### Construction

High Performance Rigid Core Tile

### Finish

ProGuard™ Coating

### Wear Layer Thickness

22 mil (0.56 mm)

### Overall Thickness

6.2 mm (0.244")

### Integrated Pad

1.2 mm IXPE pad

### Edge Profile

Micro Bevel, with secure locking mechanism

### Critical Radiant Flux (ASTM E648)

Pass - Class I

### Smoke Density (ASTM E662)

Pass - ≤ 450

### Flexibility (ASTM F137)

Pass

### Heat Stability by Color Change (ASTM F1514)

Pass

### Light Stability (ASTM F1515)

Pass

### Static Coefficient of Friction (ASTM D2047)

Pass

### Dimensional Stability (ASTM F2199)

Pass

### Resistance to Chemicals (ASTM F925)

Pass

### Static Load Limit (ASTM F970)

Pass

### Installation

Floating floor

### Tile Sizes

7" x 48"

18" x 36"

### Pieces Per Box

7" x 48": 9

18" x 36": 5

### Weight Per Box

7" x 48": 45.5 lb (20.62 kg)

18" x 36": 48.7 lb (22.09 kg)

### Quantity Per Box

7" x 48": 21.7 ft<sup>2</sup> (2.02 m<sup>2</sup>)18" x 36": 23.35 ft<sup>2</sup> (2.17 m<sup>2</sup>)

### Recommended Installation Method

Ashlar, Random

### Warranty

15 Year Limited Commercial Wear Warranty

### WARRANTIES

15 Year Limited Commercial Wear

1 Year Manufacturing Defect Warranty

See warranty document for full details of terms and conditions.

### ADHESIVE

For more information on our adhesive options, please visit our website.

See installation instructions for more information on adhesive use.



**Declare.**

